

ADD = Added chart, REV = Revised chart, DEL = Deleted chart.

No revision activity since Disc 22-2010

TERMINAL CHART NOTAMs

No Chart NOTAMs for Airport EEPU

General Info

Parnu, EST

N 58° 25.1' E 24° 28.4' Mag Var: 5.6°E

Elevation: 47'

Public, IFR, Customs, Landing Fee, Jet Starting Unit available

Time Zone Info: GMT+2:00 uses DST

Runway Info

Runway 03-21 8136' x 148' concrete

Runway 03 (29.0°M) TDZE 21'

Lights: Edge, ALS

Runway 21 (209.0°M) TDZE 47'

Lights: Edge, ALS

Communications InfoParnu Information **135.3** AFIS**Notebook Info**

EPU/EPU


Apt Elev **47'**
 N58 25.1 E024 28.4

JEPPesen

1 JAN 10 **(10-9)**

PARNU, ESTONIA

PARNU



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond		
03	HIRL (60m) HIALS PAPI-L (angle 3.0°)	RVR		1	148'
21					45m

1 TAKE-OFF RUN AVAILABLE

RWY 03:

From rwy head 8136' (2480m)
 twy B int 6004' (1830m)

RWY 21:

From rwy head 8136' (2480m)
 twy C int 5413' (1650m)

Standard

TAKE-OFF 1

	All Rwys		
	LVP must be in Force	RCLM (DAY only) or RL	NIL (DAY only)
A			
B	250m	400m	500m
C			
D	300m		

1 Operators applying U.S. Ops Specs: CL required below 300m.



EPU/EPU
PARNU

JEPPesen
1 JAN 10 **(13-1)**

PARNU, ESTONIA
VOR DME Rwy 03

BRIEFING STRIP

*PARNU Information				
135.3				
VOR PRN 115.9	Final Apch Crs 025°	Minimum Alt Refer to chart 13-1A	DA(H) Refer to chart 13-1A	Apt Elev 47' RWY 21'
Alt Set: hPa (MM on req) Rwy Elev: 1 hPa Trans level: By ATC Trans alt: 5000'				
Procedure based on MAX 240 KT.				




EPU/EPU
PARNU

JEPPESEN
1 JAN 10 **(13-1A)**


PARNU, ESTONIA
VOR DME Rwy 03

BRIEFING STRIP

*PARNU Information					
135.3					
VOR PRN 115.9	Final Apch Crs 025°	Minimum Alt D6.3 1900' (1879')	DA(H) 410' (389')	Apt Elev 47' RWY 21'	1700' MSA PRN VOR
MISSED APCH: Climb on R-025 to 1900', then turn LEFT to VOR to join holding.					
Alt Set: hPa (MM on req) Rwy Elev: 1 hPa Trans level: By ATC Trans alt: 5000' Procedure based on MAX 240 KT.					



PRN DME	5.0	4.0	3.0	2.0
ALTITUDE	1510'	1190'	880'	560'



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI	1900' on 115.9 PRN R-025 LT
Descent angle	3.00°	372	478	531	637	743		
MAP at VOR								


Standard			CIRCLE-TO-LAND		
STRAIGHT-IN LANDING RWY 03			Not authorized East of airport		
DA(H) 410' (389')					
ALS out		Max Kts	MDA(H)	VIS	
A	RVR 1500m	100	530' (509')	1500m	
B	RVR 1500m	135	550' (529')	1600m	
C	RVR 1600m	180	760' (739')	2400m	
D	RVR 1600m	205	760' (739')	3600m	

1 Circling height based on rwy 03 thresh elev of 21'.

EEPU/EPU
PARNU

JEPPESEN
1 JAN 10 (13-2)

PARNU, ESTONIA
VOR DME Rwy 21



CHANGES: Information Frequency.

© JEPPESEN, 2004, 2010. ALL RIGHTS RESERVED.


EEPU/EPU
PARNU

JEPPESEN
1 JAN 10 **(13-2A)**


PARNU, ESTONIA
VOR DME Rwy 21

BRIEFING STRIP

*PARNU Information					
135.3					
VOR PRN 115.9	Final Apch Crs 212°	Minimum Alt D6.6 1900' (1853')	DA(H) 460' (413')	Apt Elev 47' RWY 47'	1700' MSA PRN VOR
MISSED APCH: Climb on R-212 to 1900', then turn RIGHT to VOR to join holding.					
Alt Set: hPa (MM on req) Rwy Elev: 2 hPa Trans level: By ATC Trans alt: 5000'					
Procedure based on MAX 240 KT.					



PRN DME	3.0	4.0	5.0
ALTITUDE	760'	1080'	1390'



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI	1900' on PRN 115.9 R-212 RT	PRN 115.9
Descent angle	3.00°	372	478	531	637	743			
MAP at VOR									

Standard				CIRCLE-TO-LAND			
STRAIGHT-IN LANDING RWY 21				Not authorized East of airport			
DA(H) 460' (413')							
				Max Kts	MDA(H)	VIS	
A B C D	RVR 1200m	ALS out		100	530' (483')	1500m	
		RVR 1500m		135	550' (503')	1600m	
		RVR 1900m		180	760' (713')	2400m	
				205	760' (713')	3600m	

PANS OPS

EEPU/EPU
PARNU

JEPPESEN
1 JAN 10 **(16-2)**


PARNU, ESTONIA
2 NDB Rwy 21

BRIEFING STRIP


*PARNU Information				
135.3				
Lctr RC *425	Final Apch Crs 209°	Minimum Alt RC Lctr 1570' (1523')	DA(H) 460' (413')	Apt Elev 47' RWY 47'
MISSED APCH: Climb on track 209° to 1900', then turn RIGHT to RC Lctr to join holding.				
Alt Set: hPa (MM on req) Rwy Elev: 2 hPa Trans level: By ATC Trans alt: 5000'				
Procedure based on MAX 240 KT.				

1700'

MSA RC Lctr



PRN DME	3.0	4.0	5.0
ALTITUDE	740'	1060'	1380'



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI 1900' ↑ on 209° RC 425 RT
Descent angle	3.00°	372	478	531	637	743	
MAP at R Lctr							

Standard				Circle-to-Land			
STRAIGHT-IN LANDING RWY 21				Not authorized East of airport			
DA(H) 460' (413')							
				Max Kts	MDA(H)	VIS	
A B C D	RVR 1200m		ALS out	100	530' (483')	1500m	
			RVR 1500m	135	550' (503')	1600m	
	RVR 1200m		RVR 1900m	180	760' (713')	2400m	
				205	760' (713')	3600m	

PANS OPS