

ADD = Added chart, REV = Revised chart, DEL = Deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
-----	-----------------	-------	----------	----------

No revision activity since Disc 22-2010

TERMINAL CHART NOTAMs

No Chart NOTAMs for Airport EYPA

EYPA (Palanga Intl)**General Info**

Palanga, LTU

N 55° 58.4' E 21° 05.6' Mag Var: 4.0°E

Elevation: 33'

Public, IFR, Control Tower, Customs, Landing Fee

Fuel: 100LL, Jet A-1

Time Zone Info: GMT+2:00 no DST

Runway Info

Runway 01-19 7480' x 148' asphalt

Runway 01 (9.0°M) TDZE 33'

Lights: Edge, ALS, Centerline, REIL

Displaced Threshold Distance 492'

Runway 19 (189.0°M) TDZE 33'

Lights: Edge, ALS, Centerline, REIL, TDZ


Displaced Threshold Distance 492'

Communications InfoATIS **127.8**Palanga Tower **118.3**Palanga Approach Control **128.0**Palanga Approach Control **124.3** At or below 19500' TCAPalanga Radar **128.0**Palanga Radar **126.1****Notebook Info**

EYPA/PLQ
PALANGA INTL

JEPPESSEN
 13 AUG 10 **10-2** **Eff 26 Aug**

PALANGA, LITHUANIA
RNAV STAR



EYPA/PLQ
PALANGA INTL

13 AUG 10

JEPPESEN

10-2A

Eff 26 Aug

PALANGA, LITHUANIA

RNAV STAR

MANUX 2C [MANU2C]
TIRIN 2C [TIRI2C]
VALUV 2C [VALU2C]
XARIN 2C [XARI2C]

RWY 19 RNAV ARRIVALS
 RNAV (GNSS)
DEEP S MAX 250 KT BELOW FL100

STAR ROUTING

STAR	ROUTING
MANUX 2C ①	MANUX (FL110+) - PA202 (FL75+) - NAPUS (3000'; K230-).
TIRIN 2C	TIRIN - PLG (5000'+) - PA204 - NAPUS (3000'; K230-).
VALUV 2C	VALUV (FL110+) - PA201 (FL75+) - PLG (5000'+) - PA204 - NAPUS (3000'; K230-).
XARIN 2C	XARIN (FL110+) - PA203 (FL75+) - NAPUS (3000'; K230-).

① During activity of SPECIAL GLIDER ZONE KARTENA expect FL restriction by ATC.

MANUX 2C
 D33.9 PLG
 N56 12.9 E021 58.9
 (KLA R-035/D39)
 At or above FL110

TIRIN 2C
 D13.2 PLG
 N56 04.0 E020 44.9
 D27 318°

VALUV 2C
 D36 PLG
 N55 41.5 E020 08.0
 At or above FL110

XARIN 2C
 D33.9 PLG
 N56 09.0 E021 42.4
 At or above FL75

PA201
 D24.9 PLG
 N55 46.5 E020 25.6
 At or above FL75

PA202
 D25.4 PLG
 N55 48.3 E021 47.3
 At or above FL75

PA203
 D23.9 PLG
 N56 09.0 E021 42.4
 At or above FL75

PA204
 D6.9 PLG
 N55 59.3 E021 17.0

PA205
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA206
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA207
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA208
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA209
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA210
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA211
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA212
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA213
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA214
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA215
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA216
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA217
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA218
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA219
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA220
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA221
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA222
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA223
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA224
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA225
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA226
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA227
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA228
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA229
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA230
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA231
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA232
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA233
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA234
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA235
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA236
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA237
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA238
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA239
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA240
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA241
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA242
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA243
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA244
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA245
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA246
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA247
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA248
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA249
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA250
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA251
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA252
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA253
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA254
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA255
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA256
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA257
 D11.1 PLG
 N55 57.4 E021 05.2
 At or above 5000'

PA

CHANGES: New chart.


© JEPPESEN, 2010. ALL RIGHTS RESERVED.

EYPA/PLQ
PALANGA INTL

JEPPESSEN
13 AUG 10 **10-2B** Eff 26 Aug

PALANGA, LITHUANIA

STAR



CHANGES: New chart.

© JEPPESSEN, 2010. ALL RIGHTS RESERVED.

EYPA/PLQ
PALANGA INTL

13 AUG 10

10-3

Eff 26 Aug

PALANGA, LITHUANIA


SID

*PALANGA Approach
124.3

Apt Elev
33'

Trans level: By ATC Trans alt: 5000'

1. Contact PALANGA Approach when passing 1000'.
2. Noise abatement procedures should be applied according to ICAO DOC 8168, VOL I, Section 7.




EYPA/PLQ
PALANGA INTL

JEPPESSEN
13 AUG 10 **(10-3A)** **Eff 26 Aug**

PALANGA, LITHUANIA

SID



EYPA/PLQ


Apt Elev **33'**
N55 58.4 E021 05.6

JEPPESSEN

13 AUG 10 **(10-9)** Eff 26 Aug

PALANGA, LITHUANIA

PALANGA INTL



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
01	HIRL ① CL ② HIALS REIL PAPI-L(3.0°) RVR	6988' 2130m	6016' 1834m		148' 45m
19	HIRL ① CL ② HIALS-II TDZ REIL PAPI-L(3.0°) RVR				

① 60m spacing. ② 30m spacing.

LOW VISIBILITY PROCEDURES (LVP)

- LVP are established for take-off only when RVR value limitation is from 350m till 250m.
- The status of LVP is passed to pilots by means of ATIS broadcast or RTF:
"Low Visibility Take-off Procedures are in force".
- During LVP the following shall be executed:
 - a) only one aircraft is allowed on the manoeuvring area at the time and no vehicle movements;
 - b) movements of an aircraft will be conducted with accompanying Follow-me car O/R only.
- LVP is cancelled when RVR is 450m with increasing tendency.

Standard TAKE-OFF ① & DEPARTURE PROCEDURE

	LVP must be in force			
	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL
A	250m	250m	400m	500m
B				
C				
D				

① Operators applying U.S. Ops Specs: CL required below 300m.

OMNIDIRECTIONAL DEPARTURE PROCEDURE

- RWY 01:** Climb STRAIGHT AHEAD with 400'/NM (6.6%) to turning alt 500'. Continue climb to appropriate MSA.
- RWY 19:** Climb STRAIGHT AHEAD with 400'/NM (6.6%) to turning alt 500'. Continue climb to appropriate MSA.

EYPA/PLQ **JEPPESEN**

13 AUG 10

(10-9X)**Eff 26 Aug****PALANGA, LITHUANIA**
PALANGA INTL**JAA MINIMUMS**

STRAIGHT-IN RWY		A	B	C	D
01	RNAV	520' (487')	520' (487')	520' (487')	520' (487')
		R1400m	R1500m	R1600m	R1800m
	<i>ALS out</i>	R1500m	R1500m	R2000m	R2000m
	NDB	520' (487')	520' (487')	520' (487')	520' (487')
		R1400m	R1500m	R1600m	R1800m
	<i>ALS out</i>	R1500m	R1500m	R2000m	R2000m
19	ILS	280' (247')	280' (247')	280' (247')	280' (247')
		R600m	R600m	R600m	R600m
	<i>ALS out</i>	R1000m	R1000m	R1000m	R1000m
	LOC	470' (437')	470' (437')	470' (437')	470' (437')
		R900m	R1000m	R1000m	R1400m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R2000m
	RNAV	520' (487')	520' (487')	520' (487')	520' (487')
		R1000m	R1200m	R1200m	R1600m
	<i>ALS out</i>	R1500m	R1500m	R2000m	R2000m
	NDB	520' (487')	520' (487')	520' (487')	520' (487')
		R1000m	R1200m	R1200m	R1600m
	<i>ALS out</i>	R1500m	R1500m	R2000m	R2000m

CIRCLE-TO-LAND	100 KT	135 KT	180 KT	D
	470' (437') ❶	760' (727')	880' (847')	NOT AUTHORIZED
	V1500m	V1600m	V2400m	

❶ After RNAV/NDB 01/19: MDA(H) 520' (487').

TAKE-OFF RWY 01, 19


LVP must be in force			
RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
A B C D	250m	400m	500m
	300m		


EYPA/PLQ PALANGA INTL

JEPPesen
13 AUG 10 **(11-1)** Eff 26 Aug


PALANGA, LITHUANIA ILS or LOC Rwy 19


BRIEFING STRIP

*ATIS 127.8		*PALANGA Approach 124.3		*PALANGA Tower 118.3		*Ground 131.5	
LOC IAN *110.1	Final Apch Crs 189°	GS D3.0 IAN 1040' (1007')	ILS DA(H) 280' (247')	Apt Elev 33' RWY 33'			
MISSED APCH: Climb on track 189° to 2000'. Radar vectors provided. MISSED APCH WITH COMM FAILURE: Climb on track 189° to 1800', then turn RIGHT to NDB climbing to 2000'.							
Alt Set: hPa		Rwy Elev: 1 hPa		Trans level: By ATC			
MSA PN NDB							



LOC (GS out)	IAN DME	2.0	3.0
	ALTITUDE	720'	1040'



Gnd speed-Kts	70	90	100	120	140	160	
ILS GS or LOC Descent angle 3.00°	377	484	538	646	753	861	
MAP at D1.1 IAN/D2.7 PLG							

PANS OPS	STRAIGHT-IN LANDING RWY 19					CIRCLE-TO-LAND		
	ILS			LOC (GS out)				
	DA(H) 280' (247')			DA(H) 470' (437')				
	FULL	Limited	ALS out	ALS out		Max Kts	MDA(H)	VIS
A						100	470' (437')	2000m
B						135	760' (727')	2000m
C	RVR 550m	RVR 750m	RVR 1300m	RVR 1300m	RVR 2000m	180	880' (847')	2400m
D							NOT AUTHORIZED	



EYPA/PLQ
PALANGA INTL

JEPPESSEN
13 AUG 10 (12-1) Eff 26 Aug


PALANGA, LITHUANIA
RNAV (GNSS) Rwy 01

BRIEFING STRIP

*ATIS	*PALANGA Approach	*PALANGA Tower	*Ground
127.8	124.3	118.3	131.5
RNAV	Final Apch Crs 009°	Minimum Alt PA301 1800' (1767')	LNAV DA(H) 520' (487')
		Apt Elev 33' RWY 33'	
MISSED APCH: Climb on track 009° to 2000', at D5.0 turn RIGHT on track 099°. Radar vectors provided. MISSED APCH WITH COMM FAILURE: Climb on track 009° to 1700', at D5.0 turn RIGHT to NDB climbing to 2000'.			
Alt Set: hPa	Rwy Elev: 1 hPa	Trans level: By ATC	Trans alt: 5000'



DIST to RW01	5.0	4.0	3.0	2.0
ALTITUDE	1680'	1360'	1040'	720'



TO DISPL THRESH	9.4	4.0	5.4	2.4	3.0	0
Gnd speed-Kts	70	90	100	120	140	160
Descent angle	3.00°	372	478	531	637	743
MAP at RW01						

Standard

STRAIGHT-IN LANDING RWY 01

LNAV

DA(H) **520'** (487')

ALS out

PANS OPS

A	RVR 1500m	
B		
C	RVR 1800m	CMV 2300m
D		

EYPA/PLQ PALANGA INTL


JEPPESSEN

13 AUG 10 (12-2) Eff 26 Aug


PALANGA, LITHUANIA RNAV (GNSS) Rwy 19

BRIEFING STRIP™

*ATIS		*PALANGA Approach		*PALANGA Tower		*Ground	
127.8		124.3		118.3		131.5	
RNAV	Final Apch Crs 189°	Minimum Alt PA401 1300' (1267')	LNAV DA(H) 520' (487')	Apt Elev 33'	1700' 090° → ← 270° 1800' MSA PN NDB		
MISSED APCH: Climb on track 189° to 2000'. Radar vectors provided.							
MISSED APCH WITH COMM FAILURE: Climb on track 189° to 1800', then turn RIGHT to NDB climbing to 2000'.							
Alt Set: hPa		Rwy Elev: 1 hPa		Trans level: By ATC		Trans alt: 5000'	



DIST to RW19	2.0	3.0
ALTITUDE	720'	1040'



Gnd speed-Kts	70	90	100	120	140	160		2000' ↑ on 189°
Descent angle	3.00°	372	478	531	637	743		
MAP at RW19								

Standard

STRAIGHT-IN LANDING RWY 19

LNAV

DA(H) **520'** (487')

ALS out

PANS OPS

A	RVR 1500m	RVR 1500m	
B			
C		CMV 2300m	
D			


EYPA/PLQ
PALANGA INTL

JEPPESSEN
13 AUG 10 (16-2) Eff 26 Aug


PALANGA, LITHUANIA
NDB Rwy 19

BRIEFING STRIP™

*ATIS		*PALANGA Approach		*PALANGA Tower		*Ground	
127.8		124.3		118.3		131.5	
NDB PN *407	Final Apch Crs 189°	Minimum Alt D5.3 1300' (1267')	DA(H) 520' (487')	Apt Elev 33' RWY 33'	1700' 090° → ← 270° 1800' MSA PN NDB		
MISSED APCH: Climb on track 189° to 2000'. Radar vectors provided.							
MISSED APCH WITH COMM FAILURE: Climb on track 189° to 1800', then turn RIGHT to NDB climbing to 2000'.							
Alt Set: hPa		Rwy Elev: 1 hPa		Trans level: By ATC		Trans alt: 5000'	



PLG DME	3.0	4.0	5.0
ALTITUDE	560'	880'	1200'



Gnd speed-Kts	70	90	100	120	140	160	
Descent angle 3.05°	378	486	540	648	755	863	
MAP at D2.9							

Standard		STRAIGHT-IN LANDING RWY 19		CIRCLE-TO-LAND	
		DA(H) 520' (487')			
		ALS out		Max Kts	
A	RVR 1500m	CMV 2300m	100	MDA(H) 520' (487')	VIS 2300m
B			135	760' (727')	2300m
C			180	880' (847')	2400m
D			NOT AUTHORIZED		