

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UBBQ

Terminal Charts For UBBQ

Revision Letter For Cycle 08-2012

Change Notices

Notebook

General Information

Location: Gabala Aze
IATA Code:
Lat/Long: N40° 48.5' E047° 43.5'
Elevation: 1129 ft

Airport Use: Public
Magnetic Variation: 6.0°E

Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0204 Z
Sunset: 1533 Z,

Runway Information



Runway: 16
Length x Width: 11417 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 1129 ft
Lighting: Edge, ALS, Centerline, TDZ
Stopway: 197 ft


Runway: 34
Length x Width: 11417 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 1116 ft
Lighting: Edge, ALS, Centerline, TDZ
Stopway: 197 ft

Communication Information

ATIS 135.1
Gabala Tower 133.9
Gabala Tower 130.9


Alt set: hPa (MM on request)
Trans level: FL60 Trans alt: 4000'






Apt Elev
1129'

Trans level: FL60 Trans alt: 4000'



ADEKI 1A [ADEK1A]
BEKIR 1A [BEK11A]
GIPAR 1A [GIPA1A]
RWY 16 DEPARTURES



HOLDING OVER
QBL




Gnd speed-KT	75	100	150	200	250	300
3.7% V/V (fpm)	281	375	562	749	937	1124

SID	ROUTING
ADEKI 1A	Climb on 162° track to at or above 2500', turn RIGHT to QBL, enter holding, leave at FL110, turn LEFT, QBL R-298 to ADEKI, climbing to assigned FL.
BEKIR 1A	Climb on 162° track to at or above 2500', turn RIGHT to QBL, enter holding, leave at FL170, turn RIGHT, QBL R-025 to BEKIR, climbing to assigned FL.
GIPAR 1A	Climb on 162° track to at or above 2500', turn RIGHT to QBL, enter holding, leave at FL170, turn LEFT, QBL R-341 to GIPAR, climbing to assigned FL.

Trans level: FL60 Trans alt: 4000'

Diagram of a VOR station showing radial and bearing information. The station is labeled "MSA QBL VOR". The diagram shows a circle with a central point. Four radial lines extend from the center to the circumference, labeled with bearings: 120°, 240°, 305°, and 065°. Four distances are indicated along these radials: 15,700' (top), 12,400' (right), 3400' (bottom), and 3900' (left). Arrows point from the distances to the center.




Gnd speed-KT	75	100	150	200	250	300
3.7% V/V (fpm)	281	375	562	749	937	1124


SID	ROUTING
ED 1A	Climb on 162° track to at or above 2500', turn RIGHT to QBL, enter holding, leave at FL60, turn RIGHT, QBL R-236 to ED, climbing to assigned FL.
LUSAL 1A	Climb on 162° track to at or above 2500', turn RIGHT to QBL, enter holding, leave at FL60, turn LEFT, QBL R-140 to LUSAL, climbing to assigned FL.

Apt Elev
1129'

Trans level: FL60 Trans alt: 4000'



ADEKI 1B [ADEK1B]
BEKIR 1B [BEK11B]
GIPAR 1B [GIPA1B]
RWY 34 DEPARTURES




Gnd speed-KT	75	100	150	200	250	300
3.5% V/V (fpm)	266	354	532	709	886	1063




SID	ROUTING
ADEKI 1B	Climb on 342° track to at or above 2500', turn LEFT to QBL, enter holding, leave at FL110, turn LEFT, QBL R-298 to ADEKI, climbing to assigned FL.
BEKIR 1B	Climb on 342° track to at or above 2500', turn LEFT to QBL, enter holding, leave at FL170, turn RIGHT, QBL R-025 to BEKIR, climbing to assigned FL.
GIPAR 1B	Climb on 342° track to at or above 2500', turn LEFT to QBL, enter holding, leave at FL170, turn LEFT, QBL R-341 to GIPAR, climbing to assigned FL.

Apt Elev
1129'


Trans level: FL60 Trans alt: 4000'



ED 1B
LUSAL 1B [LUSA1B]
RWY 34 DEPARTURES



HOLDING OVER
QBL



Gnd speed-KT	75	100	150	200	250	300
3.5% V/V (fpm)	266	354	532	709	886	1063

SID

ROUTING

ED 1B

Climb on 342° track to at or above 2500', turn LEFT to QBL, enter holding, leave at FL60, turn RIGHT, QBL R-236 to ED, climbing to assigned FL.


LUSAL 1B

Climb on 342° track to at or above 2500', turn LEFT to QBL, enter holding, leave at FL60, turn LEFT, QBL R-140 to LUSAL, climbing to assigned FL.

UBBQ
Apt Elev 1129'
N40 48.5 E047 43.5

JEPPESEN
2 MAR 12 (10-9)

GABALA, AZERBAIJAN
GABALA



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS				WIDTH
		Threshold	Landing Beyond	Glide Slope	TAKE-OFF	
16	HIRL (60m) CL (30m) HIALS-II TDZ PAPI-L (3.0°) RVR					148'
34	HIRL (60m) CL (30m) HIALS-II TDZ PAPI-L (3.5°) RVR			10,445' 3184m		45m

START-UP PROCEDURE

The parking position, QNH value and designator of latest received ATIS broadcast shall be reported in the initial call.


JAR-OPS


TAKE-OFF 1

	All Rwys				
	LVP must be in force				
	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
A					
B	150m	200m	250m	400m	500m
C					
D	200m	250m	300m		

1 Operators applying U.S. Ops Specs: CL required below 300m.

© JEPPESEN, 2012. ALL RIGHTS RESERVED.





GABALA, (GABALA - UBBQ)

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UBBQ