

List of pages in this Trip Kit

Trip Kit Index

Airport Information For GCTS

Terminal Charts For GCTS

Revision Letter For Cycle 08-2013

Change Notices

Notebook

General Information

Location: Tenerife-South Xje
IATA Code: TFS
Lat/Long: N28° 02.7' W016° 34.3'
Elevation: 209 ft

Airport Use: Public
Magnetic Variation: 5.7°W

Fuel Types: Jet A-1
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0642 Z
Sunset: 1931 Z,

Runway Information

Runway: 08
Length x Width: 10499 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 188 ft
Lighting: Edge, ALS, Centerline

Runway: 26
Length x Width: 10499 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 209 ft
Lighting: Edge, ALS, Centerline

Communication Information

ATIS 118.675
Tenerife-South Clearance Tower 121.75
Tenerife-South Tower 121.9
Tenerife-South Tower 119.0
Tenerife-South Tower 25.78 Military
Tenerife-South Approach Control 127.7
Tenerife-South Approach Control 119.7 Secondary

1. GENERAL

1.1. ATIS

ATIS 118.67

1.2. NOISE ABATEMENT PROCEDURES**1.2.1. RUN-UP TESTS**

Engine tests higher than idle regime are forbidden between 0000-0600LT.

Exceptions are allowed only, if it is essential for ACFTs return to the origin APT, or when the planned and cleared flight takes off between 0400-0600LT.

Clearance for engine testing must be requested to the operations centre (CEOPS).

1.3. LOW VISIBILITY PROCEDURES (LVP)**1.3.1. GENERAL**

LVP will be applied when RVR/VIS is 600m. Pilots will be informed about application of LVP by Tower or via ATIS. ATC will also inform pilots when LVP are going to be cancelled, when VIS is above 1000m and strong improvement tendency of MET conditions is expected. In case of being disoriented or in doubt, pilots will stop ACFT and immediately notify ATC.

1.3.2. DEPARTING ACFT

Pilots will notify ATC of stand position when requesting clearance for start-up.

When RVR or VIS is lower than 400m, and in case TWY CL lighting is out of service, taxiing ACFT will be guided by Follow-me car to apron exit gate, prior Tower or ACFT crew request.

When RVR or VIS is lower than 150m, and in case TWY CL lighting is out of service, it will be mandatory for ACFT to taxi with guidance of Follow-me car to the apron exit gate.

1.3.3. RWY ENTRIES

Entry to RWY 08 via TWY B-0, B-1 or B-2 only.

Entry to RWY 26 via TWY B-6 or B-7 only.

1.3.4. RWY HOLDING POINTS

For take-off, CAT I holding points must be used.

1.3.5. COMMUNICATION FAILURE FOR DEPARTING ACFT

ACFT will continue the assigned route to its ATC clearance limit, taking extreme CAUTION. Once at this point, ACFT must hold position and wait for a Follow-me car to be guided to assigned stand or holding bay.

1.4. TAXI PROCEDURES

Taxiing between holding point A2-2 and TWY B1 not allowed.

TWY B-2 MAX wingspan 167' /51m and MAX length of 184' /56m.

Apron taxilane between gates D-3 and D-5 MAX wingspan 171' /52m.

TWY B-6 MAX length of 190' /58m.

1.5. PARKING INFORMATION**1.5.1. GENERAL**

Stands F1 thru F8 equipped with visual docking guidance system.

On stands F1 thru F8, H2 thru H10, I1 thru I11A and J12 push-back required.

1.5.2. USE OF APU

Use of APU is forbidden on stands F1 thru F8 in the period between 2 min after blocks for ARR and 5 min before off-blocks for DEP.

APU will only be able to use when 400 Hz facilities and mobile units are not operative.

1.6. OTHER INFORMATION

RWY 08 right-hand circuit.

Birds.

2. ARRIVAL

2.1. NOISE ABATEMENT PROCEDURES

Landing and approach procedures on visual meteorological conditions will be performed with an angle equal to or higher than the ILS GP or PAPI of each RWY. At night time, visual approaches shall avoid overflying inhabited areas and visual approaches to RWY 26 from west via Ganta Int or TFS VORDME shall not initiate the left turn before TFS 10 DME.

2.2. RWY OPERATIONS

ACFT will report vacating RWY.

Four engined wide-bodied ACFT shall leave RWY 08 via TWY B-7 and RWY 26 via TWYB-1.

2.3. TAXI PROCEDURES

In general, taxiing between the apron gate and the stand will be carried out accompanied by Follow-me car. The supervision of this vehicle is essential for docking or parking.

2.4. OTHER INFORMATION

CAUTION: Risk of windshear on final approach.

3. DEPARTURE

3.1. START-UP & TAXI PROCEDURES

3.1.1. START-UP

Pilots will request clearance to start-up to TENERIFE-SOUTH Ground. On requesting this clearance, ACFT must be completely ready to start-up, considering that the ACFT must leave stand 10 min before the calculated take-off time.

Clearance will be issued as soon as requested. When delays are expected to exceed 15 min, ATC will provide appropriate start-up time. In that moment, ATC clearance will be issued.

3.1.2. TAXIING

Pilots will contact Tower to request permission for towing and/or taxiing.

Towed push-back is mandatory at all front stands and will be carried out in order to nose to the RWY in use with the exception of:

- ATC indicates the opposite,
- Existing engine start-up limitations, that shall be previously communicated to ATC,
- Stands F1, F5A, F8, H2, I1, I1A and I1B, where they will nose to THR 26 and stand I11A to THR 08.

Autonomous exits will be carried out using the minimum start-up engine power and in a way where making the turn, the engine power will not be higher than IDLE. Exit from stands E13, H14 and J36 will always nose to THR 08.

Push-back from stand I8 nosing to THR 08.

Exits will not be carried out from stands E28 and E29 via gate D-2, from H20 and E21 via gate D-3 and from T17 and H18 via gate D-4.

3.2. NOISE ABATEMENT PROCEDURES

Take-off

Take-off power.

Take-off flaps/slats.

Climb at $V_2 + 10$ KT to 1500' AGL.

At 1500'

Reduce to power of ascent.

Accelerate to zero flap minimum safe manoeuvring speed (VZF) + 10 KT maintaining minimum rate of climb 500'.


Retract flaps/slats as needed.


Up to FL60

Do not exceed 250 KT and continue SID in force, except ATC clearance.


ACFT taking-off from RWY 08 shall maintain RWY heading until TFS 10 DME before initiating any Right turn.

ACFT taking-off from RWY 26 and overflying TFS VORDME must not turn Right before overflying this navigation facility.



ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

KONBA FOUR GOLF
(KONBA 4G)[KONB4G]
ORTIS FOUR GOLF
(ORTIS 4G)[ORTI4G]
VIDRI FOUR GOLF
(VIDRI 4G)[VIDR4G]
RWY 08 ARRIVALS



TENERIFE-NORTH
D 117.7 TFN
(H) N28 32.2 W016 16.1

SPEED RESTRICTION

MAX 250 KT at or below FL150
within speed reduction area, except
for military aircraft or
if danger areas are active.

----- Speed Reduction Area

ARACO
N28 26.0
W017 27.1

GANTA
N28 16.5 W017 10.2
D129.0/17.6
FL70
D48.0

(IAF) BAMEL
N28 06.7 W016 52.6
D18.4
FL70
D30.4
D12.0/17.0
D

(IAF) TENERIFE-SOUTH
317 TES
N28 03.3 W016 33.8




(IAF) TENERIFE-SOUTH
D 12.0
FL70
R309°
D


(IAF) TENERIFE-SOUTH
D 116.4 TFS
(H) N28 00.1 W016 41.3


VIDRI
N26 53.7 W017 02.4
D 022.0
FL70
VIDRI 4G
D

HOLDING OVER TES

MHA FL100
MHA 6000
for NDB apch
MAX 210 KT





ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'


KONBA FOUR HOTEL
(KONBA 4H)[KONB4H]
ORTIS FOUR HOTEL
(ORTIS 4H)[ORTI4H] ●
VIDRI FOUR GOLF
(VIDRI 4G)[VIDR4G]
RWY 26 ARRIVALS


● By ATC


SPEED RESTRICTION

MAX 250 KT at or below FL150
within speed reduction area, except
for military aircraft or
if danger areas are active.


----- Speed Reduction Area


**HOLDINGS
OVER TES**




ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

KONBA THREE DELTA CHARLIE GOLF
(KONBA 3DCG) [KO3DCG]
ORTIS THREE DELTA CHARLIE GOLF
(ORTIS 3DCG) [OR3DCG]
VIDRI THREE DELTA CHARLIE GOLF
(VIDRI 3DCG) [VI3DCG]
RWY 08
CONTINUOUS DESCENT ARRIVALS (CDA)
BY ATC
USABLE BETWEEN 2300-0700LT



ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

KONBA THREE DELTA CHARLIE HOTEL
(KONBA 3DCH) [KO3DCH]
ORTIS THREE DELTA CHARLIE HOTEL
(ORTIS 3DCH) [OR3DCH]
VIDRI THREE DELTA CHARLIE GOLF
(VIDRI 3DCG) [VI3DCG]
RWY 26
CONTINUOUS DESCENT ARRIVALS (CDA)
BY ATC
USABLE BETWEEN 2300-0700LT

ORTIS
N31 24.4 W016 33.4
(265.1 NM to THR 26 IAF TFS)
(219.2 NM to THR 26 DCT FM TERFE)

KONBA
N31 18.1 W015 18.1
(272.5 NM to
THR 26 IAF TFS)
(226.5 NM to
THR 26 DCT FM TERFE)

GURKA
N30 26.0
W015 51.0
(213.4 NM to
THR 26 IAF TFS)
(167.4 NM to
THR 26 DCT FM TERFE)

BRICK
N29 35.5 W016 22.4
(156.0 NM to THR 26 IAF TFS)
(110.1 NM to
THR 26 DCT FM TERFE)


TENERIFE-NORTH
D(H) 117.7 TFS
N28 32.2 W016 16.1
(92.7 NM to THR 26 IAF TFS)
(46.7 NM to THR 26 DCT FM TERFE)

(IAF)
TENERIFE-SOUTH
D(H) 116.4 TFS
N28 00.1 W016 41.3
(38.5 NM to THR 26)

TERFE
N28 10.9 W016 07.6
(70.2 NM to THR 26 IAF TFS)
(24.2 NM to THR 26 DCT)


VIDRI
N26 53.7 W017 02.4
(107.4 NM to THR 26)




ATIS
118.67Apt Elev
209'Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.



ARACO THREE ECHO
(ARACO 3E) [ARAC3E]
ARACO THREE FOXTROT
(ARACO 3F) [ARAC3F]
RWYS 08, 26 DEPARTURES



ARACO 3E

This SID require minimum climb gradient
of
4.5% up to 1000'.

Gnd speed-KT	75	100	150	200	250	300
10.4% V/V (fpm)	790	1053	1580	2106	2633	3160
4.5% V/V (fpm)	342	456	684	911	1139	1367




Initial ATC clearance:
Maintain **FL90** await further clearance

SID	RWY	ROUTING
ARACO 3E	08	Intercept TFS R-076 to D10.0 TFS, turn RIGHT, intercept TFS R-103 inbound to TFS, TFS R-309 via GANTA to ARACO.
ARACO 3F	26	Climb on runway heading to TFS, TFS R-309 via GANTA to ARACO.

CONTINGENCY DEPARTURE

In case of one or more navaid failure following procedures shall be carried out:
These SIDs require a minimum climb gradient of 10.4% up to FL70.
Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'


1. Due to restrictions of DVOR/DME GDV, and when its coverage is not sufficient below FL150, radar vectoring guidance will be provided.
2. EXPECT close-in obstacles.

BIMBO SEVEN ECHO
(BIMBO 7E) [BIMB7E]
BIMBO FIVE FOXTROT
(BIMBO 5F) [BIMB5F]
RWYS 08, 26 DEPARTURES

SPEED RESTRICTION

MAX 250 KT at or below FL150
within speed reduction area, except
for military aircraft or
if danger areas are active.

----- Speed Reduction Area



Initial ATC clearance:
BIMBO 7E: Maintain **FL200**, await further clearance
BIMBO 5F: Cross **GANTA** at or above **FL90**, climb to **FL150**,
await further clearance


SID	RWY	ROUTING
BIMBO 7E	08	Intercept TFS R-076 to TERFE, turn LEFT, intercept TFN R-166 inbound to TFN, TFN R-023 to KASAS, turn LEFT, intercept GDV R-357 to BIMBO.
BIMBO 5F	26	Climb on runway heading to TFS, TFS R-309 to GANTA, turn RIGHT, intercept TFN R-265 inbound to TFN, TFN R-023 to KASAS, turn LEFT, intercept GDV R-357 to BIMBO.

CONTINGENCY DEPARTURE



In case of one or more navaid failure following procedures shall be carried out:
These SIDs require a minimum climb gradient of 10.4% up to FL70.
Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.



GRAN CANARIA FOUR ECHO (LPC 4E)
GRAN CANARIA FOUR FOXTROT (LPC 4F)
RWYS 08, 26 DEPARTURES



Gnd speed-KT	75	100	150	200	250	300
10.4% V/V (fpm)	790	1053	1580	2106	2633	3160
4.5% V/V (fpm)	342	456	684	911	1139	1367
4% V/V (fpm)	304	405	608	810	1013	1215

These SIDs require minimum climb gradients of

LPC 4E
4.5% up to 1000'.

LPC 4F
4% up to 1000'.

Initial ATC clearance:
Maintain **FL90** await further clearance


SID	RWY	ROUTING
LPC 4E	08	Intercept TFS R-076 to D10.0 TFS, turn RIGHT, 158° heading, intercept TFS R-120 to TOMOS, turn LEFT, intercept LPC R-207 inbound to LPC.
LPC 4F	26	Climb on runway heading to TFS 3.0 DME, turn LEFT, intercept TFS R-120 to TOMOS, turn LEFT, intercept LPC R-207 inbound to LPC.

CONTINGENCY DEPARTURE



In case of one or more navaid failure following procedures shall be carried out:
These SIDs require a minimum climb gradient of 10.4% up to FL70.
Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.





HIERRO THREE ECHO (HIE 3E)
HIERRO THREE FOXTROT (HIE 3F)
RWYS 08, 26 DEPARTURES



Gnd speed-KT	75	100	150	200	250	300
10.4% V/V (fpm)	790	1053	1580	2106	2633	3160
4.5% V/V (fpm)	342	456	684	911	1139	1367

HIE 3E
This SID require minimum climb gradient of 4.5% up to 1000'.

Initial ATC clearance: Maintain FL70 await further clearance		
SID	RWY	ROUTING
HIE 3E	08	Intercept TFS R-076 to D10.0 TFS, turn RIGHT, intercept TFS R-103 inbound to TFS, TFS R-266 to HIE.
HIE 3F	26	Climb on runway heading to TFS, TFS R-266 to HIE.
CONTINGENCY DEPARTURE		
In case of one or more navaid failure following procedures shall be carried out: These SIDs require a minimum climb gradient of 10.4% up to FL70. Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.		

Apt Elev
209'Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.**KONBA SEVEN ECHO (KONBA 7E) [KONB7E]
KONBA FIVE FOXTROT (KONBA 5F) [KONB5F]
RWYS 08, 26 DEPARTURES**

Initial ATC clearance:

KONBA 7E: Maintain **FL200**, await further clearance**KONBA 5F:** Cross GANTA at or above **FL90**, climb to **FL150**,
await further clearance

SID	RWY	ROUTING
KONBA 7E	08	Intercept TFS R-076 to TERFE, turn LEFT, intercept TFN R-166 inbound to TFN, TFN R-023 via KASAS to KONBA.
KONBA 5F	26	Climb on runway heading to TFS, TFS R-309 to GANTA, turn RIGHT, intercept TFN R-265 inbound to TFN, TFN R-023 via KASAS to KONBA.

CONTINGENCY DEPARTURE


In case of one or more navaid failure following procedures shall be carried out:

These SIDs require a minimum climb gradient of 10.4% up to FL70.


Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.



LANZAROTE SIX ECHO (LTE 6E) LANZAROTE FOUR FOXTROT (LTE 4F) RWYS 08, 26 DEPARTURES



LTE 6E: Cross GDV at or above **FL140**, maintain **FL200**, await further clearance

LTE 4F: Cross MERAN at or above **FL90**, LPC at or above **FL220**, maintain **FL240**, await further clearance

ROUTING

LTE 6E 08 Climb on TFS R-076 to D10.0 TFS, turn RIGHT, intercept TFS R-092 via TENAR to GDV, GDV R-067 via CAINA to LTE.

LTE 4F 26 Climb on runway heading to TFS 3.0 DME, turn LEFT, intercept TFS R-114 to MERAN, turn LEFT, intercept LPC R-278 inbound to LPC, LPC R-059 to CAINA, turn RIGHT, intercept LTE R-248 inbound to LTE.

CONTINGENCY DEPARTURE

In case of one or more navaid failure following procedures shall be carried out:
These SIDs require a minimum climb gradient of 10.4% up to FL70.
Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.

LTE 6E




This SID require a minimum climb gradient of 4.5% up to FL90.

Gnd speed-KT	75	100	150	200	250	300
10.4% V/V (fpm)	790	1053	1580	2106	2633	3160
4.5% V/V (fpm)	342	456	684	911	1139	1367

Apt Elev
209'

Trans level: By ATC Trans alt: 6000'
EXPECT close-in obstacles.

ORION FIVE ECHO (ORION 5E) [ORIO5E] ①
ORION THREE FOXTROT (ORION 3F) [ORIO3F]
RWYS 08, 26 DEPARTURES




Initial ATC clearance:

ORION 5E: Cross GDV at or above **FL140**, maintain **FL200**, await further clearance
ORION 3F: Cross MERAN at or above **FL90**, LPC at or above **FL220**, maintain **FL240**, await further clearance

SID	RWY	ROUTING
ORION 5E ①	08	Intercept TFS R-076 to D10.0 TFS, turn RIGHT, intercept TFS R-092 to GDV, GDV R-093 to ORION.
ORION 3F	26	Climb on runway heading to TFS 3.0 DME, turn LEFT, intercept TFS R-114 to MERAN, turn LEFT, intercept LPC R-278 inbound to LPC, LPC R-083 to ORION.

CONTINGENCY DEPARTURE

In case of one or more navaid failure following procedures shall be carried out:
These SIDs require a minimum climb gradient of 10.4% up to FL70.
Climb on runway heading to FL90, turn by following ATC instructions. In case of turn LEFT (Rwy 08), or turn RIGHT (Rwy 26), special attention must be taken into account because of high minimum altitudes due to orography.





NOISE ABATEMENT

SUMMER: LT minus 1 HOUR = UTC(Z) WINTER: LT = UTC(Z)

ARRIVALS

Landing and approach procedures on visual meteorological conditions will be performed with an angle equal to or higher than the ILS GP or PAPI of each runway.

At night time, visual approaches shall avoid overflying inhabited areas and visual approaches to runway 26 from west via Ganta Int or TFS VORDME shall not initiate the left turn before TFS 10 DME.

DEPARTURES

Take-off	Take-off power. Take-off flaps/slats. Climb at $V_2 + 10$ KT to 1500' AGL.
At 1500'	Reduce to power of ascent. Accelerate to zero flap minimum safe manoeuvring speed (VZF) + 10 KT maintaining minimum rate of climb 500'. Retract flaps/slats as needed.
Up to FL60	Do not exceed 250 KT and continue SID in force, except ATC clearance.

Aircraft taking-off from runway 08 shall maintain runway heading until TFS 10 DME before initiating any right turn.

Aircraft taking-off from runway 26 and overflying TFS VORDME must not turn right before overflying this navigation facility.

RUN-UP TESTS

Engine tests higher than idle regime are forbidden between 0000-0600LT. Exceptions are allowed only, if it is essential for aircrafts return to the origin airport, or when the planned and cleared flight takes off between 0400-0600LT.

ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond Glide Slope		
08	HIRL (50m) CL (15m) HIALS PAPI(3.0°) HSTIL-B4&B5		9269' 2825m	①	148' 45m
26	HIRL (50m) CL (15m) HIALS PAPI(3.0°) HSTIL-B3		9341' 2847m		

① TAKE-OFF RUN AVAILABLE

RWY 08: From rwy head 10,499' (3200m)
 twy B2 int 9678' (2950m)
 twy B3 int 6234' (1900m)

RWY 26: From rwy head 10,499' (3200m)
 twy B6 int 9843' (3000m)
 twy B5 int 7300' (2225m)


STAND No.	COORDINATES	STAND No.	COORDINATES
E13	N28 02.8 W016 34.3	H14	N28 02.9 W016 34.4
E21 thru E23	N28 02.7 W016 34.7	H15	N28 02.8 W016 34.4
E24 thru E27	N28 02.7 W016 34.8	H18	N28 02.8 W016 34.5
E28	N28 02.7 W016 34.9	H19, H20	N28 02.8 W016 34.6
E29	N28 02.6 W016 34.9	I1, I1A, I1B	N28 02.9 W016 34.3
E30 thru E32	N28 02.6 W016 35.0	I6, I6A, I6B	N28 02.8 W016 34.8
F1	N28 02.9 W016 34.5	I7	N28 02.9 W016 34.8
F2, F3	N28 02.9 W016 34.6	I8 thru I9	N28 02.7 W016 34.9
F4	N28 02.8 W016 34.6	I11, I11A, J12	N28 02.7 W016 35.0
F5 thru F8	N28 02.8 W016 34.7	J33 thru J36	N28 02.6 W016 35.1
G1	N28 02.6 W016 35.1	T16	N28 02.8 W016 34.4
G2 thru G8	N28 02.7 W016 35.1	T17	N28 02.8 W016 34.5
H2, H3	N28 02.9 W016 34.4		
H4, H5	N28 02.9 W016 34.5		
H10	N28 02.7 W016 35.0		

Standard

TAKE-OFF ①

	LVP must be in force			RCLM (DAY only) or RL	NIL (DAY only)
	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL		
A				400m	500m
B	150m	200m	250m		
C					
D	200m	250m	300m		

① Operators applying U.S. Ops Specs: CL required below 300m.



VISUAL DOCKING GUIDANCE SYSTEM

GENERAL

This system contains information about azimuth guidance (shows the aircraft position with relation to the centerline of the parking area) and distance to the stop position, (based on a laser radar measurement), that is provided by a display unit, in front of the cockpit.

DISPLAY UNIT

Consists of:

1. One alphanumeric presentation line of 4 characters, composed by yellow LED, which can indicate several information: 'ACFT TYPE, STOP, OK, TOO FAR, SLOW DOWN, WAIT TEST, ID FAIL and DOWN GRADE'.
2. One line with a unit of yellow LED and 2 units of red/yellow LED for indication of acft azimuth and stop indication.
3. One column of 3 units of yellow LED in the center to indicate the distance to the stop position.

PILOT INSTRUCTIONS

GENERAL ADVICE

When the pilot is not sure about the information shown in the display unit, he must immediately stop the acft and obtain more information to proceed.


1. DOCKING START

When the system starts (manually operated by an operator in ground), it shows the flashing message: 'WAIT TEST'.

2. CAPTURE


When the system is working in capture way, looking for the approaching acft, the system shows vertical floating arrows. The first line of the display unit will show the 'ACFT TYPE'.

ADVICE: If the system does not show vertical arrows in movement and an acft type like the approaching acft, the pilot must not enter into the stand point area.



3. MONITORING

When the acft has been captured by the laser, the floating arrows are substituted by the yellow indicator in the centerline. A flashing red arrow shows the pilot the direction of turn in order to line-up along the stand edge. If the system does not show the direction arrows, it means the acft is over the centerline.



4. APPROACH RATE

When the acft is less than 52'/16m from the stop point, the approach rate is shown by one LED line turn-off from the centerline each 2'/0,7m covered when the acft moves until the stop position.

5. SPEED REDUCTION

When the acft exceeds the programmed approach speed, the display unit will show 'SLOW DOWN' such as advice to pilot.

6. REACHING STOP POINT

When the correct stop point is reached, the display unit shows STOP and red bar lights turn on.

7. DOCKING FINISHED

When the acft is parked, the display unit shows 'OK'.

8. EXCEEDED

When the acft exceeds the stop point, the display unit shows 'TOO FAR'.

9. WAIT


When the detected acft is lost during the docking routine, 39'/12m before the stop point, the display unit will show 'WAIT'. The routine will continue when the system detects the acft again.

10. ADVERSE METEOROLOGICAL CONDITIONS

When the system visibility is reduced due to any reason, the display unit will show 'DOWN GRADE'. As soon as the system identifies the acft, the display unit will show the rate approach bar in order to continue the docking routine.



ADVICE: The pilot must not exceed the boarding bridge unless the message 'DOWN GRADE' had been substituted by the rate approach bar.

ATIS 118.67	TENERIFE-SOUTH Approach (R) 127.7	TENERIFE-SOUTH Tower 119.0	Ground 121.9
LOC TRS 109.7	Final Apch Crs 075°	GS D4.0 TRS 1526' (1338')	ILS DA(H) Refer to Minimums Apt Elev 209' RWY 188'



MISSED APCH: Climb STRAIGHT AHEAD to 5000', then turn RIGHT (MAX 220 KT) to VOR at FL70 and join holding.

Alt Set: hPa Rwy Elev: 7 hPa Trans level: By ATC Trans alt: 6000'
CAUTION: Severe wind shear may occur during approach.




Gnd speed-Kts	70	90	100	120	140	160	HIALS 5000' PAPI PAPI
ILS GS or LOC Descent Angle 3.00°	377	484	538	646	753	861	
MAP at D0.5 TRS							

STRAIGHT-IN LANDING RWY 08						CIRCLE-TO-LAND	
ILS						Not authorized North of rwy	
Missed Apch climb gradient mim 3.0 %			Missed Apch climb gradient mim 2.5 %				
DA(H) 1 D: 446' (258')			DA(H) 2 D: 459' (271')			DA(H) 700' (512')	
FULL	Limited	ALS out	FULL	Limited	ALS out	ALS out	Max Kts
A		RVR 1200m	RVR 550m		RVR 1200m	RVR 1500m	100
B	RVR 550m	RVR 750m		RVR 750m			135
C		RVR 1300m	RVR 600m		RVR 1300m		180
D	RVR 600m					RVR 1600m CMV 2400m	205

1 DA(H) CAT A: 415' (227'), CAT B: 427' (239'), CAT C: 435' (247').
2 DA(H) CAT A: 428' (240'), CAT B: 440' (252'), CAT C: 448' (260').



ATIS 118.67	TENERIFE-SOUTH Approach (R) 127.7	TENERIFE-SOUTH Tower 119.0	Ground 121.9
LOC TRS 109.7	Final Apch Crs 075°	GS D4.0 TRS 1526' (1338')	ILS DA(H) Refer to Minimums
Apt Elev 209'		RWY 188'	



MSA
TES NDB

MISSED APCH: Climb STRAIGHT AHEAD to 5500', then turn RIGHT (MAX 220 KT) to NDB at FL100 and join holding.

Alt Set: hPa Rwy Elev: 7 hPa Trans level: By ATC Trans alt: 6000'
CAUTION: Severe wind shear may occur during approach.



Gnd speed-Kts	70	90	100	120	140	160	5500' HIALS PAPI PAPI
ILS GS	3.00°	377	484	538	646	753	
LOC Desc Angle	3.10°	383	492	547	656	765	
MAP at D0.5 TRS							

STRAIGHT-IN LANDING RWY 08						CIRCLE-TO-LAND			
Missed Apch climb gradient min 3.0 %			Missed Apch climb gradient min 2.5 %			Not authorized North of rwy			
DA(H) 1 C: 435' (247') D: 446' (258')			DA(H) 2 C: 448' (260') D: 459' (271')			DA(H) 800' (612')			
FULL	Limited	ALS out	FULL	Limited	ALS out	ALS out	Max Kts	MDA(H)	VIS
A							100	1180' (971')	1500m
B	RVR 550m						135	1250' (1041')	1600m
C		RVR 750m					180	1350' (1141')	2400m
D	RVR 600m						205	1350' (1141')	3600m

1 DA(H) CAT A: 415' (227'), CAT B: 427' (239'). **2** DA(H) CAT A: 428' (240'), CAT B: 440' (252').


ATIS 118.67	TENERIFE-SOUTH Approach (R) 127.7	TENERIFE-SOUTH Tower 119.0	Ground 121.9
LOC ISUR 110.9	Final Apch Crs 255°	GS D3.0 ISUR 1223' (1014')	ILS DA(H) Refer to Minimums Apt Elev 209' RWY 209'

MISSED APCH: Climb on 255° to 4000'. Turn LEFT to NDB climbing to 6000' and join holding.


MSA TES NDB

Alt Set: hPa Rwy Elev: 8 hPa Trans level: By ATC Trans alt: 6000'

1. CAUTION: Severe wind shear may occur during approach. 2. ILS DME reads zero at rwy 26 threshold.



LOC (GS out)	ISUR DME	2.0	3.0	4.0	5.0	6.0	7.0
	ALTITUDE	910'	1240'	1560'	1890'	2210'	2540'



<i>Gnd speed-Kts</i>	70	90	100	120	140	160
<i>ILS GS</i> 3.00°	377	484	538	646	753	861
<i>LOC Descent Angle</i> 3.10°	383	492	547	656	765	875
<i>MAP at D1.0 ISUR</i>						

HIALS

PAPI

PAPI

4000' on 255°

Standard STRAIGHT-IN LANDING RWY 26				CIRCLE-TO-LAND	
ILS DA(H) A: 426' (217') C: 446' (237') B: 438' (229') D: 456' (247')				LOC (GS out) DA(H) 710' (501')	
FULL Limited ALS out				Not authorized North of rwy	
A B C D				Max Kts MDA(H) VIS	
RVR 550m RVR 750m RVR 1200m				100 1620' (1411') 1500m	
RVR 1600m CMV 2400m				135 1620' (1411') 1600m	
RVR 1300m				180 1720' (1511') 2400m	
				205 1720' (1511') 3600m	



ATIS 118.67	TENERIFE-SOUTH Approach (R) 127.7	TENERIFE-SOUTH Tower 119.0	Ground 121.9
LOC ISUR 110.9	Final Apch Crs 255°	GS D3.0 ISUR 1223' (1014')	ILS DA(H) Refer to Minimums Apt Elev 209' RWY 209'

MISSED APCH: Climb on R-075 inbound to 5000', then turn LEFT direct to VOR climbing to FL70 and join holding.

MSA TFS VOR


Alt Set: hPa Rwy Elev: 8 hPa Trans level: By ATC Trans alt: 6000'

1. CAUTION: Severe wind shear may occur during approach. 2. ILS DME reads zero at rwy 26 threshold.



1.0							HIALS PAPI PAPI 5000' on TFS 116.4 R-075	
Gnd speed-Kts		70	90	100	120	140	160	
ILS GS	3.00°	377	484	538	646	753	861	
LOC Descent Angle	3.10°	383	492	547	656	765	875	
MAP at D1.0 ISUR								

Standard				STRAIGHT-IN LANDING RWY 26		CIRCLE-TO-LAND	
				ILS		LOC (GS out)	
				A: 409' (200') C: 418' (209')		DA(H) 720' (511')	
				B: 410' (201') D: 428' (219')			
				FULL		Limited	
				ALS out		ALS out	
				RVR 550m		RVR 750m	
				RVR 1200m		RVR 1600m	
				RVR 1500m		CMV 2400m	
				Max Kts		MDA(H)	
				100		1620' (1411')	
				135		1620' (1411')	
				180		1720' (1511')	
				205		1720' (1511')	



BRIEFING STRIP™

ATIS	TENERIFE-SOUTH Approach (R)		TENERIFE-SOUTH Tower	Ground
118.67	127.7	120.3	119.0	121.9
VOR	Final	Minimum Alt		
TFS	Apch Crs	D12.0	DA(H)	Apt Elev 209'
116.4	255°	1600' (1391')	1330' (1121')	RWY 209'
MISSED APCH: Climb on R-075 inbound to 5000', then direct to VOR at FL70 and join holding.				
Alt Set: hPa		Rwy Elev: 8 hPa	Trans level: By ATC	Trans alt: 6000'
1. DME required.		2. CAUTION: Severe wind shear may occur during approach.		

130°

14,500'

6100'


091°

269°



4000'

MSA


TFS VOR



MSA
TFS VOR




Gnd speed-Kts	70	90	100	120	140	160
Descent Angle 2.89°	358	460	511	613	716	818
MAP at D9.0						





5000'

PANS OPS 4	Standard STRAIGHT-IN LANDING RWY 26		CIRCLE-TO-LAND	
	DA(H) 1330' (1121')		Not authorized North of rwy	
	ALS out		Max Kts	MDA(H) VIS
	A RVR 1500m		100	1620' (1411') 1500m
	B CMV 2400m		135	1620' (1411') 1600m
			180	1720' (1511') 2400m
			205	1720' (1511') 3600m



MSA
TES NDB

MAP at NDB

Standard

CIRCLE-TO-LAND

Not authorized North of rwy

	Max Kts	MDA(H)	VIS
A	100	1460' (1251')	1500m
B	135	1780' (1571')	1600m
C	180	1880' (1671')	2400m
D	205	1880' (1671')	3600m

TENERIFE-SOUTH, (REINA SOFIA - GCTS)

TERMINAL CHART CHANGE NOTICES

Chart Change Notices for Airport GCTS

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: Until Further Notice

(10-1P) Eff 13 DEC 12, paragraph 1.2.1: For engine test, clearance must be requested to the operations centre (CEOPS).