

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UUMO

Terminal Charts For UUMO

Revision Letter For Cycle 17-2013

Change Notices

Notebook

General Information

Location: Ostafyevo Rus
IATA Code: OSF
Lat/Long: N55° 30.4' E037° 30.2'
Elevation: 563 ft

Airport Use: Public
Magnetic Variation: 10.3°E

Fuel Types: Jet A-1
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0223 Z
Sunset: 1641 Z,

Runway Information

Runway: 08
Length x Width: 6726 ft x 157 ft
Surface Type: concrete
TDZ-Elev: 541 ft
Lighting: Edge, ALS

Runway: 26
Length x Width: 6726 ft x 157 ft
Surface Type: concrete
TDZ-Elev: 561 ft
Lighting: Edge, ALS
Displaced Threshold: 404 ft

Communication Information

ATIS 127.6
Ostafyevo Tower 119.2
Ostafyevo Transit Operations 130.3


© JEPPESEN, 2012. ALL RIGHTS RESERVED.

ATIS
127.6

Apt Elev
563'


Alt Set: MM (hPa on request) QNH on request
Trans level: By ATC Trans alt: By ATC

(QFE)




RWY 26 ARRIVALS


CAT C & D



(QFE)

**CAT A & B**

KARTINO
1215 WT
N55 35.0 E037 46.9



NOT TO SCALE

MAX 280 KT +/- 10 KT or Mach 0.8
whichever is less from cruising FL to FL250.
MAX 270 KT +/- 10 KT below FL250 to FL100.
MAX 250 KT +/- 10 KT below FL100 to TL.


ALT/HEIGHT CONVERSION
QNH (QFE)
1860' (1319' - 400m)

ATIS
127.6

Apt Elev
563'

Alt Set: MM (hPa on request) QNH on request
Trans level: By ATC Trans alt: By ATC

(QFE)




RWY 26 ARRIVALS

CAT A & B

SPEED RESTRICTION

MAX 280 KT +/- 10 KT or Mach 0.8
whichever is less from cruising FL to FL250.
MAX 270 KT +/- 10 KT below FL250 to FL100.
MAX 250 KT +/- 10 KT below FL100 to TL.



ALT/HEIGHT CONVERSION
QNH (QFE)
1880' (1319' - 400m)

- ❶ From OE (RWY 01): 105°, 10 NM.
From SX (RWY 19): 119°, 11 NM.
- ❷ From DMD: R-307, 10 NM.
From DO: 308°, 10 NM.
- ❸ From DMD: R-289, 15 NM.
From DO: 290°, 15 NM.

VNUKOVO Radar
126.0



DOMODEDOVO Radar
127.7

Apt Elev
563'

QNH on request **(QFE)**
Trans level: By ATC Trans alt: By ATC

RWY 08 DEPARTURES BY ATC

- ① By VNUKOVO Radar.
- ② By DOMODEDOVO Radar.



ALT/HEIGHT CONVERSION	
QNH	(QFE)
1200'	(659' - 200m)
1860'	(1319' - 400m)


VNUKOVO Radar
126.0

DOMODEDOVO Radar
127.7


Apt Elev
563'

QNH on request **(QFE)**
Trans level: By ATC Trans alt: By ATC


RWY 26 DEPARTURES **BY ATC**



- ① By VNUKOVO Radar.
- ② By DOMODEDOVO Radar.



ALT/HEIGHT CONVERSION
QNH **(QFE)**
1220' **(657' - 200m)**
1880' **(1317' - 400m)**



Taxiing on twy 1 restricted to acft with wingspan up to 105' (32m) and wheel span up to 30' (9m).
Taxiing on twy 1 strictly along twy centerline at minimum speed.
Taxiing on twy 2 restricted to acft with wingspan up to 105' (32m) and wheel span up to 20' (6m).
Taxiing onto/from rwy shall be carried out on twy 4. Twy 2 not avbl for civil acft.
If RVR is less than 800m, taxiing on twys 1, 3, 5 prohibited.

ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond Glide Slope		
08	HIRL (56m) ALS ① PAPI-L (angle 3.17°)				157' 48m
26	HIRL (56m) HIALS PAPI-L (angle 3.17°)	6322' 1927m ②	5228' 1593m		
08	Grass runway				262' 80m
26					

① Configuration unknown.

② LDA rwy 26 reduced by 404' (123m) due to narrowing of rwy strip.

The airport does not accept any acft if the actual weather is below the published weather minimums for landing.

Flight Procedures

Pilots executing approach on rwy 08 shall strictly maintain the approach path due to narrowing of rwy strip.

TAKE-OFF

AIR CARRIER (JAA)

Main Rwy

LVP must be in force

RCLM (DAY only)
or RL


RCLM (DAY only)
or RL

A
B
C
D

250m

400m

300m




Taxiing to and from stands

If VIS less than 400m acft shall be escorted by "Follow me".
At Night acft with wingspan up to 105' (32m) and wheelspan up to 20' (6m) shall be escorted by "Follow me".
Parking onto stands 1 thru 6 by towing.
Parking onto stands 7 thru 12 with facing Northwest by towing.
Parking onto stands 14 thru 31 with facing Northwest by towing.
Stands 7A, 11 thru 13 avbl for helicopters.

INS COORDINATES


STAND No.	COORDINATES
1, 2	N55 30.2 E037 30.6



UUMO
OSTAFYEVO

JEPPESEN
20 JUL 12 **(16-1)** **Eff 26 Jul**

OSTAFYEVO, RUSSIA
2 NDB Rwy 08



CHANGES: Procedure bearings. Lights.

© JEPPESEN, 2007, 2012. ALL RIGHTS RESERVED.



Chart changes since cycle 16-2013

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT PROCEDURE IDENT

INDEX

REV DATE

EFF DATE

OSTAFYEVO, (OSTAFYEVO - UUMO)

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UUMO