

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UKFF

Terminal Charts For UKFF

Revision Letter For Cycle 23-2013

Change Notices

Notebook

General Information

Location: Simferopol' Ukr
IATA Code: SIP
Lat/Long: N45° 03.1' E033° 58.4'
Elevation: 597 ft

Airport Use: Public
Magnetic Variation: 6.3°E

Fuel Types: Jet, Jet A-1
Repair Types: Minor Airframe, Minor Engine
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0439 Z
Sunset: 1418 Z,

Runway Information

Runway: 01
Length x Width: 12142 ft x 197 ft
Surface Type: concrete
TDZ-Elev: 598 ft
Lighting: Edge, ALS, Centerline

Runway: 19
Length x Width: 12142 ft x 197 ft
Surface Type: concrete
TDZ-Elev: 578 ft
Lighting: Edge, ALS, Centerline, TDZ


Communication Information


ATIS 127.2 Non-English
ATIS 122.15
Simferopol' Tower 120.8
Simferopol' Ground Control 119.0 MF


SIMFEROPOL' Radar
135.77 124.7

Apt Elev
598'

Alt Set: hPa (MM on request)
Trans level: By ATC Trans alt: 10010'
This chart may only be used for cross-checking of
altitudes assigned while under RADAR control.








2500'

260°

7100'

035°

MSA
SMF VOR




Direct distance from NL to:
Simferopol' Apt 16 NM

FT/METER CONVERSION

QNH	
10010'	- 3050m
9030'	- 2750m
8040'	- 2450m
7060'	- 2150m
2960'	- 900m


STAR	ROUTING
NOMPA 2A	On 152° track to NL.
SOTAM 1E	On 047° track to NL.



ATIS
122.15(Russian 127.2)

Apt Elev
597'

Alt Set: hPa (MM on request)
 Trans level: By ATC Trans alt: 10010'



TINAL ONE HOTEL (TINAL 1H) [TINA1H]
TITAG FOUR ALFA (TITAG 4A) [TITA4A]
RWY 01 ARRIVALS


TINAL
 N45 19.2 E032 56.2

At or above
FL140

122°
 21
 2960
TINAL 1H

D27.4 SMF

At or above
FL120



TITAG

N45 46.0 E033 30.0

At or above
9030'




169°
 43
 2960
TITAG 4A

Between
 10010' & 8040'

274°
 15
 2960

268°
 9




(IAF)

NIKOLA
***326 NL**

N44 58.0 E033 37.2

Between
 10010' & 7060'



SIMFEROPOL'
 D
 (H) **116.6 SMF**
 N45 03.1 E033 58.8

Direct distance from NL to:
 Simferopol' Apt 16 NM

FT/METER CONVERSION

QNH

10010' - 3050m
 9030' - 2750m
 8040' - 2450m
 7060' - 2150m
 2960' - 900m


STAR

ROUTING

TINAL 1H On 122° track to NL.

TITAG 4A On 169° track to NL.

ATIS
122.15 (Russian 127.2)
Apt Elev
597'
Alt Set: hPa (MM on request)
Trans level: By ATC Trans alt: 10010'



TINAL TWO GOLF (TINAL 2G) [TINA2G]
TITAG ONE GOLF (TITAG 1G) [TITA1G]
RWY 19 ARRIVALS



TITAG
N45 46.0 E033 30.0
At or above
9030'



44.8
2960
TITAG 1G

TINAL
N45 19.2 E032 56.2
At or above
FL140

21
2960
122°
TINAL 2G

D27.4 SMF
At or above
FL120


15
2960
274°

(IAF)
588 SF
N45 06.3 E033 59.5
At 4930'

SIMFEROPOL'
D (H) 116.6 SMF
N45 03.1 E033 58.8

NIKOLA
*326 NL
N44 58.0 E033 37.2
Between
10010' & 7060'

HOLDING OVER
SF



Direct distance from SF to:
Simferopol' Apt 3 NM

STAR


ROUTING

TINAL 2G On 122° track to NL, turn LEFT, 058° track to SF.


TITAG 1G On 147° track to SF.

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



NIKOLA TWO HOTEL (NL 2H)
NIKOLA TWO KILO (NL 2K)
NIKOLA ONE LIMA (NL 1L)
NOMPA THREE ALFA (NOMPA 3A) [NOMP3A]
NOMPA TWO BRAVO (NOMPA 2B) [NOMP2B]
RWYS 19, 01 DEPARTURES



FT/METER CONVERSION


QNH

2960'	-	900m
6070'	-	1850m
7060'	-	2150m
9030'	-	2750m
10010'	-	3050m


SID	RWY	ROUTING
NL 2H By ATC	01	Climb on 010° track to SMF 4.0 DME, turn LEFT, on 226° track to NL.
NL 2K		Climb on 010° track to SMF 4.0 DME, turn RIGHT to SMF, turn RIGHT, SMF R-248 to NL.
NL 1L	19	Climb on 190° track to SMF 7.6 DME, turn RIGHT, on 289° track to NL.
NOMPA 3A		Climb on 190° track to SMF 7.6 DME, turn RIGHT, on 289° track to NL, turn RIGHT, 333° track to NOMPA.
NOMPA 2B	01	Climb on 010° track to SMF 4.0 DME, turn LEFT, 272° track, on SMF R-312 to NOMPA.

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



RENBA TWO FOXTROT (RENBA 2F) [RENBA2F]
RENBA TWO HOTEL (RENBA 2H) [RENBA2H]
RWYS 01, 19 DEPARTURES



FT/METER CONVERSION

QNH

2960'	-	900m
6070'	-	1850m
9030'	-	2750m
10010'	-	3050m


RENBA 2H

This SID requires a minimum climb gradient of 8% up to 9030'.

Gnd speed-KT	75	100	150	200	250	300
8% V/V (fpm)	608	810	1215	1620	2025	2430

If unable to comply advise ATC.

SID	RWY	ROUTING
RENBA 2F	01	Climb on 010° track to SMF 4.0 DME, turn RIGHT, on 238° track to SMF, turn LEFT, SMF R-172 to RENBA.
RENBA 2H	19	Climb on 190° track to SMF 7.6 DME, turn LEFT, 142° track, intercept SMF R-172 to RENBA.




SID	RWY	ROUTING
SOGTA 1A	01	Climb on 010° track to SMF 4.0 DME, turn RIGHT, intercept SMF R-037 to SOGTA.
SOGTA 1C	19	Climb on 190° track to SMF 7.6 DME, turn RIGHT, on 050° track to SMF, turn LEFT, SMF R-037 to SOGTA.
SOGTA 1E By ATC		Climb on 190° track to SMF 3.2 DME, turn LEFT, 006° track, intercept SMF R-037 to SOGTA.
TITAG 2D		Climb on 190° track to SMF 7.6 DME, turn RIGHT, on 289° track to NL, turn RIGHT, 350° track to TITAG.
TITAG 4F	01	Climb on 010° track to SMF 4.0 DME, turn LEFT, 294° track, when passing SMF R-334 turn RIGHT, intercept SMF R-331 to TITAG.

UKFF/SIP
Apt Elev 598'
N45 03.1 E033 58.4


JEPPESEN
21 JUN 13 (10-9) Eff 27 Jun

SIMFEROPOL', UKRAINE
SIMFEROPOL'



CHANGES: Parking stands.

© JEPPESEN, 2000, 2013. ALL RIGHTS RESERVED.



INS COORDINATES

STAND No.	COORDINATES	ELEV
G1, G2	N45 01.3 E033 59.8	660' 666'
H1	N45 01.4 E033 59.8	
H4	N45 01.2 E033 59.8	
1 thru 4	N45 01.2 E033 59.8	

ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond		
01	HIRL (60m) CL (15m) HIALS PAPI-L(3.0°) RVR		11,109' 3386m		197'
19	HIRL (60m) CL (15m) HIALS-II TDZ PAPI-L(3.0°) RVR		10,988' 3349m		60m

LOW VISIBILITY PROCEDURE (LVP)

LVP shall be applied when RVR is less than 600m.

Pilots will be informed by ATIS and ATC about beginning of LVP.

- After landing pilots should report about leaving RWY and location.
- Taxiing and parking is performed with follow-me car only.
- Only one acft allowed on the manoeuvring area at a time.

JAR-OPS

TAKE-OFF 1

All Rwys						
Approved Operators		LVP must be in force				
	HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
A	125m	150m	200m	250m	400m	500m
B						
C						
D	150m	200m	250m	300m		

1 Operators applying U.S. Ops Specs: CL required below 300m; approved HUD required below 150m.

STRAIGHT-IN RWY		A	B	C	D
01	ILS	798' (200')	798' (200')	798' (200')	798' (200')
	<i>FULL</i>	R550m	R550m	R550m	R550m
	<i>Limited</i>	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1200m	R1200m	R1200m	R1200m
	LOC ①	1100' (502')	1100' (502')	1100' (502')	1100' (502')
		R1500m	R1500m	R1600m	R1600m
	<i>ALS out</i>	R1500m	R1500m	C2400m	C2400m
	VOR ①	970' (372')	990' (392')	1020' (422')	1040' (442')
	with D3.2	R1000m	R1100m	R1300m	R1400m
	<i>ALS out</i>	R1500m	R1500m	R2000m	C2100m
	VOR ①	1020' (422')	1020' (422')	1020' (422')	1020' (422')
	w/o D3.2	R1300m	R1300m	R1300m	R1300m
	<i>ALS out</i>	R1500m	R1500m	R2000m	R2000m
	NDB ①	970' (372')	970' (372')	970' (372')	970' (372')
	with LOM	R1000m	R1000m	R1000m	R1000m
	<i>ALS out</i>	R1500m	R1500m	R1700m	R1700m
	NDB ①	1140' (542')	1140' (542')	1140' (542')	1140' (542')
	w/o LOM	R1500m	R1500m	R1800m	R1800m
	<i>ALS out</i>	R1500m	R1500m	C2400m	C2400m
19	CAT 2 ILS	678' (100')	678' (100')	686' (108')	699' (121')
		RA107'R300m	RA107'R300m	RA115'R300m	RA129'R400m
	ILS	778' (200')	778' (200')	778' (200')	778' (200')
	<i>FULL</i>	R550m	R550m	R550m	R550m
	<i>Limited</i>	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1200m	R1200m	R1200m	R1200m
	LOC ①	970' (392')	970' (392')	970' (392')	970' (392')
		R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	VOR ①	960' (382')	960' (382')	960' (382')	960' (382')
	with D2.7 SMF	R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	VOR ①	970' (392')	970' (392')	970' (392')	970' (392')
	w/o D2.7 SMF	R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	NDB ①	960' (382')	960' (382')	960' (382')	960' (382')
	with LOM	R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	NDB ①	970' (392')	970' (392')	970' (392')	970' (392')
	w/o LOM	R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m

① Continuous Descent Final Approach.

CIRCLE-TO-LAND	100 KT	135 KT	180 KT	205 KT
After ILS, LOC apch to rwy 01	1100' (502')	1100' (502')	1530' (932')	1530' (932')
After NDB apch to rwy 01	1140' (542')	1140' (542')	1530' (932')	1530' (932')
After VOR apch to rwy 01	1070' (472')	1100' (502')	1530' (932')	1530' (932')
After apch to rwy 19 ❶	1070' (492')	1100' (522')	1530' (952')	1530' (952')
	V1500m ❷	V1600m ❷	V2400m	V3600m

❶ Circling height based on rwy 19 thresh elev of 578'.

❷ or higher minimums of preceding straight-in approach.

TAKE-OFF RWY 01, 19

LVP must be in force					RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
Approved Operators							
HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL				
A							
B	125m	150m	200m	250m	400m	500m	
C							
D	150m	200m	250m	300m			

UKFF/SIP SIMFEROPOL'

21 JUN 13
Eff 27 Jun

11-1

JEPPESEN SIMFEROPOL', UKRAINE
ILS or LOC or NDB Rwy 01

ATIS 122.15 (Russian 127.2)		SIMFEROPOL' Radar (APP) 124.7 135.77		SIMFEROPOL' Tower 120.8	Ground 119.0	
LOC ISN 109.3	Final <i>Apch Crs</i> 010°	GS LOM 1345' (747')	ILS DA(H) 798' (200')		Apt Elev 598'	
NDB SN 588		Minimum Alt D8.4 SMF 2960' (2362')	NDB MDA(H) (CONDITIONAL) 970' (372')		RWY 598'	

MISSED APCH: ① Climb on 010° to 2960', then as directed.

MISSED APCH RADIO COMM FAILURE: ② Climb on 010° to 2960', then turn RIGHT climbing to 3940' to SN NDB, then according to chart.

Alt Set: hPa (MM on req)



Rwy Elev: 22 hPa

Trans level: By ATC

Trans alt: 10010'

FT/METER CONVERSION
QNH

10010'	-	3050m
5580'	-	1700m
4930'	-	1500m
4430'	-	1350m
3940'	-	1200m
2960'	-	900m
1350'	-	410m



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI Refer to Missed Apch above
ILS GS or	372	478	531	637	743	849	
LOC or NDB Desc angle 3.00°							

JAR-OPS								STRAIGHT-IN LANDING RWY 01		CIRCLE-TO-LAND	
DA(H) ILS		LOC (GS out)		with LOM NDB		w/o LOM					
FULL		ALS out		ALS out		ALS out					
A			RVR 1000m		RVR 900m		RVR 1000m	Max Kts	100	MDA(H)	VIS
B	RVR 550m	RVR 1000m	RVR 1200m		RVR 1000m		RVR 1200m		135	1100' (502')	1500m
C			RVR 1600m		RVR 1400m		RVR 1600m		180	1530' (932')	2400m
D									205	1530' (932')	3600m

After NDB apch w/o LOM: MDA(H) 1140' (542').

UKFF/SIP SIMFEROPOL'

21 JUN 13
Eff 27 Jun

11-2



SIMFEROPOL', UKRAINE
ILS or LOC or NDB Rwy 19

ATIS 122.15 (Russian 127.2)		SIMFEROPOL' Radar (APP) 124.7 135.77	SIMFEROPOL' Tower 120.8	Ground 119.0	
LOC ISF 111.1	Final Apch Crs 190°	GS LOM 1345' (767')	ILS DA(H) 778' (200')	Apt Elev 598'	
NDB SF 588		Minimum Alt (CONDITIONAL) D8.3 SMF 2960' (2382')	NDB (CONDITIONAL) MDA(H) 960' (382')	RWY 578'	

MISSED APCH: ① Climb on 190° to 3940', then as directed.

MISSED APCH RADIO COMM FAILURE: ② Climb on 190° to 3940', then turn RIGHT climbing to 4930' to SF NDB, then according to chart.

Alt Set: hPa (MM on req) Rwy Elev: 21 hPa Trans level: By ATC Trans alt: 10010'



Gnd speed-Kts	70	90	100	120	140	160
ILS GS or LOC or NDB Descent angle 3.00°	372	478	531	637	743	849
MAP at LMM						



JAR-OPS				STRAIGHT-IN LANDING RWY 19						CIRCLE-TO-LAND			
DA(H) ILS			LOC (GS out)		with LOM		NDB		w/o LOM				
778' (200')			MDA(H) 970' (392')		MDA(H) 960' (382')		MDA(H) 970' (392')						
FULL		ALS out		ALS out		ALS out		ALS out	Max Kts	MDA(H)	VIS		
A	RVR 550m	RVR 1000m	RVR 900m	RVR 1500m	RVR 900m	RVR 1500m	RVR 900m	RVR 1500m	100	1070' (492')	1500m		
B			RVR 1000m		RVR 1000m		RVR 1000m		135	1100' (522')	1600m		
C			RVR 1800m		RVR 1800m		RVR 1800m		180	1530' (952')	2400m		
D			RVR 1400m		RVR 2000m		RVR 1400m		RVR 2000m	RVR 1400m	RVR 2000m	205	1530' (952')

UKFF/SIP SIMFEROPOL'


21 JUN 13
Eff 27 Jun 11-2A

SIMFEROPOL', UKRAINE CAT II ILS Rwy 19

122.15 ATIS (Russian 127.2)	SIMFEROPOL' Radar (APP) 124.7 135.77	SIMFEROPOL' Tower 120.8	Ground 119.0
LOC ISF 111.1	Final Apch Crs 190°	GS LOM 1345' (767')	CAT II ILS RA/DA(H) Refer to Minimums Apt Elev 598' RWY 578'
MISSED APCH: ① Climb on 190° to 3940', then as directed. MISSED APCH RADIO COMM FAILURE: ② Climb on 190° to 3940', then turn RIGHT climbing to 4930' to SF NDB, then according to chart.			
Alt Set: hPa (MM on req) Rwy Elev: 21 hPa Trans level: By ATC Trans alt: 10010' Special Aircrew & Aircraft Certification required.			




FT/METER CONVERSION QNH	
10010'	3050m
4930'	1500m
4430'	1350m
3940'	1200m
2960'	900m



Gnd speed-Kts	70	90	100	120	140	160	HIALS-II	Refer to Missed Apch above
GS	3.00°	372	478	531	637	743	849	

JAR-OPS STRAIGHT-IN LANDING RWY 19 CAT II ILS		
AB RA 107' DA(H) 678' (100')	C RA 115' DA(H) 686' (108')	D RA 129' DA(H) 699' (121')
RVR 300m 1	RVR 300m 1	RVR 400m

1 Operators applying U.S. Ops Specs: Autoland or HUD required below 350m.




UKFF/SIP SIMFEROPOL'

21 JUN 13

(13-2)

Eff 27 Jun

SIMFEROPOL', UKRAINE VOR Rwy 19



SIMFEROPOL', (SIMFEROPOL' - UKFF)

TERMINAL CHART CHANGE NOTICES

Chart Change Notices for Airport UKFF

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: Until Further Notice

During anti-hail firing, arrivals will be via KH, TITAG, DO or NL, followed by vectoring if RADAR is avbl; departures will be to NL, DO, TIAG or KH, then follow FPL.

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: Until Further Notice

(13-1,13-2) ATIS on freq 122.15MHz established. ATIS on freq 127.2MHz Russian only.