

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UMKK

Terminal Charts For UMKK

Revision Letter For Cycle 23-2013

Change Notices

Notebook

General Information

Location: Kaliningrad Rus
IATA Code: KGD
Lat/Long: N54° 53.4' E020° 35.5'
Elevation: 43 ft

Airport Use: Public
Magnetic Variation: 5.5°E

Fuel Types: Jet A-1
Repair Types: Minor Airframe, Minor Engine
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0604 Z
Sunset: 1440 Z,

Runway Information

Runway: 06
Length x Width: 8202 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 43 ft
Lighting: Edge, ALS

Runway: 24
Length x Width: 8202 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 31 ft
Lighting: Edge, ALS

Communication Information



ATIS 122.475
ATIS 122.05 Non-English
Kaliningrad Tower 129.425 Secondary
Kaliningrad Tower 129.0 Secondary
Kaliningrad Tower 127.2
Kaliningrad Approach Control 129.0 Secondary
Kaliningrad Approach Control 128.5 Secondary
Kaliningrad Approach Control 126.0
Kaliningrad Transit Operations 131.7 Non-English

ATIS
122.47
(Russian 122.05)


Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3299')

NERIG 1A [NERI1A], PELUG 1A [PELU1A]
RILEP 1A [RILE1A], RUSNE 1A [RUSN1A]
TURIP 1A [TURI1A]
RWY 24 ARRIVALS



Direct distance from KR to:
Khrabrovo Apt 3 NM




ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3299' - 1000m)
2990' (2959' - 900m)

ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3299')


BENAL 1A [BENA1A]
NEDRA 1A [NEDR1A]
RUTAM 1A [RUTA1A]
TARUN 1A [TARU1A]
URAMA 1A [URAM1A]
RWY 24 ARRIVALS



Direct distance from KR to:
Khrabrovo Apt 3 NM

(IAF)
840 KR
N54 54.6 E020 40.3
At
2990'
(2959')

KHRABROVO
D (H)
117.05 KR
N54 53.6 E020 36.0



TARUN
N54 54.0 E019 36.0
(KRD R-267/D34.5)
084°

BENAL
N54 46.7 E021 38.6
(KRD R-096/D36.7)
278°

NEDRA
N54 42.0 E021 08.7
(KRD R-117/D22.1)
303°

RUTAM
N54 37.2 E020 39.0
(KRD R-170/D16.5)
357°

URAMA
N54 36.5 E019 59.4
(KRD R-227/D27.2)
047°



ALT/HEIGHT CONVERSION
(QFE)
QNH
3330' (3299' - 1000m)
2990' (2959' - 900m)

ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3287')

NERIG 1B [NERI1B], PELUG 1B [PELU1B]
RILEP 1B [RILE1B], RUSNE 1B [RUSN1B]
TURIP 1B [TURI1B]
RWY 06 ARRIVALS




ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3287' - 1000m)
3000' (2957' - 900m)

ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3287')


BENAL 1B [BENA1B]
NEDRA 1B [NEDR1B]
RUTAM 1B [RUTA1B]
TARUN 1B [TARU1B]
URAMA 1B [URAM1B]
RWY 06 ARRIVALS



Direct distance from K to:
Khrabrovo Apt 1 NM

(IAF)
410 K
N54 54.0 E020 37.6
A+
3000'
(2957')

KHRABROVO
D
(H) 117.05 KRD
N54 53.6 E020 36.0



TARUN
N54 54.0 E019 36.0
(KRD R-267/D34.5)

36
TARUN 1B
085°

36
BENAL 1B
277°
BENAL
N54 46.7 E021 38.6
(KRD R-096/D36.7)

22
NEDRA 1B
299°
NEDRA
N54 42.0 E021 08.7
(KRD R-117/D22.1)

17
RUTAM 1B
352°
RUTAM
N54 37.2 E020 39.0
(KRD R-170/D16.5)
MHA FL50
MAX FL265
168°
348°

28
URAMA 1B
047°
URAMA
N54 36.5 E019 59.4
(KRD R-227/D27.2)
MHA FL50
MAX FL265
226°
046°



ALT/HEIGHT CONVERSION
(QFE)
QNH
3330' (3287' - 1000m)
3000' (2957' - 900m)

ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3287')

NERIG 1C [NERI1C], PELUG 1C [PELU1C]
RILEP 2B [RILE2B], RILEP 1C [RILE1C]
RUSNE 2B [RUSN2B], RUSNE 1C [RUSN1C]
TURIP 1C [TURI1C]
RWYS 06, 24 ARRIVALS




ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3287')


BENAL 1C [BENA1C]
NEDRA 1C [NEDR1C]
RUTAM 1C [RUTA1C]
TARUN 2A [TARU2A]
TARUN 1C [TARU1C]
URAMA 2A [URAM2A]
URAMA 1C [URAM1C]
RWYS 06, 24 ARRIVALS



(IAF)
KALININGRAD
D (H) 117.05 KRD
N54 53.6 E020 36.0

A+ 3000'
(2957')

D6.0 KRD
A+ 1690' (1647')



NOT TO SCALE

(IAF for TARUN 2A)

TARUN

N54 54.0 E019 36.0

D19.2 KRD

N54 53.9 E020 02.8

15.3

086°

TARUN

2A, 1C

D34.5

106°

TARUN 2A

11

19.2

TARUN 1C

D9.2 KRD

N54 49.8 E020 21.4

A+ 1690' (1647')

D9.2 KRD

N54 49.8 E020 21.4

14.3

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C

N54 37.2 E020 39.0

168°

MHA FL50

MAX FL265

348°

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C

N54 37.2 E020 39.0

168°

MHA FL50

MAX FL265

348°

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C

N54 37.2 E020 39.0

168°

MHA FL50

MAX FL265

348°

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C

N54 37.2 E020 39.0

168°

MHA FL50

MAX FL265

348°

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C

N54 37.2 E020 39.0

168°

MHA FL50

MAX FL265

348°

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

046°

MHA FL50

MAX FL265

226°

URAMA

N54 36.5 E019 59.4

047°

URAMA 1C

URAMA 2A, 1C

D12.9 KRD

N54 45.5 E020 18.6

12.9

URAMA 1C

R227°

R241°

R267°

R170°

R117°

R096°

36.7

BENAL 1C

N54 46.7 E021 38.6

276°

BENAL

22.1

NEDRA 1C

N54 42.0 E021 08.7

297°

NEDRA

16.5

349°

RUTAM 1C




N54 37.2 E020 39.

ATIS
122.47
(Russian 122.05)

Apt Elev
43'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3299')

RILEP 2C [RILE2C], RUSNE 2C [RUSN2C]
RWY 24 ARRIVALS
ILS APPROACH



ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3299' - 1000m)
1680' (1649' - 500m)


Apt Elev
43'

QNH on request (QFE)


Trans level: FL50 if pressure is 742mm (989.3 hPa) or above

FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above

Trans alt: 3330' (3287')



NERIG 1D, PELUG 1D
RILEP 1D, RUSNE 1D
TURIP 1D
RWY 06 DEPARTURES



ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3287' - 1000m)


Apt Elev
43'

QNH on request (QFE)

Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above



Trans alt: 3330' (3287')

BENAL 1D, NEDRA 1D, RUTAM 1D
TARUN 1D, TARUN 1F
URAMA 1D, URAMA 1F
RWY 06 DEPARTURES



KALININGRAD
D 117.05 KRD
(H) --- --- ---
N54 53.6 E020 36.0

- ① TARUN 1D
- ② URAMA 1D




ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3287' - 1000m)

Apt Elev
43'


QNH on request (QFE)

Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above

Trans alt: 3330' (3299')



NERIG 1E, PELUG 1E
RILEP 1E, RILEP 1G
RUSNE 1E, RUSNE 1G
TURIP 1E
RWY 24 DEPARTURES





ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3299' - 1000m)

Apt Elev
43'

QNH on request (QFE)

Trans level: FL50 if pressure is 742mm (989.3 hPa) or above
FL60 if pressure is less than 742mm (989.3 hPa) and
715mm (953.3 hPa) or above
Trans alt: 3330' (3299')

BENAL 1E, BENAL 1G
NEDRA 1E, NEDRA 1G
RUTAM 1E, RUTAM 1G
TARUN 1E
URAMA 1E, URAMA 1G
RWY 24 DEPARTURES



ALT/HEIGHT CONVERSION
QNH (QFE)
3330' (3299' - 1000m)

NOISE ABATEMENT

GENERAL

Noise abatement procedures shall be executed by crews of all aircraft.

ARRIVALS

If special meteorological conditions, such as considerable wind, cumulo nimbus clouds etc are present in arrival and approach sectors, ATC unit may, if it is considered necessary for safety reasons, at its own discretion or by a pilot-in-command's request deviate from the provisions stated below.

- During instrument or visual approach it is not allowed to fly below the ILS glide path.
- Increase of IAS has to be envisaged during descent.
- In order not to distract the crew's attention during execution of noise abatement procedures, air-ground communication shall be reduced to a minimum.
- Landing of aircraft with a tail-wind component up to 5m/sec is allowed under the following conditions: runway is dry or damp, friction coefficient is 0.5 or more, cross-wind component is not more than 5 m/sec.

The procedures stated above shall not be observed when

- there is ice, slush, water or mud, rubber, oil etc on the runway and the friction coefficient is 0.4 or less;
- when the ceiling is less than 150m or horizontal visibility is less than 1800m;
- when a cross-wind component on runway, including gusts, exceeds 7m/sec;
- when a tail/wind component on the runway exceeds 2.5m/sec;
- when wind shear is forecasted or reported, or it is expected that unfavourable weather conditions (e.g. thunderstorms) may influence approach and landing.

A displacement of threshold shall not be used as a noise abatement measure.

DEPARTURES

The noise abatement procedures stated below shall not be executed at the expense of reduction of flight safety or in case of failure of one of the aircraft engines during take-off phase.

- Take-off with a tail-wind component up to 5m/sec is allowed when the runway is dry or damp, when friction coefficient is 0.5 or more and when cross-wind component is not more than 5m/sec.
- Changing of flight course of the aircraft after take-off is permitted only after reaching 380' (337').
- Turns initiated between 380' (337') and 700' (657') shall be executed with a bank not exceeding 15°.
- Turns initiated at or above 700' (657') shall be executed with 25° bank or with angular speed of turn of 3m/sec.
- The minimum indicated air speed during established climb shall not be less than $V_2 + 20\text{km/h}$ or less than that prescribed in the Airplane Flight Manual if it has greater value.

Maintaining the minimum IAS during climb is not required if it leads to exceeding the minimum permissible angle of attack.

The reduction of engine power shall not be applied until

- the aircraft reaches 1030' (987')
- the established standard power mode enables with MTOW to maintain the established climb gradient of not less than 4% at a speed specified above
- take-off flight path provides overflying of all obstacles located under flight path with sufficient clearance both when all engines are operating normally and also taking into account possible engine failure and time period necessary for the rest engines to develop full power.


REVERSE THRUST

Reverse thrust power, with the exception of reverse idle thrust, is used only for safety reasons

UMKK/KGD
Apt Elev 43'
N54 53.4 E020 35.6

JEPPSEN
8 MAR 13 (10-9)

KALININGRAD, RUSSIA
KHRABROVO



ADDITIONAL RUNWAY INFORMATION

RWY					USABLE LENGTHS		WIDTH
					LANDING BEYOND	TAKE-OFF	
					Threshold	Glide Slope	
06	HIRL (60m)	ALS	PAPI-L (angle 3.00°)	RVR			148'
24	HIRL (60m)	HIALS	PAPI-L (angle 2.67°)	RVR		7169' 2185m	45m

TAKE-OFF

AIR CARRIER (JAA)


All Rwy's

LVP must be in force

RCLM (DAY only)
or RL

RCLM (DAY only)
or RL

A		
B	250m	400m
C		
D	300m	

**INS COORDINATES**

STAND No.	COORDINATES
1, 2	N54 53.0 E020 35.0
3, 4	N54 53.0 E020 35.1
5 thru 7	N54 53.0 E020 35.2
8	N54 53.1 E020 35.3
9	N54 53.0 E020 34.9
10, 11	N54 53.1 E020 34.9
12, 13	N54 53.1 E020 35.0
14 thru 16	N54 53.1 E020 35.1
17 thru 19	N54 53.1 E020 35.2
20	N54 53.2 E020 34.4
21	N54 53.3 E020 34.3
22 thru 24	N54 53.3 E020 34.2
25	N54 53.3 E020 34.1
26, 27	N54 52.9 E020 34.8

Taxiing and towing without permission of taxiing controller are prohibited.

Stands 1 thru 19 and 21 thru 28 available for helicopter.


STRAIGHT-IN RWY		A	B	C	D
06	VOR ①	460' (417')	460' (417')	460' (417')	460' (417')
		R1500m	R1500m	R1700m	R1700m
	<i>ALS out</i>	R1500m	R1500m	R1900m	R1900m
	NDB ①	860' (817')	860' (817')	860' (817')	860' (817')
		R1500m	R1500m	C2400m	C2400m
	NDB	860' (817')	860' (817')	860' (817')	860' (817')
		C3800m	C3800m	C4000m	C4000m
	<i>ALS out</i>	C4000m	C4000m	C4200m	C4200m
24	ILS	231' (200')	231' (200')	231' (200')	231' (200')
	<i>FULL</i>	R550m	R550m	R550m	R550m
	<i>Limited</i>	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1200m	R1200m	R1200m	R1200m
	LOC	NOT AUTH	NOT AUTH	NOT AUTH	NOT AUTH
	VOR ①	430' (399')	430' (399')	430' (399')	430' (399')
		R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	2 NDB ①	390' (359')	390' (359')	390' (359')	390' (359')
		R1000m	R1000m	R1200m	R1200m
	<i>ALS out</i>	R1600m	R1600m	R1600m	R1600m
	NDB ①	640' (609')	640' (609')	640' (609')	640' (609')
		C2100m	C2100m	C2100m	C2100m
	<i>ALS out</i>	C2800m	C2800m	C2800m	C2800m

① Continuous Descent Final Approach.

TAKE-OFF RWY 06, 24		
LVP must be in Force		
RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)
A	400m	500m
B		
C		
D	300m	


BRIEFING STRIP

ATIS		KALININGRAD Approach		*KALININGRAD Tower	
122.47 (Russian 122.05)		126.0	128.5	127.2	129.42
LOC IKR 109.5	Final Apch Crs 241°	GS LOM 736' (705')	ILS DA(H) 231' (200')	Apt Elev 43'	1700'
NDB KR 840		Minimum Alt LOM 740' (709')	NDB MDA(H) Refer to Minimums	RWY 31'	
MISSED APCH: Climb on 241° to 1350' (1319'), then turn RIGHT to KR NDB climbing to 1680' (1649'), then as directed.					
Alt Set: MM (hPa on req)		QNH on req (QFE)		Trans level: FL 50 ②	Trans alt: 3330' (3299')



NDB apch: Pass LMM not below 270' (239').

- ③ 2 NDB apch
- ④ NDB apch



Gnd speed-Kts	70	90	100	120	140	160	HIALS	
ILS GS or	331	425	472	567	661	756	PAPI	1350' (1319') on 241°
NDB Descent Angle 2.67°								
2 NDB: MAP at LMM								

STRAIGHT-IN LANDING RWY 24							
ILS		LOC (GS out)		2 NDB		NDB	
DA(H) 231' (200')				MDA(H) 390' (359')		MDA(H) 640' (609')	
FULL	ALS out				ALS out		ALS out
A							
B							
C	RVR 720m VIS 800m	1200m	NOT AUTH	1200m	RVR 1500m VIS 1600m	3200m	
D				RVR 1500m VIS 1600m	RVR 1800m VIS 2000m		


UMKK/KGD
KHRABROVO

19 APR 13
Eff 2 May

11-2

via RILEP 2C, RUSNE 2C

KALININGRAD, RUSSIA
ILS Rwy 24



CHANGES: IF designation. Holding withdrawn.

© JEPPESEN, 2011, 2013. ALL RIGHTS RESERVED.

BRIEFING STRIP

ATIS		KALININGRAD Approach		*KALININGRAD Tower	
122.47 (Russian 122.05)		126.0	128.5	127.2	129.42
VOR KRD 117.05	Final Apch Crs 061°	Minimum Alt D6.0 1690' (1647')	MDA(H) 460' (417')	Apt Elev 43' RWY 43'	1700' MSA KRD VOR
MISSED APCH: Climb on 061° to 1360' (1317'), then turn LEFT to VOR climbing to 1690' (1647'), then as directed.					

Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 50 ① Trans alt: 3330' (3287')

ALT/HEIGHT CONVERSION

QNH	(QFE)
3330' (3287' - 1000m)	
3000' (2957' - 900m)	
1690' (1647' - 500m)	
1360' (1317' - 400m)	

① FL 60 if pressure is less than 742mm (989.3 hPa) and 715mm (953.3 hPa) or above.

② After STAR BENAL 1C, NEDRA 1C, NERIG 1C, PELUG 1C, RILEP 1C, RUSNE 1C, RUTAM 1C, TARUN 1C, TURIP 1C or URAMA 1C.


③ After STAR RILEP 1C or RUSNE 1C.

10

5


0

5



KRD DME	5.4	4.3	3.2	2.2	1.6
ALTITUDE (HAT)	1510' (1467')	1160' (1117')	820' (777')	470' (427')	310' (267')

RACETRACK: **D9.2**
PROCEDURE TURN: **D6.0**



Gnd speed-Kts	70	90	100	120	140	160	ALS PAPI	1360' (1317') on 061°
Descent Angle 3.00°	372	478	531	637	743	849		
MAP at VOR								

STRAIGHT-IN LANDING RWY 06

MDA(H) **460' (417')**

ALS out

A	RVR 1500m VIS 1600m	
B		
C	RVR 1800m VIS 2000m	
D		

PANS OPS

UMKK/KGD
KHRABROVO

19 APR 13
Eff 2 May

(13-2)

via TARUN 2A, URAMA 2A


KALININGRAD, RUSSIA
VOR DME Rwy 06

BRIEFING STRIP


TM

ATIS		KALININGRAD Approach		*KALININGRAD Tower	
122.47 (Russian 122.05)		126.0	128.5	127.2	129.42
VOR KRD 117.05	Final Apch Crs 061°	Minimum Alt D6.0 1690' (1647')	MDA(H) 460' (417')	Apt Elev 43' RWY 43'	1700' MSA KRD VOR
MISSED APCH: Climb on 061° to 1360' (1317'), then turn LEFT to VOR climbing to 1690' (1647'), then as directed.					


Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 50 ① Trans alt: 3330' (3287')



KRD DME	5.4	4.3	3.2
ALTITUDE (HAT)	1510' (1467')	1160' (1117')	820' (777')




Gnd speed-Kts	70	90	100	120	140	160
Descent Angle 3.00°	372	478	531	637	743	849
MAP at VOR						



STRAIGHT-IN LANDING RWY 06	
MDA(H) 460' (417')	
ALS out	

A	RVR 1500m	
B	VIS 1600m	
C	RVR 1800m	
D	VIS 2000m	




UMKK/KGD
KHRABROVO

19 APR 13
Eff 2 May

13-4


via RILEP 2B, RUSNE 2B

KALININGRAD, RUSSIA
VOR DME Rwy 24



CHANGES: IF designation. Holding withdrawn. Minimums.

© JEPPESEN, 2011, 2013. ALL RIGHTS RESERVED.



KALININGRAD, (KHRABROVO - UMKK)

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UMKK