

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UUYW

Terminal Charts For UUYW

Revision Letter For Cycle 23-2013

Change Notices

Notebook

General Information

Location: Vorkuta Rus
IATA Code: VKT
Lat/Long: N67° 29.3' E063° 59.4'
Elevation: 602 ft

Airport Use: Public
Magnetic Variation: 24.1°E

Customs: No
Airport Type: IFR
Landing Fee: No
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0438 Z
Sunset: 1019 Z,

Runway Information

Runway: 08
Length x Width: 7218 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 544 ft
Lighting: Edge, ALS

Runway: 26
Length x Width: 7218 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 597 ft
Lighting: Edge, ALS
Displaced Threshold: 984 ft

Communication Information

Vorkuta Tower 129.0 Secondary Non-English
Vorkuta Tower 120.6 Non-English
Vorkuta Approach Control 129.5
Vorkuta Transit Operations 122.9 Non-English

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')



BENUR 2A [BENU2A]
SELAN 2A [SELA2A]
TINUS 2A [TINU2A]
RWY 08 ARRIVALS

FOR RUSSIAN USERS ONLY

BENUR

N68 40.8 E062 47.1

134°
BENUR 2A
33

148°

N68 09.5 E063 18.5

Between
FL200 & FL60

TINUS

N68 11.6 E064 20.9

Between
FL200 & FL60



Direct distance from N67 30.7 E063 42.8 to:
Vorkuta Apt 7NM

① Within 32.4 NM to airport descend from
FL90 under continuous RADAR surveillance.

SELAN

N67 55.3 E067 31.2

42
230°
SELAN
2A

51

N67 35.1 E063 34.3
(103° brg to DW)

At 2520'
(1976')

N67 34.5 E063 32.5
(097° brg to DW)

At 2520'
(1976')

N67 41.9 E065 47.3

Between
FL200 & FL90

N67 33.9
E063 32.4
(094° brg
to DW)

At 2190'
(1646')

N67 31.7
E063 36.0
(082° brg to DW)

At 2190'
(1646')

N67 30.7
E063 42.8

At 2190'
(1646')

*522 DW
N67 30.0 E063 51.7

ALT/HEIGHT CONVERSION

QNH	(QFE)
2900'	(2356' - 700m)
2520'	(1976' - 600m)
2190'	(1646' - 500m)

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')



BENUR 4A [BENU4A]
SELAN 4A [SELA4A]
TINUS 4A [TINU4A]
RWY 26 ARRIVALS

FOR RUSSIAN USERS ONLY



BENUR

N68 40.8 E062 47.1



N68 09.5 E063 18.5

Between
FL200 & FL60

TINUS

N68 11.6 E064 20.9

Between
FL200 & FL60



Direct distance from N67 28.5 E064 10.3 to:
Vorkuta Apt 4NM

① Within 32.4 NM to airport descend from
FL90 under continuous RADAR surveillance.

ALT/HEIGHT CONVERSION

QNH	(QFE)
2900'	(2303' - 700m)
2570'	(1973' - 600m)
2240'	(1643' - 500m)

N67 30.6 E064 27.0
(233° brg to KZ)

At 2570'
(1973')

N67 30.2 E064 27.4
(236° brg to KZ)


At 2570'
(1973')

N67 41.9 E065 47.3

Between
FL200 & FL90

SELAN

N67 55.3
E067 31.2



N67 29.3 E064 26.3
(242° brg to KZ)

At 2240' (1643')

*522 KZ

N67 28.8 E064 06.5

N67 28.5 E064 10.3

At 2240' (1643')

N67 28.0 E064 20.9
(254° brg to KZ)

At 2240' (1643')

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request **(QFE)**

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and 733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and 706mm (941.3 hPa) or above

Trans alt (hgt): 2900' **(2356')**



**ABOSO 2A [ABOS2A]
GUBAT 2A [GUBA2A]
GUBAT 2B [GUBA2B]
RWY 08 ARRIVALS**

FOR RUSSIAN USERS ONLY



Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request **(QFE)**

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
 733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
 706mm (941.3 hPa) or above

Trans alt (hgt): 2900' **(2303')**



ABOSO 4A [ABOS4A] GUBAT 4A [GUBA4A] RWY 26 ARRIVALS

FOR RUSSIAN USERS ONLY



- 1 Within 21.6 NM to airport descend from FL90 under continuous RADAR surveillance.
- 2 Within the 075°-115° sector from ASR from 18.4 NM to 11.8 NM between FL80 and 2900' (2356') deviations from STARs for separation are PROHIBITED.


Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request **(QFE)**
Trans level: FL40
FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above
FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above
Trans alt (hgt): 2900' **(2356')**

**ARLEN 2A [ARLE2A]
ROLEK 2A [ROLE2A]
UDAMA 2A [UDAM2A]
RWY 08 ARRIVALS**

FOR RUSSIAN USERS ONLY


ALT/HEIGHT CONVERSION
QNH (QFE)
2900' (2356' - 700m)
2190' (1646' - 500m)






Apt Elev
602'

Alt Set: MM (hPa on request) QNH on request (QFE)
Trans level: FL40
FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above
FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above
Trans alt (hgt): 2900' (2356')



LISBI 2A [LISB2A]
NISAN 2A [NISA2A]
RWY 08 ARRIVALS

FOR RUSSIAN USERS ONLY



Direct distance from N67 30.7 E063 42.8 to:
Vorkuta Apt 7NM

ALT/HEIGHT CONVERSION	
QNH	(QFE)
2900'	(2356' - 700m)
2190'	(1646' - 500m)

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')



LISBI 4A [LISB4A]
NISAN 4A [NISA4A]
RWY 26 ARRIVALS

FOR RUSSIAN USERS ONLY



ALT/HEIGHT CONVERSION

QNH (QFE)

2900' (2303' - 700m)

2570' (1973' - 600m)

2240' (1643' - 500m)

Direct distance from N67 28.5 E064 10.3 to:
Vorkuta Apt 4NM

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')



BENUR 2C [BENU2C]
SELAN 2C [SELA2C]
TINUS 2C [TINU2C]
RWY 08 ARRIVALS
WITHOUT RADAR CONTROL

FOR RUSSIAN USERS ONLY

BENUR
N68 40.8 E062 47.1

134°
BENUR 2C
33

N68 09.5 E063 18.5
Between
FL200 & FL60

139°

TINUS
N68 11.6 E064 20.9
Between
FL200 & FL60

170°

43
TINUS 2C

1. Overfly DW
BENUR 2C & TINUS 2C: at or above
the lowest safe FL,
SELAN 2C: at or above FL90.
2. After DW
BENUR 2C & TINUS 2C: turn RIGHT,
then according to IAC.
SELAN 2C:
- CAT A&B continue on 228° bearing
for 1 min
- CAT C&D continue on 228° bearing
for 1,5 min
turn RIGHT to DW. After over-
flying DW, turn RIGHT, then accor-
ding to IAC.
3. 25° bank for all turns.



N67 30.7 E063 42.8

At 2190'
(1646')

N67 30.7 E063 35.5
(073° brg to DW)

At 2190'
(1646')

N67 27.7
E063 31.5
(050° brg
to DW)

At 2520'
(1976')

SELAN 2C

*522 DW
N67 30.0 E063 51.7

N67 26.3 E063 49.7
At 2520'
(1976')

N67 41.9 E064 47.3

Between
FL200 & FL90

SELAN
N67 55.3 E067 31.2

42
230°
SELAN 2C
228°

46

ALT/HEIGHT CONVERSION

QNH	(QFE)
2900'	(2356' - 700m)
2520'	(1976' - 600m)
2190'	(1646' - 500m)

Direct distance from N67 30.7 E063 42.8 to:
Vorkuta Apt 7NM

Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above


Trans alt (hgt): 2900' (2303')



**BENUR 4C [BENU4C]
SELAN 4C [SELA4C], TINUS 4C [TINU4C]
RWY 26 ARRIVALS
WITHOUT RADAR CONTROL**

FOR RUSSIAN USERS ONLY

1. Overfly KZ
BENUR 4C: at or above the lowest safe FL,
SELAN 4C & TINUS 4C: at or above FL90.
2. After KZ:
BENUR 4C:
- CAT A&B continue on 108° bearing
for 1 min
- CAT C&D continue on 108° bearing
for 1.5 min
turn LEFT to KZ. After overflying KZ,
turn LEFT, then according to IAC.
SELAN 4C & TINUS 4C: turn LEFT, then
according to IAC.
3. 25° bank for all turns.



Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')



ABOSO 2C [ABOS2C]
GUBAT 2C [GUBA2C]
RWY 08 ARRIVALS
WITHOUT RADAR CONTROL

FOR RUSSIAN USERS ONLY



Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')




ABOSO 4C [ABOS4C]

GUBAT 4C [GUBA4C]

RWY 26 ARRIVALS

WITHOUT RADAR CONTROL

FOR RUSSIAN USERS ONLY



Apt Elev
602'

Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and

733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and


706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')

ARLEN 2C [ARLE2C]
ROLEK 2C [ROLE2C]
UDAMA 2C [UDAM2C]
RWY 08 ARRIVALS
WITHOUT RADAR CONTROL

FOR RUSSIAN USERS ONLY





Apt Elev
602'


Alt Set: MM (hPa on request) QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')



LISBI 4C [LISB4C]
NISAN 4C [NISA4C]
RWY 26 ARRIVALS
WITHOUT RADAR CONTROL

FOR RUSSIAN USERS ONLY



1. Overfly KZ at or above the lowest safe FL.
2. After KZ
LISBI 4C:
- CAT A&B continue on 078° bearing for 1 min
- CAT C&D continue on 078° bearing for 1,5 min
turn RIGHT to KZ. After overflying KZ, turn LEFT,
then according to IAC.
NISAN 4C:
- CAT A&B continue on 108° bearing for 1 min
- CAT C&D continue 108° bearing for 1,5 min
turn LEFT to KZ. After overflying KZ, turn LEFT,
then according to IAC.
3. 25° bank for all turns.



ALT/HEIGHT CONVERSION		
QNH	(QFE)	
2900'	(2303' -	700m)
2570'	(1973' -	600m)
2240'	(1643' -	500m)

Apt Elev
602'

QNH on request (QFE)


Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')

SELAN 1
TINUS 1
RWY 08 DEPARTURES



FOR RUSSIAN USERS ONLY


TINUS

N68 11.6 E064 20.9

At or above
FL60



*522 DW
N67 30.0 E063 51.7



078°

At 1370'
(826')

47
TINUS 1

339°

N67 41.9 E065 47.3

At or above
FL90

SELAN
N67 55.3 E067 31.2

42

048°

42
SELAN 1

043°

These SIDs require a minimum climb gradient
of
5.0% up to 1370' (826').

ALT/HEIGHT CONVERSION	
QNH	(QFE)
1370'	(826' - 250m)
2900'	(2356' - 700m)

Gnd speed-KT	75	100	150	200	250	300
5.0% V/V(fpm)	380	506	760	1013	1266	1519

Apt Elev
602'

QNH on request **(QFE)**


Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' **(2303')**

**BENUR 3
SELAN 3
TINUS 3
RWY 26 DEPARTURES**



FOR RUSSIAN USERS ONLY



ALT/HEIGHT CONVERSION
QNH **(QFE)**
1260' **(663' - 200m)**
2900' **(2303' - 700m)**



Apt Elev
602'

QNH on request (QFE)

Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above


Trans alt (hgt): 2900' (2356')

ABOSO 1


GUBAT 1A [GUBA1A] ①

GUBAT 1B [GUBA1B]

RWY 08 DEPARTURES



FOR RUSSIAN USERS ONLY



ALT/HEIGHT CONVERSION	
QNH	(QFE)
1370'	(826' - 250m)
2520'	(1976' - 600m)
2900'	(2356' - 700m)

These SIDs require a minimum climb gradient of
5.0% up to 1370' (826').

Gnd speed-KT	75	100	150	200	250	300
7.5% V/V(fpm)	570	760	1139	1519	1899	2279
5.0% V/V(fpm)	380	506	760	1013	1266	1519

Apt Elev
602'

QNH on request (QFE)


Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above


FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')

ABOSO 3
GUBAT 3
RWY 26 DEPARTURES



FOR RUSSIAN USERS ONLY



ALT/HEIGHT CONVERSION	
QNH	(QFE)
1260'	(663' - 200m)
2900'	(2303' - 700m)

Apt Elev
602'

QNH on request (QFE)


Trans level: FL40

FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')

ARLEN 1
ROLEK 1
UDAMA 1
RWY 08 DEPARTURES



FOR RUSSIAN USERS ONLY



*522 DW
N67 30.0 E063 51.7

At 1370'
(826')

078°

N67 15.0 E062 14.1

At or above
FL60

ARLEN
N66 46.9
E059 04.8

UDAMA
N66 32.8 E059 34.0

ROLEK
N66 18.0 E060 16.4

N67 02.6 E062 32.2

At or above
FL60

① N67 09.5 E062 20.5

At or above
FL60

ALT/HEIGHT CONVERSION

QNH (QFE)

1370' (826' - 250m)

2900' (2356' - 700m)

These SIDs require a minimum climb gradient
of
5.0% up to 1370' (826').

Gnd speed-KT	75	100	150	200	250	300
5.0% V/V(fpm)	380	506	760	1013	1266	1519

Apt Elev
602'

QNH on request (QFE)

Trans level: FL40



FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2356')

BENUR 1
LISBI 1
NISAN 1
RWY 08 DEPARTURES

FOR RUSSIAN USERS ONLY



ALT/HEIGHT CONVERSION	
QNH	(QFE)
1370'	(826' - 250m)
2900'	(2356' - 700m)

These SIDs require a minimum climb gradient of 5.0% up to 1370' (826').

Gnd speed-KT	75	100	150	200	250	300
5.0% V/V(fpm)	380	506	760	1013	1266	1519

Apt Elev
602'

QNH on request (QFE)

Trans level: FL40


FL50 if pressure is less than 760mm (1013.3 hPa) and
733mm (977.3 hPa) or above

FL60 if pressure is less than 733mm (977.3 hPa) and
706mm (941.3 hPa) or above

Trans alt (hgt): 2900' (2303')

LISBI 3
NISAN 3
RWY 26 DEPARTURES

FOR RUSSIAN USERS ONLY



NISAN

N68 30.2 E060 09.9

N67 54.4 E062 27.2

At or above
FL60

N67 33.4 E062 07.4

At or above
FL60

LISBI

N67 38.3 E058 41.2

At 1260'
(663')

*522 KZ
N67 28.8 E064 06.5



ALT/HEIGHT CONVERSION
QNH (QFE)
1260' (663' - 200m)
2900' (2303' - 700m)




UUYW/VKT
Apt Elev 602'
N67 29.4 E063 59.4

JEPPSEN
5 JUL 13 (10-9)

VORKUTA, RUSSIA
VORKUTA



Pre-departure run-up for Rwy 26 on runway with heading 078°.
Line up on Rwy 26 by LEFT turn.
Twy D and E and helipads H3 and H4 not available for civil acft.



GENERAL:

Landing on Rwy 08 and take-off from Rwy 26 are allowed with MAX 10 KT (5m/sec) tailwind unless further limitations by ATC.
Take-off from Rwy 08 and landing on Rwy 26 with tailwind are prohibited.

ADDITIONAL RUNWAY INFORMATION

RWY				USABLE LENGTHS		TAKE-OFF	WIDTH
				LANDING BEYOND			
				Threshold	Glide Slope		
08							164'
26	RL	ALS		6234' 1900m		2	50m

2 TAKE-OFF RUN AVAILABLE

RWY 26:

From rwy head 7218' (2200m)
displ thresh 6234' (1900m)

TAKE-OFF


AIR CARRIER (JAA)


All Rws

LVP must be in force
RCLM (DAY only)
or RL

RCLM (DAY only)
or RL

A		
B	250m	400m
C		
D	300m	








Chart changes since cycle 22-2013

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
VORKUTA, (VORKUTA - UUYW)				
REV	SELAN & TINUS 1 DEPS	10-3	01 Nov 2013	
REV	BENUR, SELAN & TINUS 3 DE...	10-3A	01 Nov 2013	
REV	ARLEN, ROLEK & UDAMA 1 DE...	10-3D	01 Nov 2013	
REV	ARLEN, ROLEK & UDAMA 3 DE...	10-3E	01 Nov 2013	

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UUYW