

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UDYE

Terminal Charts For UDYE

Revision Letter For Cycle 01-2014

Change Notices

Notebook

General Information

Location: Yerevan Arm
IATA Code:
Lat/Long: N40° 07.3' E044° 27.9'
Elevation: 2955 ft

Airport Use: Military
Magnetic Variation: 5.9°E

Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0425 Z
Sunset: 1351 Z,

Runway Information

Runway: 03
Length x Width: 8694 ft x 125 ft
Surface Type: asphalt
TDZ-Elev: 2900 ft
Lighting: ALS

Runway: 03L
Length x Width: 5741 ft x 164 ft
Surface Type: grass
TDZ-Elev: 2955 ft

Runway: 21
Length x Width: 8694 ft x 125 ft
Surface Type: asphalt
TDZ-Elev: 2955 ft
Displaced Threshold: 1312 ft


Runway: 21R
Length x Width: 5741 ft x 164 ft
Surface Type: grass
TDZ-Elev: 2955 ft

Communication Information

Erebuni Bolotny Tower 119.4


Apt Elev
2955'

Alt Set: hPa
Trans level: By ATC Trans alt: 11500'




Apt Elev
2955'

Alt Set: hPa
Trans level: By ATC Trans alt: 11500'
Non RNAV equipped ACFT advise ATC and EXPECT RADAR vectors.



**GOSIS 3A, INDUR 3A
SEVAN 3A, TIBLO 3A
RWYS 03, 21 RNAV ARRIVALS**
RNAV 1 (GNSS)

MAX 230 KT BELOW 10000'




STAR	ROUTING
GOSIS 3A	GOSIS (FL130+) - BANAG (10000'+) - ZVR (7000'+).
INDUR 3A	INDUR (FL140+) - OKUDA (7000'+).
SEVAN 3A	SEVAN (FL130+) - MAXAK (FL130+) - ZVR (7000'+).
TIBLO 3A	TIBLO (FL130+) - OKUDA (7000'+).

YEREVAN
Approach
126.0

Apt Elev
2955'

Trans level: By ATC Trans alt: 11500'
1. Contact YEREVAN Approach immediately after take-off.
2. SIDs are also minimum noise routings. Strict adherence within the limits of performance criteria is mandatory.

GOSIS 3S
SEVAN 3S
RWY 21 RNAV DEPARTURES
RNAV 1 (GNSS)



SEVAN
N40 32.1 E044 57.3


At or above
FL130

YE470
N40 20.5 E044 41.8

At or above
FL130

ZVARTNOTS
D 112.3 ZVR
N40 08.8 E044 22.0

Direct distance from
Erebuni Apt to:
GOSIS **26 NM**
YE470 **17 NM**



GOSIS
N39 56.8 E044 59.2

At or above
FL130

These SIDs require a minimum climb gradient
of
6.8% up to FL130.

Gnd speed-KT	75	100	150	200	250	300
6.8% V/V(fpm)	516	689	1033	1377	1722	2066

If unable to comply advise ATC prior take-off
and request alternative clearance.

Initial turns MAX 210 KT, bank angle 20°


SID	ROUTING
GOSIS 3S	YE440 - GOSIS (FL130+).
SEVAN 3S	YE440 - YE470 (FL130+) - SEVAN (FL130+).

YEREVAN
Approach
126.0Apt Elev
2955'

Trans level: By ATC Trans alt: 11500'

1. Contact YEREVAN Approach immediately after take-off.
2. SIDs are also minimum noise routings. Strict adherence within the limits of performance criteria is mandatory.

INDUR 3S
TIBLO 3S
RWY 21 RNAV DEPARTURES
RNAV 1 (GNSS)



TIBLO
N40 23.1 E043 53.5

At or above
FL140

Direct distance from
Erebuni Apt to:
INDUR **37 NM**
TIBLO **31 NM**

ZVARTNOTS
D 112.3 ZVR
N40 08.8 E044 22.0

INDUR
N40 06.9 E043 39.9

At or above
FL140

TIBLO 3S

INDUR 3S

YE440
N40 05.9
E044 26.7

These SIDs require minimum climb gradients of

INDUR 3S: 4.9% up to FL140.
TIBLO 3S: 5.6% up to FL140.

Gnd speed-KT	75	100	150	200	250	300
5.6% V/V(fpm)	425	567	851	1134	1418	1701
4.9% V/V(fpm)	372	496	744	992	1241	1489

If unable to comply advise ATC prior take-off and request alternative clearance.


Initial turns MAX 210 KT, bank angle 20°

SID	ROUTING
INDUR 3S	YE440 - INDUR (FL140+).
TIBLO 3S	YE440 - TIBLO (FL140+).

UDYE
Apt Elev 2955'
N40 07.3 E044 27.9

JEPPESEN
30 NOV 12 (20-9) Eff 13 Dec

YEREVAN, ARMENIA
EREBUNI



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond		
03	21	7382' 2250m		8530' 2600m	125' 38m
03	21				164' 50m

JAR-OPS


TAKE-OFF 1

	All Rwys		
	LVP must be in force	RCLM (DAY only) or RL	NIL (DAY only)
A			
B	250m	400m	500m
C			
D	300m		

1 Operators applying U.S. Ops Specs: CL required below 300m.


STRAIGHT-IN RWY		A	B	C	D
03	NDB	3350'(450') ceil 1500'- 5000m	3350'(450') ceil 1500'- 5000m	3350'(450') ceil 1500'- 5000m	3350'(450') ceil 1500'- 5000m

TAKE-OFF RWY 03, 21			
LVP must be in Force			
RCLM (DAY only) or RL		RCLM (DAY only) or RL	NIL (DAY only)
A	250m	400m	500m
B			
C			
D	300m		



Apt Elev **2955'**

VISUAL APPROACH



Visual approach to RWY 27 at ZVARTNOTS apt
authorized SOUTH of airport only.

Visual approach to RWY 21 at EREBUNI apt authorized
by prescribed routes for acft CAT A & B only.

Chart changes since cycle 26-2013

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
YEREVAN, (EREBUNI - UDYE)				

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UDYE