

## List of pages in this Trip Kit

Trip Kit Index

Airport Information For UACC

Terminal Charts For UACC

Revision Letter For Cycle 13-2016

Change Notices

Notebook

## General Information

Location: ASTANA KAZ  
ICAO/IATA: UACC / TSE  
Lat/Long: N51° 01.35', E071° 27.97'  
Elevation: 1165 ft

Airport Use: Public  
Daylight Savings: Not Observed  
UTC Conversion: -6:00 = UTC  
Magnetic Variation: 10.0° E

Fuel Types: Jet A-1  
Repair Types: Minor Airframe, Minor Engine  
Customs: Yes  
Airport Type: IFR  
Landing Fee: Yes  
Control Tower: Yes  
Jet Start Unit: No  
LLWS Alert: No  
Beacon: No

Sunrise: 2259 Z  
Sunset: 1532 Z

## Runway Information

Runway: 04  
Length x Width: 11483 ft x 148 ft  
Surface Type: asphalt  
TDZ-Elev: 1164 ft  
Lighting: Edge, ALS, Centerline, TDZ

Runway: 22  
Length x Width: 11483 ft x 148 ft  
Surface Type: asphalt  
TDZ-Elev: 1158 ft  
Lighting: Edge, ALS, Centerline, TDZ

## Communication Information

ATIS: 128.300 Non-English  
ATIS: 127.700  
Astana Tower: 118.700  
Astana Tower Ground: 119.600  
Astana Approach: 124.600 Non-English  
Astana Radar: 120.700

UACC/TSE  
ASTANAJEPPesen  
29 MAY 15 10-1PASTANA, KAZAKHSTAN  
AIRPORT BRIEFING

---

**1. GENERAL**

---

**1.1. ATIS**ATIS 127.7  
128.3 (Russian)**1.2. LOW VISIBILITY PROCEDURES (LVP)****1.2.1. GENERAL**

LVPs are established:

- during CAT II/III approaches when TDZ RVR is less 550m and/or ceiling is below 200'/60m;
- during take-off when RVR is less than 400m.

The status of LVP is passed to pilots by means of ATIS broadcast or RTF:  
"LOW VISIBILITY PROCEDURES IN OPERATION".

**1.2.2. GROUND EQUIPMENT****Arriving ACFT:**

Landing ACFT is requested to report RWY vacated after crossing light indicator **ILS**, indicating the ILS localizer sensitive area.

ACFT are permitted to taxi on the apron only under guidance of a Follow-me car. Parking to the stands is assisted by a marshaller.

**Departing ACFT:**

ACFT taxiing out from their stands are accompanied by a follow-me car up to TWYs. ACFT shall stop at the holding position before the light indicator **ILS**, indicating the ILS localizer sensitive area.

**1.3. PARKING INFORMATION**

Entrance to stands 11 thru 21, 24 thru 28 and 32 thru 53 is by towing.

Exit from stands 1 thru 10, 22, 23 and 29 thru 31 is by towing.

**1.4. OTHER INFORMATION**

Birds.

---

**2. ARRIVAL**

---

**2.1. NOISE ABATEMENT PROCEDURES**

During descent within Astana TMA the following speed restrictions apply:

- from FL 98 (FL 3000m) to TL maintain MAX 250 KT;
- from TL to traffic pattern (circling) height or 15NM to TDZ maintain 210 KT +/- 10 KT;
- from 15NM to TDZ until FAP maintain 185 KT +/- 10 KT.

During approach and landing:

- Maintain assigned level until final approach.
- Maintain the program off deceleration; extend landing gear and wing devices so, that the approach speed should be reached 5.4NM from THR.
- Avoid engine power increase from 9.2NM to THR until 8.1NM to THR.
- Do not descend below GP.

**2.2. CAT II/III OPERATIONS**

RWYs 04, 22 approved for CAT II/III operations, special aircrew and ACFT certification required.

UACC/TSE  
ASTANA

JEPPESEN  
29 MAY 15 (10-1P1)

ASTANA, KAZAKHSTAN  
AIRPORT BRIEFING

---

### 3. DEPARTURE

---

#### 3.1. NOISE ABATEMENT PROCEDURES

During take-off for CAT B, C & D the following procedures should be applied:

- From take-off to 2650' (1485'-450m):  
Take-off engine power, flaps in take-off position, V2+10 KT.
- At 2650' (1485'-450m):  
Reduce engine power to climbing power.
- From 2650' (1485'-450m) thru 4120' (2955'-900m):  
Climbing at V2+10 KT.
- From 4120' (2955'-900m):  
Adjust normal climb rate with retracted flaps.

© JEPPESEN, 2011. ALL RIGHTS RESERVED.





UACC/TSE  
ASTANA

JEPPesen  
14 AUG 15 (10-2B)

Eff 20 Aug

ASTANA, KAZAKHSTAN

STAR

ATIS  
127.7  
(Russian 128.3)

Apt Elev  
1165'


Alt Set: MM (hPa on request) QNH on request  
Trans level: FL60 Trans alt: 3790' (2632')

(QFE)

DIDAL 2N [DIDA2N], OLGAS 2N [OLGA2N]  
VAGEM 2N [VAGE2N]  
RWY 22 ARRIVALS

**VAGEM**  
N52 02.0 E071 01.2  
(AST R-336/D63.8)  
Between  
FL210 & FL90

**OLGAS**  
N52 05.2 E071 45.1  
(AST R-001/D66.2)  
Between  
FL210 & FL90



**DIDAL**  
N51 29.1 E069 54.9  
Between  
FL210 & FL90

**ASDET**  
N51 16.6 E071 39.8  
At or above  
FL70

**IBLAN**  
N51 18.5 E071 06.3

**NEGMI**  
N51 12.8 E071 45.9

(IAF)  
**ASTANA**  
D (H) 114.4 AST  
N51 00.1 E071 26.0  
At FL60

ALT/HEIGHT CONVERSION  
QNH (QFE)  
3790' (2632' - 800m)

STAR

ROUTING

DIDAL 2N

Intercept AST R-288 inbound to AST.

OLGAS 2N

On 174° track to ASDET, turn RIGHT, intercept AST R-018 inbound to AST.

VAGEM 2N

On 142° track to ASDET, turn RIGHT, intercept AST R-018 inbound to AST.

UACC/TSE  
ASTANA

JEPPESSEN


ASTANA, KAZAKHSTAN

14 AUG 15

(10-2C)

Eff 20 Aug

STAR



| STAR     | ROUTING                                                                |
|----------|------------------------------------------------------------------------|
| KODOL 2S | Intercept AST R-277 inbound to AST.                                    |
| KODOL 2T | On 114° track to APTUS, turn LEFT, intercept AST R-251 inbound to AST. |
| KOLUR 2S | On 149° track to IBLAN, turn LEFT, intercept AST R-316 inbound to AST. |
| VAGEM 2S | On 166° track to IBLAN, turn LEFT, intercept AST R-316 inbound to AST. |
| VETUB 2S | Intercept AST R-238 inbound to AST.                                    |

UACC/TSE  
ASTANA

JEPPesen  
14 AUG 15

10-3

Eff 20 Aug


ASTANA, KAZAKHSTAN

SID

Apt Elev  
1165'


QNH on request (QFE)

Trans level: FL60 Trans alt: 3790' (2625')



BOLSU 3E [BOLS3E], DIDAL 3E [DIDA3E]  
EDANO 3E [EDAN3E], OLGAS 3E [OLGA3E]  
VAGEM 3E [VAGE3E]  
RWY 04 DEPARTURES

ALT/HEIGHT CONVERSION  
QNH (QFE)  
1830' (665' - 200m)  
3790' (2625' - 800m)



These SIDs require a minimum climb gradient of 4.7% up to ASDET.

| Gnd speed-KT   | 75  | 100 | 150 | 200 | 250  | 300  |
|----------------|-----|-----|-----|-----|------|------|
| 4.7% V/V (fpm) | 357 | 476 | 714 | 952 | 1190 | 1428 |

| SID      | ROUTING                                                                                                                                                                |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BOLSU 3E | Climb straight ahead, at or above 1830' (665'), but not later than AK turn LEFT, 012° track to ASDET, turn RIGHT, 082° track to BOLSU.                                 |
| DIDAL 3E | Climb straight ahead, at or above 1830' (665'), but not later than AK turn LEFT, 012° track to ASDET, turn LEFT, 266° track to IBLAN, turn RIGHT, 274° track to DIDAL. |
| EDANO 3E | Climb straight ahead, at or above 1830' (665'), but not later than AK turn LEFT, 012° track to ASDET, turn RIGHT, 089° track to EDANO.                                 |
| OLGAS 3E | Climb straight ahead, at or above 1830' (665'), but not later than AK turn LEFT, 012° track to ASDET, turn LEFT, 354° track to OLGAS.                                  |
| VAGEM 3E | Climb straight ahead, at or above 1830' (665'), but not later than AK turn LEFT, 012° track to ASDET, turn LEFT, 323° track to VAGEM.                                  |

© JEPPESEN, 2003, 2015. ALL RIGHTS RESERVED.



UACC/TSE  
ASTANA

JEPPESSEN  
14 AUG 15

(10-3C)

Eff 20 Aug


ASTANA, KAZAKHSTAN

SID

Apt Elev  
1165'

QNH on request (QFE)

Trans level: FL60 Trans alt: 3790' (2632')



KODOL 3G [KODO3G], KODOL 3H [KODO3H]  
KOLUR 3G [KOLU3G], OLGAS 3G [OLGA3G]  
OSROL 3G [OSRO3G], VAGEM 3G [VAGE3G]  
VETUB 3G [VETU3G]  
RWY 22 DEPARTURES

**OLGAS**  
N52 05.2 E071 45.1  
(AST R-001/D66.2)

**KOLUR**  
N51 59.0 E070 41.1  
(AST R-325/D65.3)

**VAGEM**  
N52 02.0 E071 01.2  
(AST R-336/D63.8)

ALT/HEIGHT CONVERSION  
QNH (QFE)  
1820' (662' - 200m)  
3790' (2632' - 800m)



**KODOL**  
N51 16.6 E069 56.9

**IBLAN**  
N51 18.5 E071 06.3  
At FL90  
or at FL100

**ASTANA**  
N51 114.4 AST  
N51 00.1 E071 26.0


**OSROL**  
N50 48.3 E070 01.2  
(AST R-248/D55.0)

**VETUB**  
N50 41.1 E070 12.8

**APTUS**  
N50 56.0 E070 46.0  
At or above  
FL90

At or above  
1820'(662')

| SID      | ROUTING                                                                                                                                                    |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| KODOL 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 307° track, intercept AST R-277 to KODOL.                                  |
| KODOL 3H | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 281° track, intercept AST R-251 to APTUS, turn RIGHT, 295° track to KODOL. |
| KOLUR 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 346° track, intercept AST R-316 to IBLAN, turn RIGHT, 329° track to KOLUR. |
| OLGAS 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 346° track, intercept AST R-316 to IBLAN, turn RIGHT, 018° track to OLGAS. |
| OSROL 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 281° track, intercept AST R-251 to APTUS, turn LEFT, 246° track to OSROL.  |
| VAGEM 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 346° track, intercept AST R-316 to IBLAN, turn RIGHT, 346° track to VAGEM. |
| VETUB 3G | Climb straight ahead to at or above 1820' (662'), after passing AST turn RIGHT, 281° track, intercept AST R-251 to APTUS, turn LEFT, 226° track to VETUB.  |



| ADDITIONAL RUNWAY INFORMATION |    |                                       |     |                |                  |          |             |
|-------------------------------|----|---------------------------------------|-----|----------------|------------------|----------|-------------|
| RWY                           |    |                                       |     | USABLE LENGTHS |                  |          |             |
|                               |    |                                       |     | LANDING BEYOND |                  |          |             |
|                               |    |                                       |     | Threshold      | Glide Slope      | TAKE-OFF | WIDTH       |
| 04                            | 22 | HIRL ❶ CL ❷ HIALS-II TDZ PAPI-L(3.0°) | RVR |                | 10,389'<br>3167m |          | 148'<br>45m |
|                               |    |                                       |     |                |                  |          |             |

① (60m) ② (15m)

| TAKE-OFF                      |                                   |           |               |                                         |
|-------------------------------|-----------------------------------|-----------|---------------|-----------------------------------------|
| AIR CARRIER (JAA)<br>All rwys |                                   |           |               |                                         |
|                               | LVP must be in force ①<br>RL & CL | DAY<br>RL | NIGHT<br>RCLM | LVP must be in force ①<br>RL & CL<br>RL |
| A                             |                                   |           |               |                                         |
| B                             | 200m                              | 400m ②    | 400m ②        | 200m 400m ②                             |
| C                             |                                   |           |               |                                         |
| D                             | 250m (200m)                       |           | 500m          | 250m (200m) 400m                        |


① For conditions with braking coefficient not less than 0.5 and cross wind component not more than half maximum allowed for acft type.

② LVP must be in force: 300m.

UACC/TSE

JEPPesen 17 APR 15 (10-9A) Eff 30 Apr

ASTANA, KAZAKHSTAN  
ASTANA



PARKING STAND COORDINATES

| STAND No.  | COORDINATES        | STAND No.  | COORDINATES        |
|------------|--------------------|------------|--------------------|
| 1 thru 3   | N51 01.6 E071 27.6 | 35 thru 38 | N51 01.4 E071 27.5 |
| 4          | N51 01.6 E071 27.7 | 39, 40     | N51 01.5 E071 27.4 |
| 4A         | N51 01.7 E071 28.0 | 41, 42     | N51 01.4 E071 27.4 |
| 5          | N51 01.6 E071 27.7 | 43 thru 45 | N51 01.4 E071 27.5 |
| 6, 7       | N51 01.6 E071 27.8 | 46         | N51 01.3 E071 27.5 |
| 8          | N51 01.7 E071 27.8 | 47 thru 51 | N51 01.3 E071 27.4 |
| 9, 10      | N51 01.7 E071 27.9 | 52         | N51 01.3 E071 27.3 |
| 11         | N51 01.5 E071 27.5 | 53         | N51 01.2 E071 27.3 |
| 12, 13     | N51 01.5 E071 27.6 | 56         | N51 01.9 E071 28.2 |
| 14         | N51 01.4 E071 27.6 | 57, 58     | N51 01.9 E071 28.3 |
| 15 thru 17 | N51 01.5 E071 27.7 | 59         | N51 02.0 E071 28.4 |
| 18         | N51 01.5 E071 27.8 | 1M         | N51 02.2 E071 28.8 |
| 19, 20     | N51 01.6 E071 27.8 | 2M, 3M     | N51 02.2 E071 28.7 |
| 21         | N51 01.6 E071 27.9 | 4M, 5M     | N51 02.3 E071 28.7 |
| 22, 23     | N51 01.7 E071 28.0 | 6M thru 9M | N51 02.3 E071 28.6 |
| 24, 25     | N51 01.7 E071 28.1 | 10M        | N51 02.3 E071 28.5 |
| 26 thru 28 | N51 01.8 E071 28.2 |            |                    |
| 29         | N51 01.8 E071 28.0 |            |                    |
| 30, 31     | N51 01.8 E071 28.1 |            |                    |
| 32 thru 34 | N51 01.5 E071 27.4 |            |                    |

UACC/TSE

**JEPPesen**

22 APR 16  
Eff 28 Apr

10-9S

Standard

ASTANA, KAZAKHSTAN

ASTANA

| STRAIGHT-IN RWY |            | A            | B            | C            | D            |
|-----------------|------------|--------------|--------------|--------------|--------------|
| 04              | CAT 3A ILS | RA50' R200m  | RA50' R200m  | RA50' R200m  | RA50' R200m  |
|                 | CAT 2 ILS  | 1265' (100') | 1265' (100') | 1265' (100') | 1265' (100') |
|                 |            | RA102' R350m | RA102' R350m | RA102' R350m | RA102' R350m |
|                 | ILS        | 1365' (200') | 1365' (200') | 1365' (200') | 1365' (200') |
|                 | FULL       | 550m         | 550m         | 550m         | 550m         |
|                 | Limited    | 750m         | 750m         | 750m         | 750m         |
|                 | ALS out    | 1200m        | 1200m        | 1200m        | 1200m        |
|                 | LOC        | NOT          | NOT          | NOT          | NOT          |
|                 |            | AUTH         | AUTH         | AUTH         | AUTH         |
|                 | VOR ①      | 1500' (335') | 1500' (335') | 1500' (335') | 1500' (335') |
| 22              | CAT 3A ILS | RA50' R200m  | RA50' R200m  | RA50' R200m  | RA50' R200m  |
|                 | CAT 2 ILS  | 1258' (100') | 1258' (100') | 1258' (100') | 1258' (100') |
|                 |            | RA105' R350m | RA105' R350m | RA105' R350m | RA105' R350m |
|                 | ILS        | 1358' (200') | 1358' (200') | 1358' (200') | 1358' (200') |
|                 | FULL       | 550m         | 550m         | 550m         | 550m         |
|                 | Limited    | 750m         | 750m         | 750m         | 750m         |
|                 | ALS out    | 1200m        | 1200m        | 1200m        | 1200m        |
|                 | LOC        | NOT          | NOT          | NOT          | NOT          |
|                 |            | AUTH         | AUTH         | AUTH         | AUTH         |
|                 | VOR ①      | 1560' (402') | 1560' (402') | 1560' (402') | 1560' (402') |
|                 |            | 1200m        | 1200m        | 1200m        | 1400m        |
|                 |            | 1500m        | 1500m        | 1900m        | 1900m        |
|                 | 2 NDB ①    | 1510' (352') | 1510' (352') | 1510' (352') | 1510' (352') |
|                 |            | 900m         | 1000m        | 1000m        | 1400m        |
|                 | ALS out    | 1500m        | 1500m        | 1600m        | 1600m        |
|                 |            |              |              |              |              |
|                 |            |              |              |              |              |
|                 |            |              |              |              |              |
|                 |            |              |              |              |              |
|                 |            |              |              |              |              |

① Continuous Descent Final Approach.

| TAKE-OFF RWY 04, 22    |         |      |        |      |                        |         |        |
|------------------------|---------|------|--------|------|------------------------|---------|--------|
| LVP must be in Force   |         | DAY  |        |      | LVP must be in Force   |         | NIGHT  |
| RL, CL & mult. RVR req | RL & CL | RL   | RCLM   | NIL  | RL, CL & mult. RVR req | RL & CL | RL     |
| A                      | 200m    | 200m | 400m ③ | 500m | 200m                   | 200m    | 400m ③ |
| B                      |         |      |        |      |                        |         | 400m   |
| C                      |         |      |        |      |                        |         |        |
| D                      |         |      |        |      |                        |         |        |
|                        |         | 250m | 500m   |      |                        | 250m    |        |


② For conditions with braking coefficient not less than 0.5 and cross wind component not more than half maximum allowed for act type.

③ LVP must be in force: 300m.

UACC/TSE  
ASTANA

JEPPesen  
14 AUG 15 **11-1** Eff 20 Aug

ASTANA, KAZAKHSTAN  
ILS DME Z Rwy 04




UACC/TSE  
ASTANA

JEPPESEN  
14 AUG 15  
Eff 20 Aug 11-1A

ASTANA, KAZAKHSTAN  
CAT II ILS DME Z Rwy 04

BRIEFING STRIP

|                                                                                                                                                                    |                   |                           |                                               |              |                             |        |                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------------------|-----------------------------------------------|--------------|-----------------------------|--------|------------------|
| ATIS                                                                                                                                                               |                   | ASTANA Approach           |                                               | ASTANA Tower |                             | Ground |                  |
| 127.7 (Russian 128.3)                                                                                                                                              |                   | 124.6                     |                                               | 118.7        |                             | 119.6  |                  |
| LOC<br>IMO                                                                                                                                                         | Final<br>Apch Crs | GS<br>No alt<br>published | CAT II ILS<br>RA 102'<br>DA(H)<br>1265'(100') |              | Apt Elev 1165'<br>Rwy 1165' |        | <div>3000'</div> |
| MISSED APCH: Climb on 035° to 1830' (665') or above outbound to D5.3 AST, then turn RIGHT (MAX 245 KT) to VOR. Climb initially to 3790' (2625'), then as directed. |                   |                           |                                               |              |                             |        |                  |
| MISSED APCH WITH COMM FAILURE: Climb to FL 60 to VOR and hold.                                                                                                     |                   |                           |                                               |              |                             |        |                  |
| MSA AST VOR                                                                                                                                                        |                   |                           |                                               |              |                             |        |                  |
| Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2625')                                                                              |                   |                           |                                               |              |                             |        |                  |
| 1. Special Aircrew & Aircraft Certification Required. 2. ILS DME reads zero at rwy 04 threshold.                                                                   |                   |                           |                                               |              |                             |        |                  |



|                       |       |
|-----------------------|-------|
| ALT/HEIGHT CONVERSION |       |
| QNH                   | (QFE) |
| 3790' (2625' - 800m)  |       |
| 1830' (665' - 200m)   |       |

|                                              |       |                                      |     |             |     |                                |      |             |
|----------------------------------------------|-------|--------------------------------------|-----|-------------|-----|--------------------------------|------|-------------|
| CAT AB:<br>D10.3 AST<br>CAT CD:<br>D11.4 AST |       | CAT A & B ← 206°<br>CAT C & D ← 191° |     | VOR<br>FL60 |     |                                |      |             |
| 3790'<br>(2625')                             |       | 035°                                 |     | TCH 54'     |     |                                |      |             |
| D7.1 AST<br>D7.9 IMO                         |       | 7.9                                  |     | Rwy 1165'   |     |                                |      |             |
| Gnd speed-Kts                                | 70    | 90                                   | 100 | 120         | 140 | 160                            |      |             |
| GS                                           | 3.00° | 372                                  | 478 | 531         | 637 | 743                            | 849  |             |
|                                              |       |                                      |     | HIALS-II    |     | 1830'<br>(665')<br>or above on | 035° | D5.3<br>AST |
|                                              |       |                                      |     | PAPI        |     |                                |      |             |

STRAIGHT-IN LANDING RWY 04  
CAT II ILS  
ABCD  
RA 102'  
DA(H) 1265'(100')



RVR 350m

UACC/TSE  
ASTANA

JEPPESSEN  
14 AUG 15 (11-2) Eff 20 Aug

ASTANA, KAZAKHSTAN  
ILS DME Y Rwy 04

|                                                                                                                                                        |                           |                           |                              |                             |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------------------------|------------------------------|-----------------------------|
| ATIS                                                                                                                                                   | ASTANA Approach           | ASTANA Radar (SRE)        | ASTANA Tower                 | Ground                      |
| 127.7 (Russian 128.3)                                                                                                                                  | 124.6                     | 120.7                     | 118.7                        | 119.6                       |
| LOC<br>IMO<br>109.5                                                                                                                                    | Final<br>Apch Crs<br>035° | GS<br>No alt<br>published | ILS<br>DA(H)<br>1365' (200') | Apt Elev 1165'<br>Rwy 1165' |
| MISSED APCH: Climb on 035° to 1830' (665'), then turn RIGHT onto 215° climbing to 3790' (2625'), then as directed.                                     |                           |                           |                              | 3000'                       |
| Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2625')<br>1. RADAR required. 2. ILS DME reads zero at rwy 04 threshold. |                           |                           |                              | MSA<br>AST VOR              |





|                            |                      |               |                      |         |       |     |              |                      |         |               |
|----------------------------|----------------------|---------------|----------------------|---------|-------|-----|--------------|----------------------|---------|---------------|
| Gnd speed-Kts              | 70                   | 90            | 100                  | 120     | 140   | 160 | HIALS-II     | 1830' (665') on 035° | 215° RT | 3790' (2625') |
| GS                         | 3.00°                | 372           | 478                  | 531     | 637   | 743 | 849          |                      |         |               |
| STRAIGHT-IN LANDING RWY 04 |                      |               |                      |         |       |     |              |                      |         |               |
| ILS                        |                      |               |                      |         |       |     | LOC (GS out) |                      |         |               |
| DA(H) 1365' (200')         |                      |               |                      |         |       |     |              |                      |         |               |
| FULL                       |                      | TDZ or CL out |                      | ALS out |       |     |              |                      |         |               |
| A                          |                      |               |                      |         |       |     |              |                      |         |               |
| B                          |                      |               |                      |         |       |     |              |                      |         |               |
| C                          | RVR 550m<br>VIS 800m |               | RVR 720m<br>VIS 800m |         | 1200m |     |              | NOT<br>AUTHORIZED    |         |               |
| D                          |                      |               |                      |         |       |     |              |                      |         |               |

UACC/TSE  
ASTANA

JEPPesen  
14 AUG 15  
Eff 20 Aug  
(11-2A)

ASTANA, KAZAKHSTAN  
CAT II ILS DME Y Rwy 04

|                                                                                                                                                                   |                           |                           |                                               |                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------------------------|-----------------------------------------------|-----------------------------|
| ATIS                                                                                                                                                              | ASTANA Approach           | ASTANA Radar (SRE)        | ASTANA Tower                                  | Ground                      |
| 127.7 (Russian 128.3)                                                                                                                                             | 124.6                     | 120.7                     | 118.7                                         | 119.6                       |
| LOC<br>IMO<br>109.5                                                                                                                                               | Final<br>Apch Crs<br>035° | GS<br>No alt<br>published | CAT II ILS<br>RA 102'<br>DA(H)<br>1265'(100') | Apt Elev 1165'<br>Rwy 1165' |
| MISSED APCH: Climb on 035° to 1830' (665'), then turn RIGHT onto 215° climbing to 3790' (2625'), then as directed.                                                |                           |                           |                                               | 3000'                       |
| Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2625')<br>1. RADAR required. 2. Special Aircrew & Aircraft Certification Required. |                           |                           |                                               | MSA<br>AST VOR              |



|               |       |     |     |     |     |     |          |                 |      |      |               |
|---------------|-------|-----|-----|-----|-----|-----|----------|-----------------|------|------|---------------|
| Gnd speed-Kts | 70    | 90  | 100 | 120 | 140 | 160 | HIALS-II | 1830' (665') on | 035° | 215° | 3790' (2625') |
| GS            | 3.00° | 372 | 478 | 531 | 637 | 743 | 849      | PAP             | ↑    | RT   | ↑             |

STRAIGHT-IN LANDING RWY 04  
CAT II ILS  
ABCD  
RA 102'  
DA(H) 1265'(100')  
RVR 350m










UACC/TSE  
ASTANA


JEPPesen 14 AUG 15 (13-1) Eff 20 Aug

ASTANA, KAZAKHSTAN  
VOR DME Rwy 04

|                 |                                                                                                                                                                                                                                 |                           |                                     |                       |                             |  |                                             |  |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------------------------|-----------------------|-----------------------------|--|---------------------------------------------|--|
| BRIEFING STRIP™ | ATIS                                                                                                                                                                                                                            |                           | ASTANA Approach                     |                       | ASTANA Tower                |  | Ground                                      |  |
|                 | 127.7 (Russian 128.3)                                                                                                                                                                                                           |                           | 124.6                               |                       | 118.7                       |  | 119.6                                       |  |
|                 | VOR<br>AST<br>114.4                                                                                                                                                                                                             | Final<br>Apch Crs<br>035° | Minimum Alt<br>D7.3<br>3790'(2625') | MDA(H)<br>1500'(335') | Apt Elev 1165'<br>Rwy 1165' |  | <div>3000'</div> <div>MSA<br/>AST VOR</div> |  |
|                 | MISSED APCH: Climb on 035° to 2150' (985') or above outbound to D5.4, then turn RIGHT (MAX 245 KT) to VOR. Climb initially to 3790'(2625'), then as directed.<br>MISSED APCH WITH COMM FAILURE: Climb to FL 60 to VOR and hold. |                           |                                     |                       |                             |  |                                             |  |
|                 | Alt Set: MM(hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2625')                                                                                                                                            |                           |                                     |                       |                             |  |                                             |  |
|                 |                                                                                                                                                                                                                                 |                           |                                     |                       |                             |  |                                             |  |



|                |              |              |              |              |              |             |             |
|----------------|--------------|--------------|--------------|--------------|--------------|-------------|-------------|
| AST DME        | 6.2          | 5.2          | 4.2          | 3.2          | 2.2          | 1.2         | 0.2         |
| ALTITUDE (HAT) | 3500'(2335') | 3160'(1995') | 2850'(1685') | 2510'(1345') | 2190'(1025') | 1860'(695') | 1550'(385') |




|               |       |     |     |     |     |     |     |          |                                     |      |
|---------------|-------|-----|-----|-----|-----|-----|-----|----------|-------------------------------------|------|
| Gnd speed-Kts | 70    | 90  | 100 | 120 | 140 | 160 |     | HIALS-II | 2150'<br>(985')<br>or above on 035° | D5.4 |
| Descent Angle | 3.00° | 372 | 478 | 531 | 637 | 743 | 849 | PAPI     |                                     |      |
| MAP at VOR    |       |     |     |     |     |     |     |          |                                     |      |

|   |                        |                            |  |  |  |
|---|------------------------|----------------------------|--|--|--|
|   |                        | STRAIGHT-IN LANDING RWY 04 |  |  |  |
|   |                        | MDA(H) 1500' (335')        |  |  |  |
|   |                        | ALS out                    |  |  |  |
| A | 900m                   | RVR 1500m<br>VIS 1600m     |  |  |  |
| B |                        |                            |  |  |  |
| C | 1000m                  |                            |  |  |  |
| D | RVR 1500m<br>VIS 1600m |                            |  |  |  |

UACC/TSE  
ASTANA

JEPPESSEN  
14 AUG 15 (13-2) Eff 20 Aug

ASTANA, KAZAKHSTAN  
VOR DME Rwy 22





UACC/TSE  
ASTANA

JEPPesen 22 APR 16 16-1 Eff 28 Apr

ASTANA, KAZAKHSTAN  
2 NDB Rwy 04

BREFFING STRIP™

|                                                                                                                    |  |                           |  |                                                    |  |                        |  |                             |       |
|--------------------------------------------------------------------------------------------------------------------|--|---------------------------|--|----------------------------------------------------|--|------------------------|--|-----------------------------|-------|
| ATIS                                                                                                               |  | ASTANA Approach           |  | ASTANA Radar (SRE)                                 |  | ASTANA Tower           |  | Ground                      |       |
| 127.7 (Russian 128.3)                                                                                              |  | 124.6                     |  | 120.7                                              |  | 118.7                  |  | 119.6                       |       |
| NDB<br>MO<br>318                                                                                                   |  | Final<br>Apch Crs<br>035° |  | Minimum Alt<br>N50 54.9 E071 17.8<br>3790' (2625') |  | MDA(H)<br>1500' (335') |  | Apt Elev 1165'<br>Rwy 1165' |       |
| MISSED APCH: Climb on 035° to 1830' (665'), then turn RIGHT onto 215° climbing to 3790' (2625'), then as directed. |  |                           |  |                                                    |  |                        |  |                             | 3000' |
| Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2625')<br>RADAR required.           |  |                           |  |                                                    |  |                        |  |                             |       |
| MSA<br>M NDB                                                                                                       |  |                           |  |                                                    |  |                        |  |                             |       |



|               |       |     |     |     |     |     |          |                      |      |               |
|---------------|-------|-----|-----|-----|-----|-----|----------|----------------------|------|---------------|
| Gnd speed-Kts | 70    | 90  | 100 | 120 | 140 | 160 | HIALS-II | 1830' (665') on 035° | 215° | 3790' (2625') |
| Descent Angle | 3.00° | 372 | 478 | 531 | 637 | 743 | 849      | PAP                  | RT   |               |
| MAP at LMM    |       |     |     |     |     |     |          |                      |      |               |


|                            |                        |  |  |  |  |                        |  |  |  |
|----------------------------|------------------------|--|--|--|--|------------------------|--|--|--|
| STRAIGHT-IN LANDING RWY 04 |                        |  |  |  |  |                        |  |  |  |
| MDA(H) 1500' (335')        |                        |  |  |  |  |                        |  |  |  |
| ALS out                    |                        |  |  |  |  |                        |  |  |  |
| A                          |                        |  |  |  |  |                        |  |  |  |
| B                          | 1200m                  |  |  |  |  | RVR 1500m<br>VIS 1600m |  |  |  |
| C                          |                        |  |  |  |  |                        |  |  |  |
| D                          | RVR 1500m<br>VIS 1600m |  |  |  |  |                        |  |  |  |

UACC/TSE  
ASTANA

JEPPesen  
22 APR 16 (16-2) Eff 28 Apr

ASTANA, KAZAKHSTAN  
2 NDB Rwy 22

|                                                                                                                   |                           |                                                    |                        |                             |
|-------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------------------|------------------------|-----------------------------|
| ATIS                                                                                                              | ASTANA Approach           | ASTANA Radar (SRE)                                 | ASTANA Tower           | Ground                      |
| 127.7 (Russian 128.3)                                                                                             | 124.6                     | 120.7                                              | 118.7                  | 119.6                       |
| NDB<br>AK<br>318                                                                                                  | Final<br>Apch Crs<br>215° | Minimum Alt<br>N51 07.8 E071 38.2<br>3790' (2632') | MDA(H)<br>1510' (352') | Apt Elev 1165'<br>Rwy 1158' |
| MISSED APCH: Climb on 215° to 1820' (662'), then turn LEFT onto 035° climbing to 3790' (2632'), then as directed. |                           |                                                    |                        | 3000'                       |
| Alt Set: MM (hPa on req) QNH on req (QFE) Trans level: FL 60 Trans alt: 3790' (2632')<br>RADAR required.          |                           |                                                    |                        | MSA<br>A NDB                |



Pass LMM not below 1410' (252').

NEGMI

N51 07.8  
E071 38.2

3790'  
(2632')

LMM

LOM

TCH 54'

215°

1940'  
(782')

3.05°

[FN22]

215°

Rwy 1158'

0

0.6

1.7

2.3

5.9

7.2

|                     |     |     |     |     |     |     |
|---------------------|-----|-----|-----|-----|-----|-----|
| Gnd speed-Kts       | 70  | 90  | 100 | 120 | 140 | 160 |
| Descent Angle 3.05° | 378 | 486 | 540 | 648 | 755 | 863 |

HIALS-II

PAPI

1820'  
(662')

215°

MAP at LMM

STRAIGHT-IN LANDING RWY 22

MDA(H) 1510'(352')

ALS out

|   |       |                        |                        |
|---|-------|------------------------|------------------------|
| A | 1200m | RVR 1500m<br>VIS 1600m |                        |
| B |       |                        |                        |
| C |       |                        |                        |
| D |       |                        | RVR 1500m<br>VIS 1600m |

TRANS OPS



Chart changes since cycle 12-2016

ADD = added chart, REV = revised chart, DEL = deleted chart.

| ACT | PROCEDURE IDENT | INDEX | REV DATE | EFF DATE |
|-----|-----------------|-------|----------|----------|
|-----|-----------------|-------|----------|----------|

ASTANA, (ASTANA - UACC)

## **TERMINAL CHART CHANGE NOTICES**

### **Chart Change Notices for Airport UACC**

**Type:** Terminal

**Effectivity:** Temporary

**Begin Date:** Immediately

**End Date:** Until Further Notice

Minimums raised as follows: (11-1) ILS DME Z Rwy 04: DA(H) 1379' (214') RVR 600m with full lights; (11-1A) CAT II ILS DME Z Rwy 04: DA(H) 1297' (132'), RA 136', RVR 400m; (11-2) ILS DME Y Rwy 04: DA(H) 1379' (214') RVR 600m with full lights; (11-2A) CAT II ILS DME Y Rwy 04: 1297' (132'), RA 136', RVR 400m; (11-3) ILS DME Z Rwy 22: DA(H) 1405' (247') RVR 600m with full lights; (11-4) ILS DME Y Rwy22: DA(H) 1405' (247') RVR 600m with full lights.