

List of pages in this Trip Kit

Trip Kit Index

Airport Information For EGLL

Terminal Charts For EGLL

Revision Letter For Cycle 13-2016

Change Notices

Notebook

General Information

Location: LONDON GBR
ICAO/IATA: EGLL / LHR
Lat/Long: N51° 28.65', W000° 27.68'
Elevation: 83 ft

Airport Use: Public
Daylight Savings: Observed
UTC Conversion: +0:00 = UTC
Magnetic Variation: 1.0° W

Fuel Types: Jet A-1
Repair Types: Major Airframe, Major Engine
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0344 Z
Sunset: 2022 Z

Runway Information

Runway: 27L
Length x Width: 12008 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 78 ft
Lighting: Edge, ALS, Centerline, TDZ

Runway: 27R
Length x Width: 12802 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 79 ft
Lighting: Edge, ALS, Centerline, TDZ

Runway: 09L
Length x Width: 12802 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 81 ft
Lighting: Edge, ALS, Centerline, TDZ
Displaced Threshold: 1014 ft

Runway: 09R
Length x Width: 12008 ft x 164 ft
Surface Type: asphalt
TDZ-Elev: 76 ft
Lighting: Edge, ALS, Centerline, TDZ
Displaced Threshold: 1010 ft

Communication Information

ATIS: 121.935 Departure Service
ATIS: 113.750 Arrival Service
ATIS: 115.100 Arrival Service
ATIS: 128.075 Arrival Service
Heathrow Tower: 124.475
Heathrow Tower: 118.700
Heathrow Tower: 118.500
Heathrow Ground Ground: 121.900
Heathrow Ground Ground: 121.850
Heathrow Ground Ground: 121.700
Heathrow Delivery Clearance Delivery: 121.975
Heathrow Director Approach: 119.725
Heathrow Director Approach: 120.400
Heathrow Director Approach: 127.525
Heathrow Director Approach: 134.975
London Control ACC: 134.250
London Control ACC: 134.125
London Control ACC: 119.775
London Control ACC: 133.175
Heathrow Radar: 125.625
London Control ACC: 118.825
London Control ACC: 120.525
London Control ACC: 126.825
Heathrow Radar: 127.525

EGLL/LHR
HEATHROW

27 MAY 16

JEPPesen

10-1P

LONDON, UK

AIRPORT BRIEFING

1. GENERAL**1.1. ATIS**

- * D-ATIS Arrival 113.750 115.1 128.075
- * D-ATIS Departure 121.935 (Non-8.33kHz-equipped ACFT should contact Heathrow Delivery.)

1.2. NOISE ABATEMENT PROCEDURES**1.2.1. GENERAL**

The following procedures may at any time be departed from to the extent necessary for avoiding immediate danger or for complying with ATC instructions. Every operator of ACFT using the APT shall ensure at all times that ACFT are operated in a manner calculated to cause the least disturbance practicable in areas surrounding the APT.

1.2.2. PREFERENTIAL RUNWAY SYSTEM

When tailwind component is not greater than 5 KT on RWYs 27R/L, these RWYs will be used in preference to RWYs 09R/L, provided the RWY surface is dry. Pilots asking for permission to use the RWY into the wind when RWYs 27R or 27L are in use, should understand that their arrival or departure may be delayed.

1.2.3. REVERSE THRUST

Avoid use of reverse thrust between 2330-0600LT except for safety reasons.

1.2.4. RUN-UP TESTS

Run-up tests are controlled in accordance with instructions issued by Heathrow APT LTD.

1.2.5. NIGHTTIME RESTRICTIONS

Any ACFT which has a noise classification greater than 95.9 EPNdB may not be scheduled to take off or land between 2330-0600LT.

Any ACFT which has a noise classification greater than 98.9 EPNdB may not be scheduled to take off or land between 2300-0700LT.

Any ACFT which has a noise classification greater than 98.9 EPNdB may not take off between 2300-0700LT, except between 2300-2330LT when

- It was scheduled to take off prior to 2300LT;
 - Take-off was delayed for reasons beyond control of the ACFT operator;
 - APT authority has not given notice to the ACFT operator precluding take-off.
- Any ACFT may not take off or be scheduled to land between 2300-0700LT where the operator of that ACFT has not provided (prior to its take-off or prior to its scheduled landing times as appropriate) sufficient information to enable the APT authority to verify its noise classification.

None of the provisions above shall apply to a take-off or landing which is made in an emergency consisting of an immediate danger to life or health, whether human or animal.

1.3. LOW VISIBILITY PROCEDURES**1.3.1. GENERAL**

During CAT II and III operations, special ATC Low Visibility Procedures will be applied. Pilots will be informed when these procedures are in operation via ATIS or RTF. ATC Low Visibility Procedures will only be applied when the RVR is less than 600 m.

EGLL/LHR
HEATHROW

27 MAY 16

JEPPESEN

10-1P1

LONDON, UK

AIRPORT BRIEFING

1. GENERAL

1.3.2. ARRIVAL

- Surface Movement Guidance and Control System (SMGCS) is normally available and all RWY exits will then be illuminated. Pilots should select the first convenient exit.
- Pilots are to delay the call "runway vacated" until ACFT has completely passed the end of the green/yellow colour-coded TWY centerline lights.

1.3.3. DEPARTURE

The ILS on the departure RWY will be turned off when the IRVR is greater than 250m. Pilots requiring the ILS for departure when the IRVR is in the range 275m to 550m must inform HEATHROW Delivery.

1.4. SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM

APT is equipped with Mode S movement radar. Pilots must ensure that: ACFT transponder is set to transmit Mode S signals, and associated Mode A code, from the request for push-back or taxi, whichever is earlier and after landing, continuously until ACFT is fully parked on stand.

After parking, Mode A code 2000 must be set before selecting OFF or STDBY.

1.5. RWY OPERATIONS

1.5.1. RWY CROSSING PROCEDURE

After crossing RWY 09R/27L and having reported RWY vacated, the ACFT will be instructed to revert to Ground for further clearance. In absence of further clearance it is essential that ACFT holds position when clear of RWY.

1.6. TAXI PROCEDURES

1.6.1. GENERAL

Pilots who intend to execute a reduced engine taxi-out must report their intention to Delivery on first contact by data link or if possible by RT.

In the apron areas minimum engine power shall be used as far as possible, and use of reverse thrust for manoeuvring to and from a stand is not permitted.

Whenever operationally and safely feasible, all ACFT are requested to shut down as many engines as possible while taxiing and holding on the ground, EXCEPT in the following circumstances:

- By any ACFT that is required to cross an active RWY;
- By any ACFT exiting T and turning West onto S due to jet blast affecting Stand 412;
- By B777 variants in G and H due to jet blast.

Pilots are to use the minimum power necessary when manoeuvring on the TWY system. This is of particular importance when manoeuvring in the apron cul-de-sacs, where jet blast can affect adjacent stands.

Pilots are reminded of the extreme importance of maintaining a careful lookout at all times and are at all times responsible for wingtip clearance, notwithstanding the TWY lighting system.

EGLL/LHR
HEATHROW

JEPPESEN
27 MAY 16 (10-1P2)

LONDON, UK
AIRPORT BRIEFING

1. GENERAL

1.6.2. RESTRICTIONS TO LARGE ACFT

- A380 ACFT: Reduced "TWY centerline to object clearance" of 161'/49m applies on TWY E between TWY B and Link 36 and on TWY W between TWY S and TWY T.
Reduced clearance of 156'/47.5m applies on TWY A at MORRA. Pilots are to ensure that ACFT remain on TWY centerline at all times.
Use minimum power when manoeuvring at Terminal 4.
- Pilots of Code E ACFT must exercise caution when using TWY S between reporting point SY6 and TWY Z as wingtip clearances to the South are minimal.
- All B747-400 ACFT on TWY Z must be under tow.
- A340-600 and B777-300 ACFT: It is recommended that flight crews use judgemental steering at all times when manoeuvring on the TWYs. These ACFT are not permitted to use the following routes:
Eastbound on TWY S, at TULLA turning RIGHT onto Link 41 to face West.
Eastbound on TWY S, at NESSY turning RIGHT onto Link 41 to face West.
- Pilots of B747, B777, A340 and Code F ACFT are not permitted to route north on TWY Tango turning left on TWY Sierra facing west under power.

1.6.3. TWY ROUTE WEST ON TWY S - RIGHT TO S3/SB3

During DAY and good visibility only and MAX wingspan 91'/27.7m.

1.6.4. CODE E TWY TO TWY SEPARATION

Separation of 262'/80m is not met as follows: TWYs A and B between TWY H and AY5.

1.6.5. CODE E TWY TO STAND OR TWY TO OBJECT SEPARATION

Separation of 156'/47.5m is not met on the following TWYs:

- **Minimum clearance 139'/42.5m**
TWY B from TWY F to TWY J.
All of TWY F.
TWY S from reporting point SY6 East to TWY W.
- **Minimum clearance 121'/37m**
TWY S between reporting point SY6 and TWY Z to the South.

1.6.6. RWY STOP BARS

The RWY stop bars at N4E, N5W, S4 and S5 are not positioned perpendicular to the TWY centerline.

1.7. PARKING INFORMATION

The majority of stands are equipped with the 'Safedock' Visual Docking Guidance System (VDGS). A marshalling service will be provided for the minority of the remaining stands that do not have VDGS fitted.

EGLL/LHR
HEATHROW

27 MAY 16

JEPPesen

(10-1P3)

LONDON, UK

AIRPORT BRIEFING

2. ARRIVAL

2.1. SPEED RESTRICTIONS

Pilots should typically expect the following speed restrictions to be enforced:

- 220 KT from the holding facility during the initial approach phase;
- 180 KT on base leg/closing heading to the final APCH;
- Between 180 KT and 160 KT when established on the final APCH;

and thereafter 160 KT to D4.0.

Adherence to speeds assigned by ATC is mandatory.

These speeds are applied for ATC separation purposes.

In the event of a new (non-speed related) ATC clearance being issued (e.g. an instruction to descend on ILS), pilots shall continue to maintain a previously allocated speed. All speed restrictions are to be flown as accurately as possible. ACFT unable to conform to these speeds should inform ATC and state what speeds can be used. In the interests of accurate spacing, pilots are requested to comply with speed adjustments as promptly as feasible within their own operational constraints, advising ATC if circumstances necessitate a change of speed for ACFT performance reasons.

2.2. NOISE ABATEMENT PROCEDURES

The following procedures may at any time be departed from to the extent necessary for avoiding immediate danger or for complying with ATC instructions.

Every operator of ACFT using the APT shall ensure at all times that ACFT are operated in a manner calculated to cause the least disturbance practicable in areas surrounding the airport.

An ACFT approaching to land shall according to its ATC clearance minimize noise disturbance by the use of continuous descent and low power, low drag operating procedures (see below).

Where the use is not practicable, ACFT shall maintain an altitude as high as possible.

Propeller-driven ACFT with MTOW above 5700kgs and jet ACFT:

ACFT approaching RWY 27L/R between 0600-2330LT

and using the ILS shall not descend below 2500' (Heathrow QNH) on GS before being established on LOC, nor thereafter fly below GS. ACFT approaching without ILS assistance shall follow a descent path which will not result in its being at any time lower than the approach path that would be followed by an ACFT using the ILS GS, and shall follow a track to intercept the extended RWY centerline at or above 2500'.

ACFT approaching RWY 27L/R between 2330-0600LT

and using the ILS shall not descend below 3000' (Heathrow QNH) on GS before being established on LOC at not less than 10NM from touchdown, nor thereafter fly below GS. ACFT approaching without ILS assistance shall follow a descent path which will not result in its being at any time lower than the approach path that would be followed by an ACFT using the ILS GS, and shall follow a track to intercept the extended RWY centerline at or above 3000'.

ACFT approaching RWY 09L/R between 0700-2300LT

and using the ILS shall not descend below 2500' (Heathrow QNH) on GS before being established on LOC, nor thereafter fly below GS. ACFT approaching without ILS assistance shall follow a descent path which will not result in its being at any time lower than the approach path that would be followed by an ACFT using the ILS GS, and shall follow a track to intercept the extended RWY centerline at or above 2500'.

ACFT approaching RWY 09L/R between 2300-0700LT

and using the ILS shall not descend below 3000' (Heathrow QNH) on GS before being established on LOC at not less than 10NM from touchdown, nor thereafter fly below GS. ACFT approaching without ILS assistance shall follow a descent path which will not result in its being at any time lower than the approach path that would be followed by an ACFT using the ILS GS, and shall follow a track to intercept the extended RWY centerline at or above 3000'.

EGLL/LHR
HEATHROW

26 FEB 16

JEPPESEN

10-1P4

LONDON, UK

AIRPORT BRIEFING

2. ARRIVAL

CONTINUOUS DESCENT APPROACH

Headings and flight levels/altitudes by ATC. ACFT will be radar-vectorred. An estimate of track distance to touchdown will be passed with descent clearance. Further distance information will be given between descent clearance and the intercept heading to the ILS LOC.

On receipt of descent clearance, descend at the rate best suited to a continuous descent so as to join the GS at the appropriate height for the distance without recourse to level flight.

2.3. CAT II/III OPERATIONS

RWYs 09L/27R and 09R/27L approved for CAT II/III operations, special aircrew and ACFT certification required.

2.4. RWY OPERATIONS

2.4.1. MINIMUM RWY OCCUPANCY TIME

Pilots are reminded that rapid exit from the landing RWY enables ATC to apply the minimum spacing on final approach that will achieve maximum RWY utilisation and will minimize the occurrence of go-arounds.

Landing ACFT are to vacate expeditiously. All arrivals are to ensure that they are fully vacated before stopping.

2.4.2. RWY VACATION GUIDELINES

ACFT lands but cannot contact HEATHROW Ground due to RTF congestion:

In this case the pilot should completely vacate the landing RWY and taxi into the first TWY available. The pilot should then hold position until contact with Ground can be established.

RWY 09L: Preferred exit for A380 ACFT is A5.

EGLL/LHR
HEATHROW

26 FEB 16

JEPPESSEN

(10-1P5)

LONDON, UK

AIRPORT BRIEFING

2. ARRIVAL

2.5. OTHER INFORMATION

2.5.1. GENERAL

Warning: The possibility of building-induced turbulence and large windshear effects may occur when landing on RWY 27R in strong southerly / south westerly winds.

2.5.2 "LAND AFTER" PROCEDURE

Normally, only one ACFT is permitted to land or take-off on the RWY-in-use at any one time. However, when the traffic sequence is two successive landing ACFT, the second one may be allowed to land before the first one has cleared the RWY-in-use, providing:

- The RWY is long enough;
- It is during daylight hours;
- The second ACFT will be able to see the first ACFT clearly and continuously until it is clear of the RWY;
- The second ACFT has been warned.

ATC will provide this warning by issuing the second ACFT with the instruction "Land after ... (first ACFT type)" in place of the usual instruction "Cleared to land". Responsibility for ensuring adequate separation between the two ACFT rests with the pilot of the second ACFT.

EGLL/LHR
HEATHROW

26 FEB 16

JEPPESEN

10-1P6

LONDON, UK

AIRPORT BRIEFING

3. DEPARTURE

3.1. START-UP & PUSH-BACK PROCEDURES

3.1.1. APT-COLLABORATIVE DECISION MAKING (A-CDM)

3.1.1.1. TARGET OFF-BLOCK TIME (TOBT)/TARGET START-UP APPROVAL TIME (TSAT)

Pilots should take note of the TSAT which they receive from their airline operator or ATC and comply with it.

If TOBT or TSAT can no longer be met, at any time, then TOBT must be updated by airline operator/ground handler.

Pilot should ensure that the flight is ready to depart at TOBT +/-5 minutes.

3.1.1.2. START REQUEST - HEATHROW DELIVERY

Pilot should report ready to HEATHROW Delivery at TOBT +/-5 minutes.

ATC will then approve start or in the case of a delay will advise the TSAT.

- Pilots to monitor the frequency from this point, as TSAT can improve up to TOBT.
- Pilots will be informed of an ATC delay to TSAT in excess of 5 minutes.

If at TOBT +5 minutes ATC have not received a start-up request the ACFT may lose its position in the sequence.

- ATC will advise the pilot that a new TOBT is required.
- The ACFT will not be allowed to depart until a valid TOBT is entered and revised TSAT given and complied with.

3.1.1.3. REMOTE HOLDING REQUEST

If an airline operator is aware of a CTOT and wishes to take the delay on a TWY rather than on the stand, then they should contact the Tower supervisor via phone to arrange it.

In this instance, TSAT will be adjusted to allow ACFT to be transferred to HEATHROW Ground earlier for remote hold.

3.1.2. DATALINK DEPARTURE CLEARANCE (DCL)

DCL via SITA or ARINC.

DCL available from 25 MIN prior to EOBT to 15 MIN after EOBT. Clearance will not be issued if requested later than 15 MIN after EOBT.

Successful clearance must be accepted within 5 MIN after receipt or a "Revert to voice" message will be received.

If the attempt to obtain a clearance is unsuccessful, the ACFT should revert to RTF. Regardless of clearance source, departing ACFT must report ACFT type, stand number, QNH and the identification letter of the received ATIS information to HEATHROW Delivery when fully ready for push-back and start.

In strong crosswind conditions (crosswind component above 35 KT), pilots are requested to advise Ground Movement Planning, on start-up, of their ACFT crosswind limitations. This is to enable better tactical planning at the Runway Holding point and a more efficient departure rate. In those conditions, this requirement will be confirmed through ATIS broadcast and NOTAM (if sufficient time allows).

3.1.3. START-UP

On first contact with HEATHROW Delivery, pilots are to report ACFT type, stand number, QNH and identification letter of received ATIS info.

Between 0630-1400LT and between 1500-2200LT pilots of operators who have been briefed with regard to the correct phraseology may call for ATC clearance up to 15MIN prior to being fully ready to push-back. All other operators must be fully ready before calling on frequency.

Pilots who wish to start engines on stand must request permission from HEATHROW Ground not later than 5 MIN after being transferred from Delivery.

All jet ACFT are to advise ATC, if for any reason they are unable to accelerate after noise abatement procedures to 250 KT.

EGLL/LHR
HEATHROW

JEPPESEN
26 FEB 16 10-1P7

LONDON, UK
AIRPORT BRIEFING

3. DEPARTURE

If within 30 minutes of a previously issued Calculated Take-off Time (CTOT) the flight is unable to comply with that CTOT, the pilot should advise ATC as soon as possible. Pilots are advised that delays in excess of 10 MIN can be expected at holding position. Sufficient time should be allowed for start, push-back and taxi to take account of such a delay especially if required to comply with a Calculated Take-off Time (CTOT).

3.1.4. PUSH-BACK

Following push-back from cul-de-sac stands, all ACFT must pull forward to a minimum of 328'/100m from the blast screen (indicated by a painted mark on the TWY centerline) before disconnecting the tug. Due to exhaust fume ingestion within the buildings at the end of all cul-de-sacs, engine start-up must be delayed until the ACFT has reached the 328'/100m mark.

Push-back/start clearance must be requested from HEATHROW Ground no later than 5 minutes after being transferred from Delivery.

Push-back approval includes permission to start engines during push-back.

3.2. NOISE ABATEMENT PROCEDURES

3.2.1. GENERAL

The following procedures may at any time be departed from to the extent necessary for avoiding immediate danger or for complying with ATC instructions.

Every operator of ACFT using the APT shall ensure at all times that ACFT are operated in a manner calculated to cause the least disturbance practicable in areas surrounding the airport.

After take-off operate ACFT so that it is at or above 1090' at 6.5km from start of roll as measured along the departure track and so that it will not cause more than:

- 94 dBA between 0700-2300LT
- 89 dBA between 2300-2330LT and between 0600-0700LT
- 87 dBA between 2330-0600LT

at any noise monitoring terminal. Jet ACFT maintain a minimum climb gradient of 243' per NM (4%) to at least 4000' to ensure progressively decreasing noise levels at points on the ground under the flight path beyond the monitoring terminal.

Noise preferential routing procedures applicable for all jet ACFT and other ACFT with MTWA of more than 5700kgs (between 0600-2330LT of more than 17000kgs and except any Dash 7 ACFT) are depicted on London Heathrow SID charts and on page 10-4.

3.2.2. NOISE QUOTA SYSTEM DURING NIGHT (2300-0700LT)

Main restrictions are as follows:

- Night Period (2300-0700LT)
- Night Quota Period (2330-0600LT)

The quota count is to be calculated based on the noise classification for the ACFT as follows:

Noise Classification	QUOTA Count
84 - 86.9	0.25
87 - 89.9	0.5
90 - 92.9	1
93 - 95.9	2
96 - 98.9	4
99 - 101.9	8
more than 101.9	16

EGLL/LHR
HEATHROW

7 MAY 10

JEPPesen

10-1P8

LONDON, UK
AIRPORT BRIEFING

3. DEPARTURE

3.4. RWY OPERATIONS

3.4.1. MINIMUM RWY OCCUPANCY TIME

On receipt of line up clearance pilots should ensure, commensurate with safety and standard operating procedures, that they are able to taxi into the correct position at the hold and line up on the RWY as soon as the preceding ACFT has commenced its take-off roll.

Pilots in receipt of a conditional line up clearance on a preceding departing ACFT (for example; 'ABC123, after the departing Sky Train DC10, line up RWY 27L via N2E') should remain behind the subject ACFT but may cross the RWY holding point (subject to there being no illuminated red stop bar) and enter the RWY upon receipt of the clearance. There is no requirement for the subject ACFT to have commenced its take-off roll before entering the RWY. Pilots must be aware that there may be a blast hazard as the ACFT on the RWY applies power.

Pilots in receipt of a conditional line up clearance on a preceding arriving ACFT (for example; 'ABC123, after the landing Sky Train DC10, line up RWY 27L via N2E') may cross the RWY holding point (subject to there being no illuminated red stop bar) as soon as the landing ACFT has passed the RWY entry point.

Pilots who require to back-track the RWY (including line up from N2W onto RWY 27L) must notify ATC prior to arrival at the holding point.

Pilots are advised that there is an increased risk of RWY Incursions when holding at N11 and NB11. Pilots may mistakenly believe that when on reaching the front of the queue, they have been given permission to line up in turn. Pilots are to be extra vigilant as to whether they have received a line-up clearance from ATC and seek confirmation where there is doubt.

Whenever possible, cockpit checks must be completed prior to line up and any checks requiring completion whilst on the RWY should be kept to the minimum required. Pilots should ensure that they are able to commence the take-off roll immediately after take-off clearance is issued.

Pilots not able to comply with these requirements should notify ATC as soon as possible once transferred to HEATHROW Tower.

3.4.2. RWY HOLDING AREAS

In promulgated holding areas, ATC may require ACFT to pass each other. Avoidance of other ACFT is the responsibility of the flight crew involved. If doubt exists as to whether other ACFT can be safely overtaken, ACFT must stop, advise ATC and request alternative instructions.

EGLL/LHR
HEATHROW

JEPPesen


LONDON, UK

3 FEB 12

10-1R

Eff 9 Feb

RADAR MINIMUM ALTITUDES



OUTSIDE THE DESIGNATED RADAR MINIMUM ALTITUDE AREA

The minimum altitude to be allocated by the radar controller will be either the Minimum Sector Altitude or 1000' above any fixed obstacles:

- within 5 NM ① of the aircraft and
- within the sector 15 NM ② ahead of and within 20° either side of the aircraft's track.

3 NM ① or 10 NM ② when the aircraft is within 15 NM of the radar antennae.

PROCEDURE	RWY	LOSS OF COMMUNICATION PROCEDURE
INITIAL APPROACH	09L/27R	Continue visually or by means of an appropriate approved final approach aid. If not possible proceed to CHT or last assigned level if higher.
	09R/27L	Continue visually or by means of an appropriate approved final approach aid. If not possible proceed to EPM or last assigned level if higher.
INTERMEDIATE AND FINAL APPROACH	09L/27R	Continue visually or by means of an appropriate approved final approach aid. If not possible follow the Missed Approach Procedure to CHT.
	09R/27L	Continue visually or by means of an appropriate approved final approach aid. If not possible follow the Missed Approach Procedure to EPM.

In all cases where the acft returns to the holding facility the procedures to be adopted are the Approach Radio Failure Procedures on charts 11-5/11-6.

EGLL/LHR
HEATHROW

JEPPesen
6 MAR 15 10-2


LONDON, UK
STAR

*D-ATIS 113.750 115.1 128.075 Apt Elev 83' Alt Set: hPa Trans level: By ATC Trans alt: 6000'

BIG 3D, BIG 1E, BIG 1F
ARRIVALS
DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED
VIA OCK 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

SPEED RESTRICTION
Cross SLP or 3 MIN before
holding facility at 250 KT or less.
■ SLP Speed Limit Point

WARNING
Do not proceed beyond
BIG
without ATC clearance.



HOLDING OVER BIG

Aircraft will be instructed by ATC to fly the appropriate FL.

DESCENT PLANNING
Pilots should plan for possible descent clearance as directed by ATC.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

STAR	ROUTING
BIG 3D ①	At LAM, LAM R-171 to HILLY, turn onto inbound holding, 303° track to BIG.
BIG 1E ①	At LOGAN, intercept DET R-055 inbound via KOPUL and TANET to DET, turn RIGHT, intercept BIG R-095 inbound to BIG.
BIG 1F	At SANDY, intercept BIG R-113 inbound to BIG.

① As directed by ATC. Not to be used for flight planning purposes.

113.750	*D-ATIS 115.1	128.075	Apt Elev 83'	Alt Set: hPa Trans level: By ATC	Trans alt: 6000'
---------	------------------	---------	-----------------	-------------------------------------	------------------

WEALD 3D [WEAL3D]
WEALD 1E [WEAL1E]
WEALD 1F [WEAL1F]

ARRIVALS


TO BE USED WHEN BIG VOR UNSERVICEABLE
DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED
VIA OCK 1G AS DIRECTED BY ATC

NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

**SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS**


WARNING

Do not proceed beyond
WEALD
without ATC clearance.



HOLDING OVER WEALD

Aircraft will be instructed by ATC to fly the appropriate FL.



Direct distance from WEALD to:
Heathrow Apt 21 NM

DESCENT PLANNING

Pilots should plan for possible descent clearance as as directed by ATC.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

STAR	ROUTING
WEALD 3D①	At LAM, LAM R-171 to HILLY, turn onto inbound holding, 318° track to WEALD.
WEALD 1E①	At LOGAN, intercept DET R-055 inbound via KOPUL and TANET to DET, turn RIGHT, DET R-275 to WEALD.
WEALD 1F	At SANDY, intercept DET R-130 inbound to DET, turn LEFT, DET R-275 to WEALD.

❗ As directed by ATC. Not to be used for flight planning purposes.

EGLL/LHR
HEATHROW

29 JAN 16 **10-2B** Eff 4 Feb

LONDON, UK
STAR

*D-ATIS Apt Elev Alt Set: hPa
113.750 115.1 128.075 83' Trans level: By ATC Trans alt: 6000'

BIG 4B, BIG 3C, BIG 1G

ARRIVALS

DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED
VIA OCK 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

DESCENT PLANNING

Pilots should plan for possible descent clearance as follows:

BIG 4B: FL180 by ETVAX,

BIG 3C, 1G: As directed by ATC.

ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

SPEED RESTRICTION

Cross SLP or 3 MIN before holding facility at 250 KT or less.

■ SLP Speed Limit Point


Direct distance from BIG to:
Heathrow Apt 21 NM



LAMBOURNE
D 115.6 LAM
N51 38.8 E000 09.1


WARNING

Do not proceed beyond
BIG
without ATC clearance.



HOLDINGS OVER BIG

Aircraft will be instructed
by ATC to fly the appropriate FL.



TIGER



STAR

ROUTING

BIG 4B

At ALESO, 316° track via ROTNO to ETVAX, 315° track to TIGER, intercept BIG R-136 inbound to BIG.

BIG 3C

At DVR, intercept LYD R-062 inbound to LYD, turn RIGHT, LYD R-285 to TIGER, turn RIGHT, intercept BIG R-136 inbound to BIG.

BIG 1G ①

At OCK, OCK R-106 to DORKI, turn LEFT, 080° track to HILLY, turn RIGHT to BIG.

① As directed by ATC. Not to be used for flight planning purposes.

EGLL/LHR
HEATHROW

JEPPesen
29 JAN 16 10-2C Eff 4 Feb

LONDON, UK
STAR

*D-ATIS 113.750 115.1 128.075 Apt Elev 83' Alt Set: hPa Trans level: By ATC Trans alt: 6000'

WEALD 4B [WEAL4B]

WEALD 3C [WEAL3C]

WEALD 1G [WEAL1G]

ARRIVALS

TO BE USED WHEN BIG VOR UNSERVICEABLE
DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED
VIA OCK 1G AS DIRECTED BY ATC

NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

**SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS**

LAMBOURNE
115.6 LAM
N51 38.8 E000 09.1

DESCENT PLANNING
Pilots should plan for possible descent
clearance as follows:
WEALD 4B: FL180 by ETVAX,
WEALD 3C, 1G: As directed by ATC.
**ACTUAL DESCENT
WILL BE AS DIRECTED BY ATC.**

DETLING
117.3 DET
N51 18.2 E000 35.8

DOVER
114.95 DVR
N51 09.8 E001 21.5


OCKHAM
115.3 OCK
N51 18.3 W000 26.8

Direct distance from WEALD to:
Heathrow Apt 21 NM

HOLDINGS OVER TIGER WEALD



Aircraft will be instructed
by ATC to fly the appropriate FL.



WARNING
Do not proceed beyond
WEALD
without ATC clearance.

STAR	ROUTING
WEALD 4B	At ALESO, 316° track via ROTNO to ETVAX, 315° track to TIGER, 317° track to WEALD.
WEALD 3C	At DVR, intercept LYD R-062 inbound to LYD, turn RIGHT, LYD R-285 to TIGER, turn RIGHT, 317° track to WEALD.
WEALD 1G ①	At OCK, OCK R-106 to DORKI, turn LEFT, 080° track to HILLY.

① As directed by ATC. Not to be used for flight planning purposes.

EGLL/LHR
HEATHROW

JEPPESSEN
6 MAR 15 10-2D

LONDON, UK
STAR

*D-ATIS	Apt Elev	Alt Set: hPa
113.750 115.1 128.075	83'	Trans level: By ATC Trans alt: 6000'

BNN 4A, BNN 1B, BNN 1C
BNN 1D, BNN 1E
ARRIVALS



- 1 STARs are to facilitate the transfer of traffic between terminal holding facilities and are for use only as directed by ATC, not to be used for flight planning purposes.
- 2 Aircraft will be instructed by ATC to fly the appropriate FL.
- 3 During periods of congestion in the London TMA, traffic may be required to hold at HON.

DESCENT PLANNING
Pilots should plan for possible descent clearance as follows:
BNN 4A: FL150 by SOPIT.
BNN 1B: FL200 by TOBID, FL150 by SOPIT.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

HOLDING OVER BNN

118°
7000'
298°

HOLDINGS OVER WCO

FL150 189° 009°
FL160 154° 334°
Do not exceed BNN 27 DME

SPEED RESTRICTION
Cross SLP or 3 MIN before holding facility at 250 KT or less.
■ SLP Speed Limit Point

WARNING
Do not proceed beyond BNN without ATC clearance.

STAR	ROUTING
BNN 4A	At HON, intercept HON R-141 via TOBID and SOPIT to WCO, turn LEFT, intercept BNN R-298 inbound to BNN.
BNN 1B	At NUGRA, 149° track to TOBID, turn LEFT, intercept HON R-141 via SOPIT to WCO, turn LEFT, intercept BNN R-298 inbound to BNN.
BNN 1C	At DTY, intercept DTY R-166 to WCO, turn LEFT, intercept BNN R-298 inbound to BNN.
BNN 1D	At KENET, intercept BNN R-252 inbound to BNN.
BNN 1E	At LAM, intercept LAM R-277 to DONNA, turn RIGHT, 118° track (holding track) to BNN.

EGLL/LHR
HEATHROW

JEPPesen
6 MAR 15 10-2E

LONDON, UK
STAR

*D-ATIS 113.750 115.1 128.075 Apt Elev 83' Alt Set: hPa Trans level: By ATC Trans alt: 6000'

BOVVA 4A [BOVA4A], BOVVA 1B [BOVA1B]
BOVVA 1C [BOVA1C], BOVVA 1D [BOVA1D] ①
BOVVA 1E [BOVA1E] ①

ARRIVALS

TO BE USED WHEN BNN VOR UNSERVICEABLE

SPEED CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS

WARNING

Do not proceed beyond
BOVVA
without ATC clearance.

- ① STARs are to facilitate the transfer of traffic between terminal holding facilities and are for use only as directed by ATC, not to be used for flight planning purposes.
- ② Aircraft will be instructed by ATC to fly the appropriate FL.
- ③ During periods of congestion in the London TMA, traffic may be required to hold at HON.

DESCENT PLANNING


Pilots should plan for possible descent clearance as follows:

BOVVA 4A: FL150 by SOPIT.

BOVVA 1B: FL200 by TOBID.

FL150 by SOPIT.

**ACTUAL DESCENT CLEARANCE
WILL BE AS DIRECTED BY ATC.**




STAR	ROUTING
BOVVA 4A	At HON, intercept HON R-141 via TOBID and SOPIT to WCO, turn LEFT, 117° bearing to BOVVA.
BOVVA 1B	At NUGRA, 149° track to TOBID, turn LEFT, intercept HON R-141 via SOPIT to WCO, turn LEFT, 117° bearing to BOVVA.
BOVVA 1C	At DTY, intercept DTY R-166 to WCO, turn LEFT, 117° bearing to BOVVA.
BOVVA 1D	At KENET, 071° track to BOVVA.
BOVVA 1E	At LAM, intercept LAM R-277 to DONNA, turn RIGHT, 139° track (holding track) to BOVVA.

113.750	*D-ATIS 115.1	128.075	Apt Elev 83'	Alt Set: hPa Trans level: By ATC	Trans alt: 6000'
---------	------------------	---------	-----------------	-------------------------------------	------------------

LAM 3A
ARRIVAL

DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED VIA
BIG 3D, BIG 1E, BNN 1E & OCK 1H AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES



DESCENT PLANNING

Pilots should plan for possible descent clearance as follows:

- FL250 by LOGAN (Aircraft Flight Planned at or above FL300 and all aircraft via airway UP-7),
- FL240 by LOGAN (Aircraft Flight Planned at or below FL290),
- FL160 by SARB.

ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

WARNING

Do not proceed beyond
LAM
without ATC clearance.

ROUTING

At LOGAN, intercept LAM R-084 inbound via TRIPO, SABER and BRASO to LAM.

- 1 Due to proximity of EG(D)-138 do not fly SOUTH of track Abeam CLIN until BRASO.
- 2 Aircraft will be instructed by ATC to fly the appropriate FL.

EGLL/LHR
HEATHROW



JEPPESSEN
29 JAN 16 (10-2G) Eff 4 Feb

LONDON, UK
STAR

113.750	*D-ATIS	128.075	Apt Elev 83'	Alt Set: hPa Trans level: By ATC	Trans alt: 6000'
115.1					

TAWNY 3A [TAWN3A]
ARRIVAL

TO BE USED WHEN LAM VOR UNSERVICEABLE
DURING PERIODS OF CONGESTION TRAFFIC MAY BE ROUTED VIA
BIG 3D, BIG 1E, BNN 1E & OCK 1H AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES
SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS



- 1 Due to proximity of EG(D)-138 do not fly SOUTH of track Abeam CLN until BRASO.
- 2 Aircraft will be instructed by ATC to fly the appropriate FL.

DESCENT PLANNING
Pilots should plan for possible descent clearance as follows:
FL250 by LOGAN (Aircraft Flight Planned at or above FL300 and all aircraft via airway UP-7),
FL240 by LOGAN (Aircraft Flight Planned at or below FL290),
FL160 by SABER.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

EGLL/LHR
HEATHROW

JEYPESEN
4 DEC 15 (10-2H)

LONDON, UK
STAR

*D-ATIS	Apt Elev	Alt Set: hPa
113.750 115.1 128.075	83'	Trans level: By ATC Trans alt: 6000'

OCK 1G, OCK 1H
ARRIVALS
FROM EAST

STARS ARE TO FACILITATE THE TRANSFER OF
TRAFFIC BETWEEN TERMINAL HOLDING FACILITIES
AND ARE FOR USE ONLY AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES
DURING PERIODS OF CONGESTION TRAFFIC MAY
BE ROUTED VIA BIG 1G AS DIRECTED BY ATC

**SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS**

WARNING

Do not proceed beyond
OCK
without ATC clearance.

LAMBOURNE
D(H) 115.6 LAM
N51 38.8 E000 09.1



216°

BIGGIN
D(H) 115.1 BIG
N51 19.9 E000 02.1



254°

OCK 1H
27.1

11.7

OCK 1G

DORKI
N51 16.6 W000 15.9

OCKHAM
D 115.3 OCK
N51 18.3 W000 26.8



7000'

R106°

330°




NOT TO SCALE

1 Aircraft will be instructed by
ATC to fly the appropriate FL.

DESCENT PLANNING
ACTUAL DESCENT CLEARANCE
WILL BE AS DIRECTED BY ATC.

Direct distance from OCK to:
Heathrow Apt 10NM


STAR	ROUTING
OCK 1G	At BIG, intercept BIG R-254 to DORKI, turn RIGHT, intercept OCK R-106 inbound to OCK.
OCK 1H	At LAM, intercept LAM R-216 to DORKI, turn RIGHT, intercept OCK R-106 inbound to OCK.



EGLL/LHR
HEATHROW

JEPPesen
25 MAR 16 10-2L

LONDON, UK
STAR



EGLL/LHR
HEATHROW

JEYPESEN
11 DEC 15 (10-2M)

LONDON, UK
STAR

113.750 *D-ATIS 115.1 128.075 Apt Elev 83' Alt Set: hPa
Trans level: By ATC Trans alt: 6000'


WARNING
Do not proceed beyond
OCK
without ATC clearance.

OCK 2C ①
OCK 3J
ARRIVALS

FROM SOUTHWEST
DURING PERIODS OF CONGESTION TRAFFIC MAY
BE ROUTED VIA BIG 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

Direct distance from OCK to:
Heathrow Apt 10NM

② Aircraft will be instructed
by ATC to fly the appro-
priate FL.



SPEED RESTRICTION
Cross SLP or 3 MIN before
holding facility at 250 KT or less.
■ SLP Speed Limit Point

DESCENT PLANNING
Pilots should plan for possible descent
clearance as follows:
OCK 2C: FL130 by HAZEL.
OCK 3J: FL270 by 27NM before BEWLI,
FL130 by HAZEL.
**ACTUAL DESCENT CLEARANCE
WILL BE AS DIRECTED BY ATC.**

① When OCK VOR is u/s, the
route will be to TOMMO.

ROUTING	
STAR	
OCK 2C	At SAM, intercept SAM R-079 to HAZEL, turn LEFT, intercept OCK R-230 inbound to OCK.
OCK 3J	At BEWLI, 090° track to BEGTO, turn LEFT, intercept LON R-215 inbound to HAZEL, turn RIGHT, intercept OCK R-230 inbound to OCK.
③	Not available for flight planning between 0600-2200LT.

EGLL/LHR
HEATHROW

JEPPESEN
11 DEC 15 (10-2N)

LONDON, UK
STAR

113.750 *D-ATIS 115.1 128.075

Apt Elev
83'

Alt Set: hPa
Trans level: By ATC Trans alt: 6000'

WARNING

Do not proceed beyond
TOMMO
without ATC clearance.

TOMMO 2C [TOMO2C]
TOMMO 3J [TOMO3J]

ARRIVALS

FROM SOUTHWEST

TO BE USED WHEN OCK VOR UNSERVICEABLE
DURING PERIODS OF CONGESTION TRAFFIC MAY
BE ROUTED VIA BIG 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES



**SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS**

Aircraft will be instructed
by ATC to fly the appropriate FL.

DESCENT PLANNING

Pilots should plan for possible descent
clearance as follows:
TOMMO 2C: FL130 by HAZEL.
TOMMO 3J: FL270 by 27NM before BEWLI,
FL130 by HAZEL.
**ACTUAL DESCENT CLEARANCE
WILL BE AS DIRECTED BY ATC.**

Direct distance from TOMMO to:
Heathrow Apt 10NM



ROUTING

STAR

At SAM, intercept SAM R-079 to HAZEL, turn LEFT, intercept LON R-215 inbound to FIMLI, turn RIGHT, intercept BIG R-267 inbound to TOMMO.

At BEWLI, 090° track to BEGTO, turn LEFT, intercept LON R-215 inbound via HAZEL to FIMLI, turn RIGHT, intercept BIG R-267 inbound to TOMMO.

Not available for flight planning between 0600-2200LT.

LONDON, UK
STAR

113.750	*D-ATIS 115.1	128.075	Apt Elev 83'	Alt Set: hPa Trans level: By ATC	Trans alt: 6000'
---------	------------------	---------	-----------------	-------------------------------------	------------------

OCK 1A^① , OCK 1D, OCK 2F ①
ARRIVALS

FROM WEST & NORTHWEST
DURING PERIODS OF CONGESTION TRAFFIC MAY BE
ROUTED VIA BIG 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES



WARNING

Do not proceed beyond
OCK
without ATC clearance.


SPEED RESTRICTION

Cross SLP or 3 MIN before
holding facility at 250 KT or less.

■ **SLP** Speed Limit Point

- ① During periods of congestion in the London TMA, traffic may be required to hold at OKESI.
- ② Aircraft will be instructed by ATC to fly the appropriate FL.

Direct distance from OCK to Heathrow Apt 10 NM



DESCENT PLANNING

Pilots should plan for possible descent clearance as follows:

OCK 1A: FL140 by 40 NM before OCK.

OCK 1D: As directed by ATC.

OCK 2F: FL140 by BEDEK.

**ACTUAL DESCENT CLEARANCE
BE AS DIRECTED BY ATC.**

STAR	ROUTING
OCK 1A	At KENET, intercept OCK R-291 inbound to OCK.
OCK 1D ③	At HON, HON R-153 to WOD, turn LEFT, intercept OCK R-300 inbound to OCK.
OCK 2F	At BEDEK, 104° track to NIGIT, turn LEFT, intercept OCK R-273 inbound to OCK.

③ By ATC. Not to be used for flight planning purposes.

EGLL/LHR
HEATHROW

JEPPESSEN
11 DEC 15 10-2Q

LONDON, UK
STAR

*D-ATIS 113.750 115.1 128.075 Apt Elev 83' Alt Set: hPa Trans level: By ATC Trans alt: 6000'

TOMMO 1A [TOMO1A] ①
TOMMO 1D [TOMO1D]
TOMMO 2F [TOMO2F] ①

ARRIVALS

FROM WEST & NORTHWEST

TO BE USED WHEN OCK VOR UNSERVICEABLE
DURING PERIODS OF CONGESTION TRAFFIC MAY
BE ROUTED VIA BIG 1G AS DIRECTED BY ATC
NOT TO BE USED FOR FLIGHT PLANNING PURPOSES

**SPEED: CROSS 3 MIN BEFORE HOLDING FACILITY
AT 250 KT OR LESS**




- ① During periods of congestion in the London TMA, traffic may be required to hold at OKESI.
- ② Aircraft will be instructed by ATC to fly the appropriate FL.

DESCENT PLANNING

Pilots should plan for possible descent clearance as follows:

TOMMO 1A: FL140 by 40 NM before TOMMO.
TOMMO 1D: As directed by ATC.
TOMMO 2F: FL140 by BEDEK.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

Direct distance from TOMMO to Heathrow Apt 10 NM



WARNING

Do not proceed beyond
TOMMO
without ATC clearance.

STAR

ROUTING

TOMMO 1A	At KENET, intercept CPT R-283 inbound to CPT, turn RIGHT, CPT R-109 to TOMMO.
TOMMO 1D ③	At HON, HON R-153 to WOD, turn LEFT, intercept CPT R-109 to TOMMO.
TOMMO 2F	At BEDEK, 104° track to NIGIT, turn LEFT, 091° track to TOMMO.

③ By ATC. Not to be used for flight planning purposes.

EGLL/LHR
HEATHROW

JEPPESSEN
4 DEC 15 (10-2S)

LONDON, UK
INITIAL APPROACH


*D-ATIS
113.750
115.1
128.075

Apt Elev
83'


- Alt Set: hPa Trans level: By ATC Trans alt: 6000'
1. Minimum holding level (Flight Level equivalent of 7000') is above TA and will be allocated by ATC.
 2. Initial approach procedures are designed for manoeuvring speeds up to 220 KT and assume acft can maintain a descent gradient of approximately 320' per NM.
 3. Continuous descent approach should be used whenever practicable unless otherwise instructed by ATC. Procedure design is compatible with 3° descent path from 6000'.
 4. Approximate distances to touchdown are indicated in brackets.

RWYS 09L/R, 27L/R
INITIAL APPROACH
WITHOUT RADAR CONTROL
FROM BIG TO ILS OR MLS

(IAF) BIGGIN
D 115.1 BIG
(H) 115.1
N51 19.9 E000 02.1
(RWYS 09L/R 48 NM)
(RWYS 27L/R 35 NM)



FOR FINAL APPROACH
SEE APPROACH CHARTS



ROUTING	
RWY	
09L/R	At BIG, intercept BIG R-275 to D29 BIG, turn RIGHT, intercept GWC R-359 to D35 GWC, turn RIGHT, establish on ILS IAA by D10 IAA (RWY 09L) or on ILS IBB by D10 IBB (RWY 09R).
27L/R	At BIG, intercept BIG R-273 to D9 BIG, turn RIGHT, 092° track, when crossing BIG R-301 turn LEFT, establish on ILS ILL by D10 ILL (RWY 27L) or on ILS IRR by D10 IRR (RWY 27R).

***D-ATIS**
113.750
115.1
128.075

Alt Set: hPA Trans level: By ATC Trans alt: 6000'

1. Minimum holding level (Flight Level equivalent of 7000') is above TA and will be allocated by ATC.
2. Initial approach procedures are designed for manoeuvring speeds up to 220 KT and assume acft can maintain a descent gradient of approximately 320' per NM.
3. Continuous descent approach should be used whenever practicable unless otherwise instructed by ATC. Procedure design is compatible with 3° descent path from 6000'.
4. Approximate distances to touchdown are indicated in brackets.

RWYS 09L/R, 27L/R
INITIAL APPROACH
WITHOUT RADAR CONTROL
FROM BNN TO ILS OR MLS

FOR FINAL APPROACH
SEE APPROACH CHARTS

ROUTING

At BNN, intercept BNN R-179 to D5 BNN, turn RIGHT, intercept LAM R-266 to D34 LAM, turn LEFT, intercept GWC R-359 inbound to D39 GWC, turn LEFT, establish on ILS IAA by D10 IAA (RWY 09L) or on ILS IBB by D10 IBB (RWY 09R).

At BNN, intercept BNN R-128 to D19 BNN, turn RIGHT, establish on ILS ILL by D10 ILL (RWY 27L) or on ILS IRR by D10 IRR (RWY 27R).

EGLL/LHR
HEATHROW

JEPPesen
4 DEC 15 (10-2U)


LONDON, UK
INITIAL APPROACH

*D-ATIS
113.750
115.1
128.075


Apt Elev
83'

- Alt Set: hPa Trans level: By ATC Trans alt: 6000'
1. Minimum holding level (Flight Level equivalent of 7000') is above TA and will be allocated by ATC.
 2. Initial approach procedures are designed for manoeuvring speeds up to 220 KT and assume acft can maintain a descent gradient of approximately 320' per NM.
 3. Continuous descent approach should be used whenever practicable unless otherwise instructed by ATC. Procedure design is compatible with 3° descent path from 6000'.
 4. Approximate distances to touchdown are indicated in brackets.

RWYS 09L/R, 27L/R
INITIAL APPROACH
WITHOUT RADAR CONTROL
FROM LAM TO ILS OR MLS



ROUTING	
RWY	
09L/R	At LAM, intercept LAM R-266 to D34 LAM, turn LEFT, intercept GWC R-359 inbound to D39 GWC, turn LEFT, establish on ILS IAA by D10 IAA (RWY 09L) or on ILS IBB by D10 IBB (RWY 09R).
27L/R	At LAM, intercept LAM R-274 to D11 LAM, turn LEFT, intercept BNN R-128 to D19 BNN, turn RIGHT, establish on ILS ILL by D10 ILL (RWY 27L) or on ILS IRR by D10 IRR (RWY 27R).



EGLL/LHR
HEATHROW

JEPPESSEN
4 OCT 13 (10-3) Eff 17 Oct


LONDON, UK
SID

LONDON Control 118.82	Apt Elev 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
--------------------------	-----------------	---

BROOKMANS PARK SEVEN FOXTROT (BPK 7F)
BROOKMANS PARK SEVEN GOLF (BPK 7G)
RWYS 27R/L DEPARTURES
~~SPEED~~ MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED

WARNING: Due to interaction with other routes do not climb above 6000' until cleared by ATC.

AVERAGE TRACK MILEAGE
32 NM to BPK.



Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000' for ATM purposes.

Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to take-off.

SID	RWY	ROUTING / ALTITUDE
BPK 7F	27R	Climb straight ahead, intercept 299° bearing towards BUR by D4 LON, at D6 LON turn RIGHT, intercept 056° bearing towards CHT, cross LON R-306 at or above 4000' (MAX 6000'), LON R-327 at or above 5000' (MAX 6000'), to CHT at 6000', turn RIGHT, intercept BPK R-245 inbound to BPK.
BPK 7G	27L	Climb straight ahead, intercept 299° bearing towards BUR by D3 LON, at D6 LON turn RIGHT, intercept 056° bearing towards CHT, cross LON R-306 at or above 4000' (MAX 6000'), LON R-327 at or above 5000' (MAX 6000'), to CHT at 6000', turn RIGHT, intercept BPK R-245 inbound to BPK.

EGLL/LHR
HEATHROW

JEPPESSEN
4 OCT 13 (10-3A) Eff 17 Oct

LONDON, UK
SID

LONDON Control 118.82	Apt Elev 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
--------------------------	-----------------	---


BROOKMANS PARK SIX JULIETT (BPK 6J)
BROOKMANS PARK FIVE KILO (BPK 5K)
RWYS 09R/L DEPARTURES
~~SPEED~~ MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED

WARNING: Due to interaction with other routes do not climb above 6000' until cleared by ATC.



WARNING
No turns below 590'.

LONDON
D(H) 113.6 LON
N51 29.2 W000 28.0




D10 LON
N51 32.5 W000 12.8
6000'
3000'

D10 BPK
6000'
4000'

D6 BPK
6000'

BAPAG
N51 43.1 W000 07.4
(LON R-044/D18.9)

BROOKMANS PARK
D(H) 117.5 BPK
N51 45.0 W000 06.4



AVERAGE TRACK MILEAGE
23 NM to BPK.

Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000' for ATM purposes.

Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to take-off.

SID	RWY	ROUTING / ALTITUDE
BPK 6J	09R	Climb straight ahead, at LON 2 DME turn LEFT, 052° track, intercept LON R-072, cross D10 LON at or above 3000' (MAX 6000'), turn LEFT, intercept BPK R-197 inbound, cross D10 BPK at or above 4000' (MAX 6000'), D6 BPK at 6000', via BAPAG to BPK.
BPK 5K	09L	Climb straight ahead, at LON 1.5 DME turn LEFT, 052° track, intercept LON R-072, cross D10 LON at or above 3000' (MAX 6000'), turn LEFT, intercept BPK R-197 inbound, cross D10 BPK at or above 4000' (MAX 6000'), D6 BPK at 6000', via BAPAG to BPK.

EGLL/LHR
HEATHROW


JEPPESSEN
4 OCT 13 (10-3B) Eff 17 Oct

LONDON, UK
SID

LONDON Control
119.77

Apt Elev
83'

- Trans level: By ATC Trans alt: 6000'
1. When instructed contact LONDON Control.
 2. SIDs include noise preferential routes (refer to 10-4).
 3. Cruising levels will be issued after take-off by LONDON Control.
 4. Do not climb above SID levels until instructed by ATC.



SID	RWY	ROUTING / ALTITUDE
BUZAD 4J	09R	Climb straight ahead, at LON 2 DME turn LEFT, 052° track, intercept LON R-072, cross D10 LON at or above 3000' (MAX 6000'), turn LEFT, intercept BIG R-331, cross D20 BIG at or above 5000' (MAX 6000'), D23 BIG at 6000', to BUZAD.
BUZAD 3K	09L	Climb straight ahead, at LON 1.5 DME turn LEFT, 052° track, intercept LON R-072, cross D10 LON at or above 3000' (MAX 6000'), turn LEFT, intercept BIG R-331, cross D20 BIG at or above 5000' (MAX 6000'), D23 BIG at 6000', to BUZAD.

LONDON Control
134.12

Apt Elev
83'

Trans level: By ATC Trans alt: 6000'
1. When instructed contact LONDON Control.
2. SIDs include noise preferential routes (refer to 10-4).
3. Cruising levels will be issued after take-off by LONDON Control.
4. Do not climb above SID levels until instructed by ATC.

COMPTON THREE FOXTROT (CPT 3F)
COMPTON THREE GOLF (CPT 3G)
RWYS 27R/L DEPARTURES
~~SPEED~~ MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED

WARNING: Due to interaction with other routes do not climb above **6000'** until cleared by ATC.


Gnd speed-KT	75	100	150	200	250	300
5% V/V (fpm)	380	506	760	1013	1266	1519
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to take-off.

AVERAGE TRACK MILEAGE
15 NM to WOD.

ROUTING / ALTITUDE		
SID	RWY	
CPT 3F	27R	Straight ahead, intercept LON R-257 to D7 LON, turn RIGHT, intercept 270° bearing towards WOD (D13 CPT), cross D11 LON (D17 CPT) above 3000' (MAX 6000'), cross WOD (D13 CPT) above 4000' (MAX 6000'), then to CPT, cross D8 CPT at 6000'.
CPT 3G	27L	

Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000'.
These SIDs require a minimum climb gradient of 5% until D8 CPT due to ATC and airspace purposes.



EGLL/LHR
HEATHROW

JEPPESSEN
3 OCT 14 (10-3D)

LONDON, UK
SID


*HEATHROW
Director
134.975

Apt Elev
83'

- Trans level: By ATC Trans alt: 6000'
1. When instructed contact HEATHROW Director after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
 2. SIDs include noise preferential routes (refer to 10-4).
 3. Cruising levels will be issued after take-off by HEATHROW Director.
 4. Do not climb above SID levels until instructed by ATC.


COMPTON FIVE JULIETT (CPT 5J)
COMPTON FOUR KILO (CPT 4K)
RWYS 09R/L DEPARTURES
~~SPEED~~ MAX 250 KT
BELOW FL100 UNLESS
OTHERWISE AUTHORISED

WARNING
No turns below 590'.



AVERAGE TRACK MILEAGE
CPT 5J: 21 NM to WOD.
CPT 4K: 22 NM to WOD.

WARNING: Due to interaction with other routes do not climb above 6000' until cleared by ATC.




Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000'.
These SIDs require a minimum climb gradient of 3.5% until D8 CPT.

Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215
3.5% V/V (fpm)	266	354	532	709	886	1063


If unable to comply with SID or climb gradient inform ATC prior to take-off.

SID	RWY	ROUTING / ALTITUDE
CPT 5J	09R	Straight ahead, at LON 2 DME turn RIGHT, intercept 282° bearing towards WOD, cross D11 LON (D17 CPT) above 3000' (MAX 6000'), WOD (D13 CPT) above 4000' (MAX 6000'), then to CPT, cross D8 CPT at 6000'.
CPT 4K	09L	Straight ahead, at LON 1.5 DME turn RIGHT, intercept 282° bearing towards WOD, cross D11 LON (D17 CPT) above 3000' (MAX 6000'), WOD (D13 CPT) above 4000' (MAX 6000'), then to CPT, cross D8 CPT at 6000'.

LONDON Control 120.525	<i>Apt Elev</i> 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
---------------------------	------------------------	---



LONDON Control 120.525	Apt Elev 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
---------------------------	-----------------	---



DETILING ONE JULIETT (DET 1J)
DETILING ONE KILO (DET 1K)
RWYS 09R/L DEPARTURES
SPEED: MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED

SID	RWY	ROUTING / ALTITUDE
DET 1J	09R	Straight ahead, at LON 2 DME turn RIGHT, 122° track, at LON 4 DME turn LEFT, intercept DET R-284 inbound by D34 DET, cross D29 DET at or above 3000' (MAX 6000'), D20 DET at or above 5000' (MAX 6000'), D16 DET at 6000'. D5 DET at 6000', then to DET.
DET 1K	09L	Straight ahead, at LON 1.5 DME turn RIGHT, 122° track, at LON 4 DME turn LEFT, intercept DET R-284 inbound by D34 DET, cross D29 DET at or above 3000' (MAX 6000'), D20 DET at or above 5000' (MAX 6000'), D16 DET at 6000'. D5 DET at 6000', then to DET.

Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of


Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

not able to comply with 31D or climb gradient inform ATC prior to departure.

WARNING: Due to interaction with other routes do not climb above 6000' until cleared by ATC.

AVERAGE TRACK MILEAGE
41 NM to DET.

WARNING
No turns below **590'**.



EGLL/LHR
HEATHROW

 **JEPPESSEN**
19 JUN 15 **(10-3G)** **Eff 25 Jun**

LONDON, UK
SID

LONDON Control
134.125

Apt Elev
83'

Trans level: By ATC Trans alt: 6000'

1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
2. SIDs include noise preferential routes (refer to 10-4).
3. Cruising levels will be issued after take-off by LONDON Control.
4. Do not climb above SID levels until instructed by ATC.


GASGU ONE JULIETT (GASGU 1J) [GASG1J]

GASGU ONE KILO (GASGU 1K) [GASG1K]

RWYS 09R/L DEPARTURES

SPEED: MAX 250 KT BELOW FL100

UNLESS OTHERWISE AUTHORISED



SID	RWY	ROUTING / ALTITUDE
GASGU 1J	09R	Straight ahead, at LON 2 DME turn RIGHT, intercept LON R-126 to D5 LON, turn RIGHT, intercept OCK R-043 inbound, cross D2 OCK above 3000' (MAX 6000'), turn RIGHT, intercept OCK R-255, cross D3 OCK above 4000' (MAX 6000'), D7 OCK above 5000' (MAX 6000'), D11 OCK at 6000' to GASGU.
GASGU 1K	09L	Straight ahead, at LON 1.5 DME turn RIGHT, intercept LON R-126 to D5 LON, turn RIGHT, intercept OCK R-043 inbound, cross D2 OCK above 3000' (MAX 6000'), turn RIGHT, intercept OCK R-255, cross D3 OCK above 4000' (MAX 6000'), D7 OCK above 5000' (MAX 6000'), D11 OCK at 6000' to GASGU.


EGLL/LHR
HEATHROW

JEYPESEN
19 JUN 15 (10-3H) Eff 25 Jun

LONDON, UK
SID

LONDON Control 134.125	Apt Elev 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
---------------------------	-----------------	---

GOGSI ONE FOXTROT (GOGSI 1F) [GOGSI1F]
GOGSI ONE GOLF (GOGSI 1G) [GOGSI1G]
RWYS 27R/L DEPARTURES
SPEED: MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED



EGLL/LHR
HEATHROW

JEPPESSEN
19 JUN 15 (10-3J) Eff 25 Jun

LONDON, UK
SID

LONDON Control
126.825

Apt Elev
83'

Trans level: By ATC Trans alt: 6000'

1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
2. SIDs include noise preferential routes (refer to 10-4).
3. Cruising levels will be issued after take-off by LONDON Control.
4. Do not climb above SID levels until instructed by ATC.
5. Aircraft VOR or DME failure advise ATC and comply with ATC instructions.

MAYFIELD THREE FOXTROT (MAY 3F)


MAYFIELD TWO GOLF (MAY 2G)

RWYS 27R/L DEPARTURES

TO EGKK ONLY

SPEED: MAX 250 KT BELOW FL100

UNLESS OTHERWISE AUTHORISED



Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to departure.

SID	RWY	ROUTING / ALTITUDE
MAY 3F	27R	Straight ahead, at LON 2 DME turn LEFT, intercept 138° bearing to EPM, cross at 5000', at EPM but not before D10 LON intercept MAY R-316 inbound to MAY at 5000'.
MAY 2G	27L	Straight ahead, at ILL 1 DME (LON 2 DME if ILL u/s) turn LEFT, intercept 138° bearing to EPM, cross at 5000', at EPM but not before D10 LON intercept MAY R-316 inbound to MAY at 5000'.

EGLL/LHR
HEATHROW

JEPPESSEN
19 JUN 15 **(10-3K)** **Eff 25 Jun**

LONDON, UK
SID


LONDON Control
126.825

Apt Elev
83'

- Trans level: By ATC Trans alt: 6000'
1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
 2. SIDs include noise preferential routes (refer to 10-4).
 3. Cruising levels will be issued after take-off by LONDON Control.
 4. Do not climb above SID levels until instructed by ATC.
 5. Aircraft VOR or DME failure advise ATC and comply with ATC instructions.

MAYFIELD TWO JULIETT (MAY 2J)
MAYFIELD TWO KILO (MAY 2K)
RWYS 09R/L DEPARTURES
TO EGKK ONLY

SPEED: MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED



Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000'.

Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to departure.

SID	RWY	ROUTING / ALTITUDE
MAY 2J	09R	Straight ahead, at LON 2 DME turn RIGHT, intercept LON R-126 to D3.5 LON, turn RIGHT, intercept MID R-027 inbound to D20 MID, cross at 5000', turn LEFT, intercept MAY R-316 inbound to MAY at 5000'.
MAY 2K	09L	Straight ahead, at LON 1.5 DME turn RIGHT, intercept LON R-126 to D3.5 LON, turn RIGHT, intercept MID R-027 inbound to D20 MID, cross at 5000', turn LEFT, intercept MAY R-316 inbound to MAY at 5000'.

EGLL/LHR
HEATHROW

JEPPESSEN
19 JUN 15 (10-3L) Eff 25 Jun

LONDON, UK
SID

LONDON Control
133.175

Apt Elev
83'


- Trans level: By ATC Trans alt: 6000'
1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
 2. SIDs include noise preferential routes (refer to 10-4).
 3. Cruising levels will be issued after take-off by LONDON Control.
 4. Do not climb above SID levels until instructed by ATC.

MIDHURST FOUR FOXTROT (MID 4F)

MIDHURST THREE GOLF (MID 3G)

RWYS 27R/L DEPARTURES

SPEED: MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED



SID	RWY	ROUTING / ALTITUDE
MID 4F	27R	Straight ahead, intercept LON R-257 to D5 LON, turn LEFT, intercept 162° bearing from BUR, cross D8 LON above 3000' (MAX 6000'), D12 LON above 4000' (MAX 6000'), turn RIGHT, intercept MID R-012 inbound, cross D17 LON (D10 MID) above 5000' (MAX 6000'), then to MID at 6000'.
MID 3G	27L	Straight ahead, intercept LON R-241 to D5.5 LON, turn LEFT, intercept 162° bearing from BUR, cross D8 LON above 3000' (MAX 6000'), D12 LON above 4000' (MAX 6000'), turn RIGHT, intercept MID R-012 inbound, cross D17 LON (D10 MID) above 5000' (MAX 6000'), then to MID at 6000'.

EGLL/LHR
HEATHROW

JEPPESSEN
19 JUN 15 **(10-3M)** **Eff 25 Jun**

LONDON, UK
SID

LONDON Control
133.175

Apt Elev
83'

Trans level: By ATC Trans alt: 6000'

1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.
2. SIDs include noise preferential routes (refer to 10-4).
3. Cruising levels will be issued after take-off by LONDON Control.
4. Do not climb above SID levels until instructed by ATC.

MIDHURST THREE JULIETT (MID 3J)


MIDHURST THREE KILO (MID 3K)

RWYS 09R/L DEPARTURES

SPEED: MAX 250 KT BELOW FL100

UNLESS OTHERWISE AUTHORISED

LONDON
D (H) 113.6 LON
NS1 29.2 W000 28.0



WARNING
No turns below **590'**.

WARNING: Due to interaction with other routes: do not climb above **6000'** until cleared by ATC.


D19 MID
6000'
3000'

D15 MID
6000'
4000'

D12 MID
6000'
5000'

D8 MID
6000'

MIDHURST
D (H) 114.0 MID
NS1 03.2 W000 37.5



AVERAGE TRACK MILEAGE
29 NM to MID.

Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000'.

MID 3J

5% until D19 MID due to ATC and airspace purposes.

MID 3K

4.8% until D19 MID due to ATC and airspace purposes.

Gnd speed-KT	75	100	150	200	250	300
5% V/V (fpm)	380	506	760	1013	1266	1519
4.8% V/V (fpm)	365	486	729	972	1215	1458
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to departure.

SID	RWY	ROUTING / ALTITUDE
MID 3J	09R	Straight ahead, at LON 2 DME turn RIGHT, intercept LON R-126 to D3.5 LON, turn RIGHT, intercept MID R-027 inbound, cross D19 MID at or above 3000' (MAX 6000'), D15 MID at or above 4000' (MAX 6000'), D12 MID at or above 5000' (MAX 6000'), D8 MID at 6000', then to MID at 6000'.
MID 3K	09L	Straight ahead, at LON 1.5 DME turn RIGHT, intercept LON R-126 to D3.5 LON, turn RIGHT, intercept MID R-027 inbound, cross D19 MID at or above 3000' (MAX 6000'), D15 MID at or above 4000' (MAX 6000'), D12 MID at or above 5000' (MAX 6000'), D8 MID at 6000', then to MID at 6000'.


EGLL/LHR
HEATHROW

JEPPESSEN
19 JUN 15 (10-3N) Eff 25 Jun

LONDON, UK
SID

LONDON Control 119.775	Apt Elev 83'	Trans level: By ATC Trans alt: 6000' 1. When instructed contact LONDON Control after take-off, report C/S, SID designator, current altitude and initial cleared altitude.. 2. SIDs include noise preferential routes (refer to 10-4). 3. Cruising levels will be issued after take-off by LONDON Control. 4. Do not climb above SID levels until instructed by ATC.
---------------------------	-----------------	--

WOBUN THREE FOXTROT (WOBUN 3F) [WOBU3F]
WOBUN THREE GOLF (WOBUN 3G) [WOBU3G]
RWYS 27R/L DEPARTURES
SPEED: MAX 250 KT BELOW FL100
UNLESS OTHERWISE AUTHORISED



Cross appropriate Noise Monitoring Terminal (refer to chart 10-4) at or above 1090', thereafter maintain a minimum climb gradient of 4% up to 4000' for ATM purposes.

Gnd speed-KT	75	100	150	200	250	300
4% V/V (fpm)	304	405	608	810	1013	1215

If unable to comply with SID or climb gradient inform ATC prior to departure.


SID	RWY	ROUTING / ALTITUDE
WOBUN 3F	27R	Climb straight ahead, intercept 299° bearing towards BUR by D4 LON to D7 LON, turn RIGHT, intercept 357° bearing from BUR (MID R-357), cross LON 8 DME at or above 3000' (MAX 6000'), D10 LON at or above 4000' (MAX 6000'), D14 LON at 6000' to WOBUN.
WOBUN 3G	27L	Climb straight ahead, intercept 299° bearing towards BUR by D3 LON to D7 LON, turn RIGHT, intercept 357° bearing from BUR (MID R-357), cross LON 8 DME at or above 3000' (MAX 6000'), D10 LON at or above 4000' (MAX 6000'), D14 LON at 6000' to WOBUN.

Tailwind component	≤ 1 KT	≤ 2 KT	≤ 3 KT	≤ 4 KT	> 4 KT
Amount to be disregarded	0.4 dB	0.8 dB	1.2 dB	1.6 dB	2.0 dB

EGLL/LHR
Apt Elev 83'
N51 28.7 W000 27.7

JEPPESSEN
27 MAY 16 10-9


LONDON, UK
HEATHROW



EGLL/LHR

LONDON, UK
HEATHROW


ADDITIONAL RUNWAY INFORMATION				USABLE LENGTHS		TAKE-OFF	WIDTH				
RWY				— LANDING BEYOND —							
				Threshold	Glide Slope						
09L	① 27R	HIRL (60m) CL (15m) HIALS-II TDZ PAPI-L (3.0°)	RVR	11,785' 3592m	10,813' 3296m	②	164' 50m				
				12,736' 3882m	11,642' 3548m						
① RWY grooved.											
② TAKE-OFF RUN AVAILABLE											
RWY 09L:			RWY 27R:								
			From rwy head	12,799' (3901m)	From rwy head	12,736' (3882m)					
			twy A12 int	11,030' (3362m)	twy A4 int	11,611' (3539m)					
			twy A11 int	9311' (2838m)	twy A5 int	10,289' (3136m)					
			twy A10W int	8730' (2661m)	twy A6 int	9390' (2862m)					
			twy A10E int	7723' (2354m)	twy A7 int	8586' (2617m)					
			twy A9W int	6535' (1992m)	twy A8 int	7920' (2414m)					
			twy A9E int	5869' (1789m)	twy A9E int	7028' (2142m)					
					twy A9W int	6388' (1947m)					
09R			③ 27L	HIRL (60m) CL (15m) HIALS-II TDZ PAPI-L (3.0°)	RVR	10,991' 3350m	9958' 3035m	⑤	164' 50m		
		10,907' 3324m									
③ RWY grooved.											
④ HST - N6											
⑤ TAKE-OFF RUN AVAILABLE											
RWY 09R:			RWY 27L:								
	From rwy head	12,001' (3658m)	From rwy head	12,001' (3658m)							
	twy N10 int	11,575' (3528m)	twy N2E int	11,601' (3536m)							
	twy N8 int	10,994' (3351m)	twy N2W int	11,089' (3380m)							
	twy SB7 int	9360' (2853m)	twy N3 int	10,577' (3224m)							
	twy N7 int	9357' (2852m)	twy S3 int	10,538' (3212m)							
	twy N6 int	7628' (2325m)	twy N4E int	8865' (2702m)							
	twy S6 int	7362' (2244m)	twy S4W int	8550' (2606m)							
	twy N5W int	5591' (1704m)	twy S4E int	8494' (2589m)							
			twy N4W int	8009' (2441m)							
			twy S5E int	7290' (2222m)							
			twy N5E int	6860' (2091m)							
			twy S5W int	6827' (2081m)							
HOT SPOTS											
(For information only, not to be construed as ATC instructions.)											
HS1	Pilots are to ensure they have clearance to enter the RWY before crossing the holding point.										
HS2	Pilots are to maintain a good lookout at all times and are responsible for wing tip clearance.										
HS3											
SEQUENCING OF AIRCRAFT GROUND MOVEMENTS											
FOR TAKE-OFF IN LOW VISIBILITY											
When the reported RVR is below 400m do not request start-up until the reported RVR is equal to or greater than the appropriate value as shown below:											
AIRCRAFT TAKE-OFF MINIMA				MINIMUM RVR FOR START-UP							
350m RVR				300m							
300m RVR				250m							
250m RVR				200m							
200m RVR				150m							
150m RVR				150m							
100m RVR				100m							
75m RVR				75m							
Standard TAKE-OFF ①											
LVP must be in Force											
Approved Operators HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL	NIL (DAY only)						
A											
B	125m	150m	200m	250m	400m	500m					
C											
D	150m	200m	250m	300m							
① Operators applying U.S. Ops Specs: CL required below 300m; approved HUD required below 150m.											



EGLL/LHR

JEPPesen
29 JAN 16 10-9D Eff 4 Feb

LONDON, UK
HEATHROW



EGLL/LHR



JEPPESSEN

29 JAN 16

10-9E

Eff 4 Feb

LONDON, UK

HEATHROW

INS COORDINATES			
STAND No.	COORDINATES	STAND No.	COORDINATES
103	N51 28.5 W000 27.1	307	N51 28.1 W000 27.5
104	N51 28.4 W000 27.0	309	N51 28.1 W000 27.6
105	N51 28.5 W000 27.0	311	N51 28.2 W000 27.6
106	N51 28.4 W000 26.9	313	N51 28.1 W000 27.7
117, 119	N51 28.4 W000 26.9	316	N51 28.1 W000 27.8
120, 121, 121L	N51 28.4 W000 26.8	317	N51 28.1 W000 27.9
121R	N51 28.4 W000 26.9	318	N51 28.2 W000 27.7
122	N51 28.3 W000 26.8	319	N51 28.2 W000 27.9
139, 141	N51 28.3 W000 26.7	320	N51 28.2 W000 27.8
216 thru 218R	N51 28.2 W000 26.8	321	N51 28.2 W000 28.0
219, 220	N51 28.1 W000 26.8	322	N51 28.3 W000 27.8
221, 221L/R	N51 28.1 W000 26.9	323	N51 28.2 W000 27.7
223, 224	N51 28.1 W000 27.0	325	N51 28.3 W000 27.7
225, 226	N51 28.1 W000 27.1	326	N51 28.4 W000 27.6
231 thru 233R	N51 28.4 W000 26.7	327	N51 28.3 W000 27.7
236 thru 238	N51 28.2 W000 26.7	328	N51 28.4 W000 27.7
239	N51 28.1 W000 26.7	329	N51 28.3 W000 27.8
241	N51 28.1 W000 26.5	330	N51 28.4 W000 27.7
242 thru 243R	N51 28.2 W000 26.5	331	N51 28.3 W000 27.8
244 thru 246R	N51 28.3 W000 26.5	332, 334	N51 28.5 W000 27.8
247	N51 28.4 W000 26.5	335	N51 28.4 W000 27.9
247L	N51 28.3 W000 26.5	336	N51 28.5 W000 27.9
247R thru 249	N51 28.4 W000 26.5	340, 340L	N51 28.5 W000 28.0
251	N51 28.1 W000 26.4	340R, 342	N51 28.4 W000 28.0
252 thru 253R	N51 28.2 W000 26.4	351, 353	N51 28.4 W000 27.6
254, 254L	N51 28.3 W000 26.4	355	N51 28.5 W000 27.6
254R	N51 28.2 W000 26.4	357, 357 L/R	N51 28.5 W000 27.5
255, L/R	N51 28.3 W000 26.4	363	N51 28.2 W000 28.0
256 thru 258	N51 28.4 W000 26.4	364	N51 28.3 W000 27.9
258L	N51 28.5 W000 26.4	365	N51 28.3 W000 28.0
258R	N51 28.4 W000 26.4		
301	N51 28.1 W000 27.3		
303L	N51 28.1 W000 27.4		
303, 303R	N51 28.1 W000 27.3		
305, 305L/R	N51 28.1 W000 27.4		

EGLL/LHR


JEPPESSEN
29 JAN 16 (10-9F)

Eff 4 Feb

LONDON, UK
HEATHROW

INS COORDINATES			
STAND No.	COORDINATES	STAND No.	COORDINATES
401	N51 27.5 W000 26.9	547L thru 548L	N51 28.4 W000 28.8
402	N51 27.5 W000 27.0	548R	N51 28.5 W000 28.8
403	N51 27.4 W000 27.0	551	N51 28.1 W000 28.7
405	N51 27.5 W000 27.1	552 thru 554	N51 28.2 W000 28.7
406	N51 27.6 W000 27.1	555, 556	N51 28.3 W000 28.7
407, 408	N51 27.6 W000 27.0	557, 558	N51 28.4 W000 28.7
409 thru 410R	N51 27.7 W000 26.9	561, 562	N51 28.4 W000 28.5
411	N51 27.7 W000 26.8	563, 564	N51 28.3 W000 28.5
412	N51 27.8 W000 26.8	565, 566	N51 28.2 W000 28.5
414 thru 419	N51 27.7 W000 26.6	567, 568	N51 28.1 W000 28.5
420	N51 27.7 W000 26.7	572	N51 28.4 W000 28.4
421	N51 27.6 W000 26.7	573	N51 28.3 W000 28.4
422, 423	N51 27.6 W000 26.6	575, 576	N51 28.2 W000 28.4
424	N51 27.7 W000 26.6	581, 582	N51 28.1 W000 28.3
425	N51 27.7 W000 26.5	583	N51 28.1 W000 28.2
440	N51 27.6 W000 27.1	590 thru 592	N51 28.2 W000 28.2
441	N51 27.7 W000 27.0	594	N51 28.3 W000 28.2
449 thru 452	N51 27.5 W000 27.3	595, 596	N51 28.4 W000 28.2
453	N51 27.6 W000 27.2	601	N51 27.8 W000 27.5
454	N51 27.6 W000 27.3	602, 603	N51 27.8 W000 27.6
455, 456	N51 27.7 W000 27.3	604	N51 27.8 W000 27.7
457L	N51 27.7 W000 27.4	605, 606	N51 27.8 W000 27.8
457, 457R	N51 27.8 W000 27.4	607	N51 27.8 W000 27.9
461	N51 27.5 W000 27.2	608, 609	N51 27.8 W000 28.0
501	N51 28.5 W000 29.4	611, 612	N51 27.7 W000 28.3
502, 503, 505	N51 28.5 W000 29.3	613	N51 27.6 W000 28.3
506 thru 509	N51 28.4 W000 29.1	614	N51 27.6 W000 28.4
511 thru 515	N51 28.3 W000 29.1	615, 616	N51 27.7 W000 28.4
516 thru 518	N51 28.2 W000 29.1		
519	N51 28.1 W000 29.1		
520, 521	N51 28.1 W000 29.2		
522 thru 525	N51 28.1 W000 29.3		
526, 527	N51 28.1 W000 29.2		
531, 532	N51 28.4 W000 29.0		
533 thru 535	N51 28.3 W000 29.0		
536, 537	N51 28.2 W000 29.0		
538, 539	N51 28.1 W000 29.0		
541, 542	N51 28.1 W000 28.8		
543 thru 544R	N51 28.2 W000 28.8		
545L thru 546R	N51 28.3 W000 28.8		

EGLL/LHR


JEPPESSEN
 29 JAN 16 **(10-9G)**
Eff 4 Feb
LONDON, UK
HEATHROW

STAND ENTRY GUIDANCE SYSTEMS (SEG)

A. GENERAL

If a Stand Entry Guidance System becomes unserviceable or is not illuminated, call Ground Movement Control (GMC) to request marshalling assistance.

Aircrew must not attempt to self-park if the Stand Entry Guidance is unserviceable, uncalibrated or not switched on.

STOP SHORT PROCEDURE

The term "STOP SHORT" is defined as a requirement to stop the acft in a position that allows mobile or integral airstairs to be deployed, due to the unserviceability of the stand loading bridge or some other obstruction. The requirement to "STOP SHORT" will be indicated to the flight crew by marshalling signals.

EMERGENCY STOP


Should an emergency arise as the acft is taxiing onto stand, the airline or handling agent representative can activate the SEG emergency over-ride button, colocated with all emergency stop buttons at ramp level at the head of the stand. This will instantly cut power to the parking aids and activate a sign mounted at pilot's eye level which will flash "STOP".

B. GUIDANCE SYSTEMS

1. AGNIS - AZIMUTH GUIDANCE FOR NOSE-IN STANDS


AGNIS units display red and/or green light signals through two parallel vertical slots. The system is aligned for interpretation from the left hand cockpit seat. Acft should be turned towards the green light to remain on centerline. AGNIS does not provide stopping guidance. Stopping guidance is provided by a sign (PAPA or STOP ARROW) positioned near the AGNIS unit.

RED GREEN




LEFT of centerline.
Turn towards GREEN.

GREEN GREEN



Aircraft on centerline.

GREEN RED



RIGHT of centerline.
Turn towards GREEN.

2. APIS - AIRCRAFT POSITIONING AND INFORMATION SYSTEM

The unit combines both alignment and stopping signals in one visual display mounted ahead of the pilot and is to be used from the left hand cockpit seat.

Display can be used to show stand number, acft type selected and final STOP wording when the acft has reached its final stopping position.

Indicates progress of the acft over the last 52'/16m of the approach to the stop position.



Azimuth guidance element

EGLL/LHR


JEPPesen

7 MAR 08

10-9H

LONDON, UK
HEATHROW**3. PAPA - PARALLAX AIRCRAFT PARKING AID**

This stopping aid is commonly positioned to the right side of the stand centerline. On some stands it will be located to the left side and indicated as such by the sign adjacent to the AGNIS unit. The aid consists of a black board, bearing acft type identification labels and "STOP" lines, with a horizontal slot running across the center. Behind the board is a vertically mounted fluorescent light tube. As an acft is taxiing onto the stand, the pilot will see the fluorescent tube appear to move across the slot towards the "STOP" lines. When the tube is in line with the appropriate acft type "STOP" line, the acft has reached the correct position.

**4. STOP ARROWS**

This provides stopping guidance only, used in conjunction with AGNIS in the form of one or two painted lines with the word "STOP" above the line and, where appropriate, the acft type below the line. The line is aligned with the pilot's eye position and is normally located to the left of the stand centerline, but may be provided on the right or both sides.

5. MIRROR

The mirror is normally mounted on the port side of the extended centerline. It is angled to give the pilot in the left hand seat view of the aircraft's nose landing gear (NLG). Associated mirror image paint markings will indicate the various stopping positions of the NLG. All mirrors are heated to prevent misting and icing.

EGLL/LHR

 **JEPPesen**
13 JUL 12 **10-9Y** Eff 26 Jul

JAA COPTER MINIMUMS

LONDON, UK
HEATHROW

STRAIGHT-IN RWY		DA(H) / MDA(H)	RVR (ALS/ALS out)
09L	CAT 2 ILS DME	179' (100')	RA 100' - 300m
	ILS DME	279' (200')	500m / 1000m
	LOC	470' (391')	800m / 1000m
	RNAV (LNAV/VNAV)	570' (491')	1000m / 1000m
	RNAV (LNAV)	630' (551')	1000m / 1000m
	SRA	720' (641')	1000m / 1000m
09R	CAT 2 ILS DME	175' (100')	RA 100' - 300m
	ILS DME	275' (200')	500m / 1000m
	LOC	480' (405')	800m / 1000m
	RNAV (LNAV/VNAV)	500' (425')	800m / 1000m
	RNAV (LNAV)	630' (555')	1000m / 1000m
	SRA	720' (645')	1000m / 1000m
27L	CAT 2 ILS DME	177' (100')	RA 102' - 300m
	ILS DME	277' (200')	500m / 1000m
	LOC	460' (383')	800m / 1000m
	RNAV (LNAV/VNAV)	510' (433')	800m / 1000m
	RNAV (LNAV)	560' (483')	1000m / 1000m
	SRA	720' (643')	1000m / 1000m
27R	CAT 2 ILS DME	178' (100')	RA 102' - 300m
	ILS DME	278' (200')	500m / 1000m
	LOC	430' (352')	800m / 1000m
	RNAV (LNAV/VNAV)	510' (432')	800m / 1000m
	RNAV (LNAV)	530' (452')	1000m / 1000m
	SRA	720' (642')	1000m / 1000m

CIRCLE-TO-LAND	MDA(H)	VIS
	750' (667')	1000m

TAKE-OFF RWY 09L/R, 27L/R


LVP must be in Force ❶				
RL, FATO LTS, CL & RVR info	RL, FATO LTS & RCLM	Unlit/unmarked defined RWY/FATO	Nil Facilities DAY	Nil Facilities NIGHT
150m	200m	200m	250m ❷	800m

- ❶ Without LVP 400m are stipulated.
❷ Or rejected take-off distance whichever is the greater.

EGLL/LHR
HEATHROW

JEPPesen
2 SEP 11 (11-1)

LONDON, UK
ILS DME Rwy 09L






EGLL/LHR
HEATHROW

JEPPESSEN
2 SEP 11 11-1A

LONDON, UK
CAT II/III ILS DME Rwy 09L

*D-ATIS	HEATHROW Director (APP)	HEATHROW Tower	*Ground
113.75 115.1 128.07	119.72	118.5 118.7 121.9	121.7 121.85
LOC IAA *110.3	Final Apch Crs 091°	GS D4.0 IAA 1400' (1321')	CAT II & III ILS Refer to Minimums
Apt Elev 83'			RWY 79'
MISSED APCH: Climb STRAIGHT AHEAD, when passing 1580' or D0.0 IAA, whichever is later, climbing turn LEFT on track 038° to 3000', then as directed. In event of radio failure see 11-5.			
Alt Set: hPa	Rwy Elev: 3 hPa	Trans level: By ATC	Trans alt: 6000'
Special Aircrew & Acft Certification Required.			




Gnd speed-Kts	70	90	100	120	140	160	HIALS-II	1580'	D0.0 IAA	038°
GS	3.00°	377	485	539	647	755	862	PAPI	↑ whichever later	↑ LT

Standard		STRAIGHT-IN LANDING RWY 09L	
CAT IIIA ILS		CAT II ILS	
DH 50'		ABCD	
RVR 200m		RA 100'	
		DA(H) 179' (100')	
		RVR 300m	

EGLL/LHR
HEATHROW

JEPPesen
2 SEP 11 (11-2)

LONDON, UK
ILS DME Rwy 09R



EGLL/LHR
HEATHROW


JEPPESSEN

LONDON, UK
CAT II/III ILS DME Rwy 09R

2 SEP 11

11-2A

CAT II/III ILS DME Rwy 09R





EGLL/LHR
HEATHROW


JEPPESSEN
2 SEP 11 (11-3)

LONDON, UK
● ILS DME Rwy 27L

*D-ATIS	HEATHROW Director (APP)	HEATHROW Tower	*Ground	
113.75 115.1 128.07	119.72	118.5 118.7 121.9	121.7 121.85	
LOC ILL *109.5	Final Apch Crs 271°	GS D4.0 ILL 1400' (1323')	ILS DA(H) 277' (200')	Apt Elev 83' RWY 77'
MISSED APCH: Climb STRAIGHT AHEAD, when passing 1080' or D0.0 ILL, whichever is later, climbing turn LEFT on track 149° to 2000'. When passing D6.0 LON climb without delay to 3000', then as directed. In event of radio failure see 11-6.				
Alt Set: hPa	Rwy Elev: 3 hPa	Trans level: By ATC	Trans alt: 6000'	



LOC (GS out)	ILL DME ALTITUDE	2.0	3.0	4.0	5.0	6.0	7.0
		770'	1090'	1410'	1730'	2040'	2360'



Gnd speed-Kts	70	90	100	120	140	160	HIALS-II	1080'	D0.0 ILL	149°
ILS GS or LOC Descent Angle	3.00°	377	485	539	647	755	862	PAPI	↑ whichever later	↑ LT
MAP at D0.5 ILL										

STRAIGHT-IN LANDING RWY 27L				CIRCLE-TO-LAND			
ILS		LOC (GS out) CDFA		DA/MDA(H)		DA/MDA(H)	
DA(H) 277' (200')		DA/MDA(H) 460' (383')		DA/MDA(H)		DA/MDA(H)	
FULL	Limited	ALS out	ALS out	Max Kts	MDA(H)	VIS	
A				100	750' (667')	1500m	
B	RVR 550m	RVR 750m	RVR 1200m	135	750' (667')	1600m	
C				180	850' (767')	2400m	
D				205	850' (767')	3600m	

EGLL/LHR
HEATHROW




JEPPESSEN
2 SEP 11 (11-3A) CAT II/III ILS DME Rwy 27L

LONDON, UK
DME Rwy 27L

*D-ATIS 113.75 115.1 128.07	HEATHROW Director (APP) 119.72	HEATHROW Tower 118.5 118.7	*Ground 121.9 121.7 121.85
LOC ILL *109.5	Final Apch Crs 271°	GS D4.0 ILL 1400' (1323')	CAT II & IIIA ILS Refer to Minimums
			Apt Elev 83' RWY 77'

MISSED APCH: Climb STRAIGHT AHEAD, when passing 1080' or D0.0 ILL, whichever is later, climbing turn LEFT on track 149° to 2000'. When passing D6.0 LON climb without delay to 3000', then as directed.
In event of radio failure see 11-6.

Alt Set: hPa Rwy Elev: 3 hPa Trans level: By ATC Trans alt: 6000'
Special Aircrew & Acft Certification Required.



Gnd speed-Kts	70	90	100	120	140	160	HIALS-II PAPI	1080' ↑ whichever later	D0.0 ILL ↑	149° LT
GS	3.00°	377	485	539	647	755				

Standard	CAT IIIA ILS DH 50'	STRAIGHT-IN LANDING RWY 27L	CAT II ILS ABCD RA 102' DA(H) 177' (100')
	RVR 200m		RVR 300m

Operators applying U.S. Specs: Autoland or HUD required below RVR 350m.



© JEPPESEN, 1998, 2011. ALL RIGHTS RESERVED.

EGLL/LHR
HEATHROW

JEPPESSEN
2 SEP 11 (11-4A) CAT II/III ILS DME Rwy 27R

LONDON, UK
DME Rwy 27R

*D-ATIS 113.75 115.1 128.07	HEATHROW Director (APP) 119.72	HEATHROW Tower 118.5 118.7 121.9 121.7 121.85	*Ground 121.7 121.85
LOC IRR *110.3	Final Apch Crs 271°	GS D4.0 IRR 1410' (1332')	CAT II & IIIA ILS Refer to Minimums Apt Elev 83' RWY 78'
MISSSED APCH: Climb STRAIGHT AHEAD when passing 1580' or D0.0 IRR, whichever is later, climbing turn RIGHT on track 318° to 3000', then as directed. In event of radio failure see 11-6.			
Alt Set: hPa Rwy Elev: 3 hPa Trans level: By ATC Trans alt: 6000' Special Aircrew & Acft Certification Required.			



RWY 27R 78'		D4.0 IRR D5.3 LON GS 1410'		D1.0 IRR GS 450'		D7.5 IRR D8.8 LON		2500'	
TCH 58'		1.0		3.0		3.5		271°	
Gnd speed-Kts		70	90	100	120	140	160	HIALS-II	
GS		3.00°	377	485	539	647	755	862	PAPI
Standard		STRAIGHT-IN LANDING RWY 27R						1580'	D0.0 IRR
CAT IIIA ILS								whichever later	
DH 50'		CAT II ILS ABCD						RT	318°
RVR 200m		RA 102'							
		DA(H) 178' (100')							
		RVR 300m							

Operators applying U.S. Specs: Autoland or HUD required below RVR 350m.

CHANGES: Minimums.

© JEPPESEN, 1998, 2011. ALL RIGHTS RESERVED.


EGLL/LHR
Apt Elev **83'**

JEPPesen
18 APR 14 **(11-6)**

LONDON, UK
HEATHROW

**PROCEDURES TO BE USED IN THE EVENT OF RADIO
FAILURE FOLLOWING A MISSED APPROACH**

RWY 27L/R



Holdings, initial and intermediate approach valid up to 220 KT.

VIA EPSOM NDB

MISSED APCH: In event of radio failure, on reaching 3000' proceed to EPM NDB at 3000', thence:

Rwy 27L: After holding leave EPM NDB on R-077 OCK maintaining 3000'. At D12.0 OCK turn LEFT onto track 360°. At R-065 OCK turn LEFT to intercept ILS localizer to be established at D10.0 ILL. After D10.0 ILL descend to 2500'. Continue approach as charted for rwy 27L.

Rwy 27R: After holding leave EPM NDB on R-077 OCK maintaining 3000'. At D12.0 OCK turn LEFT onto track 360°. At R-065 OCK turn LEFT to intercept ILS localizer to be established at D10.0 IRR. After D10.0 IRR descend to 2500'. Continue approach as charted for rwy 27R.

VIA CHILTERN NDB

MISSED APCH: In event of radio failure, on passing D10.0 LON turn RIGHT to CHT NDB at 3000', thence:

Rwy 27L: After holding leave CHT NDB on track 111° maintaining 3000'. At D19.0 BNN (MAX 180 KT) turn RIGHT to intercept ILS localizer to be established at D10.0 ILL. After D10.0 ILL descend to 2500'. Continue approach as charted for rwy 27L.

Rwy 27R: After holding leave CHT NDB on track 111° maintaining 3000'. At D19.0 BNN (MAX 180 KT) turn RIGHT to intercept ILS localizer to be established at D10.0 IRR. After D10.0 IRR descend to 2500'. Continue approach as charted for rwy 27R.

PANS OPS

CHANGES: Holding bearings.

© JEPPESEN, 1998, 2014. ALL RIGHTS RESERVED.


EGLL/LHR
HEATHROW

JEPPesen
7 AUG 15
Eff 20 Aug (12-1)


LONDON, UK
RNAV (GNSS) Z Rwy 09L

*D-ATIS	HEATHROW Director (APP)	HEATHROW Tower	*Ground
113.750 115.1 128.075	119.725	118.5 118.7 121.9	121.7 121.850
RNAV	Final ApcH Crs 091°	Minimum Alt L09LF 2500' (2421')	LNAV/VNAV DA(H) 570' (491')
		Apt Elev 83' Rwy 79'	2300' MSA ARP
MISSED APCH: Climb to 3000'. STRAIGHT AHEAD until passing 1580' or D0.0 IAA inbound, whichever is later, then turn LEFT onto 038° and as directed. In event of radio failure see 11-5.			

Alt Set: hPa Rwy Elev: 3 hPa Trans level: By ATC Trans alt: 6000'
1. Pilots should request RNAV Z approach on first contact with Director. 2. Acft will normally be radar vectored from holding/IAF. 3. ILS DME reads zero at rwy 09L thresh. 4. Minimum temperature -10°C.



DIST to RW09L	7.0	6.0	5.0	4.0	3.0	2.0
ALTITUDE	2360'	2040'	1730'	1410'	1090'	770'



Gnd speed-Kts	70	90	100	120	140	160	HIALS-II PAPI 3000'
Descent Angle	3.00°	372	478	531	637	743	
MAP at RW09L/D0.0 IAA							

STRAIGHT-IN LANDING RWY 09L				CIRCLE-TO-LAND	
LNAV/VNAV		LNAV CDFA		Max Kts	
DA(H) 570' (491')		DA/MDA(H) 630' (551')			
ALS out		ALS out			
A	RVR 1500m		RVR 1500m	100	750' (667') 1500m
B	RVR 1500m		RVR 1500m	135	750' (667') 1600m
C	RVR 1500m	CMV 2300m	RVR 1800m	180	850' (767') 2400m
D	RVR 1500m	CMV 2300m	RVR 1800m	205	850' (767') 3600m

PANS OPS

CHANGES: Procedure title.

© JEPPesen, 2012, 2015. ALL RIGHTS RESERVED.

EGLL/LHR
HEATHROW


JEPPesen
7 AUG 15
Eff 20 Aug (12-3)

LONDON, UK
RNAV (GNSS) Z Rwy 27L


BRIEFING STRIP™

*D-ATIS			HEATHROW Director (APP)		HEATHROW Tower		*Ground		
113.750	115.1	128.075	119.725		118.5	118.7	121.9	121.7	121.850
RNAV		Final ApcH Crs 271°	Minimum Alt L27LF 2500' (2423')		LNAV/VNAV DA(H) 510' (433')		Apt Elev 83' Rwy 77'		2300' MSA ARP
MISSED APCH: Climb to 2000'. STRAIGHT AHEAD until passing 1080' or D0.0 ILL inbound, whichever is later, then turn LEFT onto 149°. When passing D6.0 LON climb to 3000' without delay and as directed. In event of radio failure see 11-6.									

Alt Set: hPa Rwy Elev: 3 hPa Trans level: By ATC Trans alt: 6000'
1. Pilots should request RNAV Z approach on first contact with Director. 2. Acft will normally be radar vectored from holding/IAF. 3. Pilots should not expect descent clearance below 4000' until 13 NM from touchdown. 4. ILS DME reads zero at rwy 27L threshold. 5. Minimum temperature -10°C.



DIST to RW27L	2.0	3.0	4.0	5.0	6.0	7.0
ALTITUDE	770'	1090'	1410'	1720'	2040'	2360'



0							7.5		10.0	
Gnd speed-Kts	70	90	100	120	140	160	HIALS-II PAPI		2000'	
Descent Angle	3.00°	372	478	531	637	743				849
MAP at RW27L/D0.0 ILL										

STRAIGHT-IN LANDING RWY 27L				CIRCLE-TO-LAND	
LNAV/VNAV		LNAV CDFA			
DA(H) 510' (433')		DA/MDA(H) 560' (483')			
ALS out		ALS out		Max Kts.	VIS
RVR 1300m	RVR 1500m	RVR 1500m		100	750' (667') 1500m
	RVR 1500m	RVR 1500m		135	750' (667') 1600m
	RVR 2000m	RVR 1500m	CMV 2300m	180	850' (767') 2400m
	RVR 2000m	RVR 1500m	CMV 2300m	205	850' (767') 3600m

EGLL/LHR
HEATHROW

JEPPESSEN
7 AUG 15
Eff 20 Aug 12-4

LONDON, UK
RNAV (GNSS) Z Rwy 27R

BRIEFING STRIP

*D-ATIS			HEATHROW Director (APP)		HEATHROW Tower		*Ground		
113.750	115.1	128.075	119.725		118.5	118.7	121.9	121.7	121.850
RNAV		Final Apch Crs 271°	Minimum Alt L27RF 2500' (2422')		LNAV/VNAV DA(H) 510' (432')		Apt Elev 83' Rwy 78'		2300' MSA ARP
MISSED APCH: Climb to 3000'. STRAIGHT AHEAD until passing 1580' or D0.0 IRR inbound, whichever is later, then turn RIGHT onto 318° and as directed.									
In event of radio failure see 11-6.									
Alt Set: hPa		Rwy Elev: 3 hPa			Trans level: By ATC		Trans alt: 6000'		
1. Pilots should request RNAV Z approach on first contact with Director. 2. Acft will normally be radar vectored from holding/IAF. 3. Pilots should not expect descent clearance below 4000' until 13 NM from touchdown. 4. ILS DME reads zero at rwy 27R threshold. 5. Minimum temperature -10°C.									





Chart changes since cycle 12-2016

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
LONDON, (HEATHROW - EGLL)				
REV	AIRPORT BRIEFING (ARR CON...	10-1P4	17 Jun 2016	23 Jun 2016
REV	AIRPORT BRIEFING (ARR CON...	10-1P5	17 Jun 2016	23 Jun 2016
REV	AIRPORT	10-9	17 Jun 2016	23 Jun 2016
REV	AIRPORT INFO, TAKE-OFF MN...	10-9A	17 Jun 2016	23 Jun 2016
REV	TAXIING	10-9B	17 Jun 2016	23 Jun 2016
REV	PARKING STANDS	10-9C	17 Jun 2016	23 Jun 2016
REV	PARKING STANDS CONTD	10-9D	17 Jun 2016	23 Jun 2016
REV	PARKING STAND COORDS	10-9E	17 Jun 2016	23 Jun 2016

TERMINAL CHART CHANGE NOTICES

Chart Change Notices for Airport EGLL

Type: Terminal

Effectivity: Temporary

Begin Date: 20160428

End Date: 20160728

(11-2A) CAT II ILS DME Rwy 09R CAT A increased to 176' (101'), RA 101', CAT B increased to 181' (106'), RA 106', CAT C increased to 191' (116'), RA 117', CAT D increased to 205' (130'), RA 132', RVR 400m.

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: 20160726

(11-4A) CAT II ILS DME Rwy 27R DA(H) CAT D increased to 197'(119') RA is 120', RVR is unchanged.

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: 20160625

(11-3A) CAT II ILS DME Rwy 27L DA(H) CAT B increased to 179' (102'), RA is 104'. CAT C increased to 192' (115'), RA is 117'. CAT D increased to 213' (136'), RA is 138', RVR raised to 400m.

Type: Terminal

Effectivity: Temporary

Begin Date: Immediately

End Date: Until Further Notice

(all SIDs) Eff 8 Mar 12, when ATC removes MAX 250 KT speed restriction below FL100 by the phrase 'No ATC speed restriction', this must not be interpreted as removing the responsibility to adhere to any speed/power limitations due to noise abatement procedures. If a pilot can anticipate to be unable to comply with speed restriction, state minimum speed acceptable when requesting start-up.

Type: Terminal

Effectivity: Temporary
Begin Date: Immediately
End Date: 20160812

(12-4) RNAV (GNSS) Z RWY 27R due to on-going crane operations DA/MDA (H) for LNAV raised to 590' (512'). RVR for CAT A&B changed to 1500m, CAT C&D RVR 1600m. ALS out CAT C&D RVR changed to CMV 2400m.

Chart Change Notices for Country GBR

Type: Gen Tmnl
Effectivity: Permanent
Begin Date: Immediately
End Date: No end date

The following Take-off minima according to Commission Regulation No. 965/2012 (EASA Air Operations Regulation) are applicable for Low Visibility Take-off Operations within the UK FIR for CAT ABCD aircraft: 1. With RL and RCLM during day or with RL or CL during night: RVR 300m 2. With RL and CL: RVR 200m 3. With RL and CL and TDZ, MID and RO RVR: RVR 150m 4. With HIRL and CL and TDZ, MID and RO RVR: RVR 125m 5. On CAT III RWYs with approved guidance system or HUD/HUDLS: RVR 75m