

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UMOO

Terminal Charts For UMOO

Revision Letter For Cycle 09-2019

Change Notices

Notebook

General Information

Location: MAHILIOU BLR
ICAO/IATA: UMOO / MVQ
Lat/Long: N53° 57.3', E030° 05.6'
Elevation: 637 ft

Airport Use: Public
Daylight Savings: Not Observed
UTC Conversion: -3:00 = UTC
Magnetic Variation: 8.0° E

Fuel Types: 100 Octane (LL), Jet A
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0207 Z
Sunset: 1746 Z

Runway Information

Runway: 13
Length x Width: 8419 ft x 138 ft
Surface Type: asphalt
TDZ-Elev: 625 ft
Lighting: Edge, ALS

Runway: 31
Length x Width: 8419 ft x 138 ft
Surface Type: asphalt
TDZ-Elev: 617 ft
Lighting: Edge, ALS


Communication Information

ATIS: 126.200 Non-English
ATIS: 118.075
Mahiliou Tower: 127.100
Mahiliou Tower: 133.000 Secondary

UM00/MVQ
MAHILIOU

JEPPESEN
12 APR 19 10-2 Eff 25 Apr

MAHILIOU, BELARUS
STAR




UM00/MVQ
MAHILIOU

JEPPESEN
12 APR 19 10-2A Eff 25 Apr

MAHILIOU, BELARUS

STAR



UM00/MVQ
MAHILIOU

 **JEPPESSEN**
12 APR 19 **10-2B** Eff 25 Apr


MAHILIOU, BELARUS

STAR



*ATIS
118.075
(126.2 Russian)

Apt Elev
637'

Alt Set: hPa
Trans level: FL80
FL90 if pressure is less than 977.2 hPa
Trans alt: 6000'
VOR DME required.



**DINPU 1M [DINP1M]
SUMOK 1D [SUMO1D]
ARRIVALS
(RWY 31)**




STAR	ROUTING
DINPU 1M	Intercept MGL R-004 inbound to MGL VOR.
SUMOK 1D	Intercept MGL R-317 inbound to MGL VOR.

UM00/MVQ
MAHILIOU

JEPPESEN
12 APR 19 10-2C Eff 25 Apr


MAHILIOU, BELARUS
STAR



UM00/MVQ
MAHILIOU

JEPPESEN
12 APR 19 10-3 Eff 25 Apr

MAHILIOU, BELARUS
SID




SID	ROUTING
LUBIN 1A	Climb straight ahead to at or above 1300', turn RIGHT to MGL VOR, intercept MGL R-031 to LUBIN.
NEZGI 1A	Climb straight ahead to at or above 1300', turn RIGHT, 232° track, intercept MGL R-202 to NEZGI.
RAFMA 1A	Climb straight ahead to at or above 1300', turn RIGHT, 295° track, intercept MGL R-265 to RAFMA.
SLEDA 1A	Climb straight ahead to at or above 1300', turn RIGHT, intercept MGL R-145 to SLEDA.

UM00/MVQ
MAHILIOU

JEPPESEN
12 APR 19 10-3A Eff 25 Apr

MAHILIOU, BELARUS
SID



UM00/MVQ
MAHILIOU

 **JEPPESEN**
26 JUL 13 **10-4**

MAHILIOU, BELARUS
NOISE

NOISE ABATEMENT

ARRIVALS

Noise abatement procedures during approach phase shall be carried out by crews of all ACFT according to the Aeroplane Flight Manual unless there are unfavourable meteorological conditions, such as considerable wind speed, cumulo-nimbus clouds etc., in arrival and approach sectors. During instrument as well as visual approach, flying below the ILS glide path angle is not allowed.

No noise abatement procedures shall prescribe the exceeding of indicated air speed of descent.

DEPARTURES


Noise abatement procedures during take-off and climbing phase shall be carried out by crews of all ACFT according to the Aeroplane Flight Manual, but not at the expense of flight safety in case of engines failure during take-off phase or in case of forecasted or expected wind shear or downward gusts.

UM00/MVQ

Apt Elev **637'**
N53 57.3 E030 05.7

JEPPESSEN

12 APR 19 **(10-9)** Eff 25 Apr

MAHILIOU, BELARUS
MAHILIOU


ADDITIONAL RUNWAY INFORMATION

ADDITIONAL RUNWAY INFORMATION					USABLE LENGTHS		TAKE-OFF	WIDTH
RWY					— LANDING BEYOND			
					Threshold	Glide Slope		
13	RL (58m)	ALS	PAPI-L (angle 2.83°)	RVR		7447' 2270m	1	138'
31	RL (58m)	ALS	PAPI-L (angle 2.67°)	RVR				42m

1 TAKE-OFF RUN AVAILABLE

RWY 13:

From rwy head 8419' (2566m)
twy A int 4465' (1361m)

RWY 31:

From rwy head 8419' (2566m)
twy A int 3953' (1205m)

TAKE-OFF

AIR CARRIER (JAA)

All Rwys

LVP must be in force

RCLM (DAY only)
or RL

RCLM (DAY only)
or RL

A
B
C
D

400m

UM00/MVQ

 **JEPPesen**

1 SEP 17

10-9S

Eff 14 Sep

MAHILIOU, BELARUS
MAHILIOU
Standard

STRAIGHT-IN RWY		A	B	C	D
13	ILS	825' (200') R1000m	825' (200') R1000m	833' (208') R1000m	843' (218') R1000m
	ALS out	R1200m	R1200m	R1200m	R1200m
	LOC	NOT AUTH	NOT AUTH	NOT AUTH	NOT AUTH
	① VOR with DME ALS out	960' (335') R1300m R1500m	960' (335') R1300m R1500m	960' (335') R1300m R1500m	960' (335') R1300m R1500m
	VOR w/o DME ALS out	1010' (385') R1800m R2000m	1010' (385') R1800m R2000m	1050' (425') R2200m R2400m	1070' (445') R2300m R2500m
	① NDB ALS out	930' (305') R1200m R1400m	930' (305') R1200m R1400m	930' (305') R1200m R1400m	940' (315') R1200m R1400m
31	① VOR with DME ALS out	900' (283') R1200m R1400m	900' (283') R1200m R1400m	900' (283') R1200m R1400m	930' (313') R1200m R1400m
	VOR w/o DME ALS out	1230' (613') R2800m R3000m	1230' (613') R2800m R3000m	1230' (613') R3000m R3200m	1230' (613') R3000m R3200m
	① NDB	920' (303') R1200m	920' (303') R1200m	920' (303') R1200m	930' (313') R1200m
	ALS out	R1400m	R1400m	R1400m	R1400m

① Continuous Descent Final Approach.

CIRCLE-TO-LAND ②	100 KT	135 KT	180 KT	205 KT
	1100' (463') ③	1140' (503') ③	1300' (663')	1340' (703')
CEILING REQUIRED	ceil 190m V1900m	ceil 200m V2800m	ceil 300m V3700m	ceil 310m V4600m

② Not authorized in sector between R-040 MGL and R-110 MGL clockwise.

③ or higher minimums of preceding straight-in approach.

TAKE-OFF		
Low Visibility Take-off		
Day: RL & RCLM Night: RL	Day: RL or RCLM Night: RL	Adequate vis ref (Day only)
A	400m	500m
B		
C		
D		



UM00/MVQ
MAHILIOU

JEPPESSEN
12 APR 19 **(11-1)** Eff 25 Apr

MAHILIOU, BELARUS
ILS Rwy 13

BRIEFING STRIP™

*ATIS				*MAHILIOU Tower (APP/TWR)			
118.075		(Russian 126.2)		127.1		133.0	
LOC IUF *111.1	Final Apch Crs 129°	GS LOM 1268' (643')	ILS DA(H) Refer to Minimums	Apt Elev 637'			
MISSED APCH: Climb on 129° to 1300' or above, then turn RIGHT to ASLIG climbing to 3000', then as directed.							
Alt Set: hPa		Rwy Elev: 23 hPa		Trans level: FL 80 ①		Trans alt: 6000'	
VOR DME required.				MSA MGL VOR			



Gnd speed-Kts	70	90	100	120	140	160	ALS	1300' or above on 129°	3000' RT	ASLIG
GS	2.80°	347	446	495	594	693	PAPI			


STRAIGHT-IN LANDING RWY 13				CEILING REQUIRED	
ILS		LOC (GS out)		Not authorized in sector between R-040 MGL and R-110 MGL clockwise	
DA(H) C: 833' (208')				Max Kts.	MDA(H) _____ CEIL-VIS _____
AB: 825' (200') D: 843' (218')					
FULL		ALS out		100	1100' (463') 190m - 1900m
A	1200m		NOT AUTHORIZED	135	1130' (493') 200m - 2800m
B				180	1300' (663') 300m - 3700m
C				205	1330' (693') 310m - 4600m
D					

UM00/MVQ
MAHILIOU
JEPPESSEN
12 APR 19 **(16-1)** Eff 25 Apr


MAHILIOU, BELARUS
NDB Rwy 13

BRIEFING STRIP™

*ATIS			*MAHILIOU Tower (APP/TWR)		
118.075 (Russian 126.2)			127.1 133.0		
NDB U *985	Final Apt Chrs 129°	Minimum Alt D6.3 MGL 2300' (1675')	MDA(H) Refer to Minimums	Apt Elev 637' Rwy 625'	
MISSED APCH: Climb on 129° to 1300' or above, then turn RIGHT to ASLIG climbing to 3000', then as directed.					
Alt Set: hPa Rwy Elev: 23 hPa Trans level: FL 80 ① Trans alt: 6000'					
DME required.					
					MSA MGL VOR



MGL DME	6.0	5.0	4.0	3.0	2.0
ALTITUDE	2220'	1920'	1620'	1320'	1020'



							2.0	0.7	0			
Gnd speed-Kts	70	90	100	120	140	160		ALS PAPI	1300' or above	on	129°	
Descent Angle	2.80°	347	446	495	594	693						792
MAP at LMM												

STRAIGHT-IN LANDING RWY 13			CEILING REQUIRED	
MDA(H) ABC: 930' (305') D: 940' (315')			Not authorized in sector between 228° to U NDB and 288° to U NDB clockwise	
ALS out			Max Kts	MDA(H) CEIL-VIS
A	RVR 1500m VIS 1600m		100	1100' (463') 190m - 1900m
B			135	1130' (493') 200m - 2800m
C			180	1300' (663') 300m - 3700m
D			205	1330' (693') 310m - 4600m

Chart changes since cycle 08-2019

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
MAHILIOU, (MAHILIOU - UMOO)				

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UMOO