

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UTAT

Terminal Charts For UTAT

Revision Letter For Cycle 09-2019

Change Notices

Notebook

General Information

Location: DASHOGUZ TKM
ICAO/IATA: UTAT / TAZ
Lat/Long: N41° 45.6', E059° 50.1'
Elevation: 282 ft

Airport Use: Public
Daylight Savings: Not Observed
UTC Conversion: -5:00 = UTC
Magnetic Variation: 6.0° E

Fuel Types: Jet A-1
Repair Types: Minor Airframe, Minor Engine
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0047 Z
Sunset: 1507 Z

Runway Information

Runway: 08
Length x Width: 12467 ft x 197 ft
Surface Type: concrete
TDZ-Elev: 278 ft
Lighting: Edge, ALS, Centerline, TDZ

Runway: 26
Length x Width: 12467 ft x 197 ft
Surface Type: concrete
TDZ-Elev: 278 ft
Lighting: Edge, ALS, Centerline, TDZ

Communication Information

Dashoguz Tower: 122.700
Dashoguz Approach: 124.700
Dashoguz Approach: 129.000 Secondary
Dashoguz Transit Operations: 131.700 Non-English
AWIS: 127.400

UTAT/TAZ
DASHOGUZ



JEPPESEN DASHOGUZ, TURKMENISTAN

5 OCT 18

10-2


Eff 11 Oct

STAR

Apt Elev
282

Alt Set: hPa Trans level: FL120

ADOBI 08A
SOVOD 08A
TASHA 08A
RWY 08 ARRIVALS



UTAT/TAZ
DASHOGUZ



JEPPESEN DASHOGUZ, TURKMENISTAN

5 OCT 18

(10-2A)

Eff 11 Oct

STAR

Apt Elev
282

Alt Set: hPa Trans level: FL120


ADOBI 08B

SOVOD 08B

TASHA 08B

RWY 08 ARRIVALS

WITHOUT RADAR CONTROL AND RADIO COMMUNICATION FAILURE



CHANGES: STARs completely revised; new format.


© JEPPESEN, 2018. ALL RIGHTS RESERVED.

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN

5 OCT 18 10-2B Eff 11 Oct

STAR



CHANGES: STARs completely revised; new format.

© JEPPESEN, 2018. ALL RIGHTS RESERVED.

UTAT/TAZ
DASHOGUZ


JEPPESSEN DASHOGUZ, TURKMENISTAN

5 OCT 18 **10-2D** Eff 11 Oct

STAR

Apt Elev
282
Alt Set: hPa Trans level: FL120

**TAKIP 08A
TOSDO 08A
RWY 08 ARRIVALS**



UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN

5 OCT 18 **10-2E** Eff 11 Oct


STAR

Apt Elev
282

Alt Set: hPa Trans level: FL120


TAKIP 08B
TOSDO 08B
RWY 08 ARRIVALS

WITHOUT RADAR CONTROL AND RADIO COMMUNICATION FAILURE



UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
5 OCT 18 **10-2F** Eff 11 Oct **STAR**






Eff 11 Oct

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
5 OCT 18 10-2L Eff 11 Oct STAR



UTAT/TAZ
DASHOGUZ



JEPPESEN DASHOGUZ, TURKMENISTAN

5 OCT 18

10-3


Eff 11 Oct

SID

Apt Elev
282

Trans alt: 12000

ADOBI 08D
TASHA 08D
RWY 08 DEPARTURES



UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN


5 OCT 18 **(10-3A)** Eff 11 Oct

SID

Apt Elev
282

Trans alt: 12000

ADOBI 26D
TASHA 26D
RWY 26 DEPARTURES



CHANGES: SIDs completely revised; new format.


© JEPPESEN, 2018. ALL RIGHTS RESERVED.

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN

5 OCT 18 (10-3B) Eff 11 Oct

SID



UTAT/TAZ
DASHOGUZ




JEPPESSEN DASHOGUZ, TURKMENISTAN

5 OCT 18

10-3C

Eff 11 Oct

SID



UTAT/TAZ
DASHOGUZ




JEPPESEN DASHOGUZ, TURKMENISTAN

5 OCT 18

10-3D

Eff 11 Oct

SID



UTAT/TAZ

Apt Elev **282'**

N41 45.6 E059 50.1

JEPPESSEN


28 SEP 18

(10-9)

Eff 11 Oct

DASHOGUZ, TURKMENISTAN

DASHOGUZ



ADDITIONAL RUNWAY INFORMATION					
RWY			USABLE LENGTHS		WIDTH
			LANDING BEYOND Threshold	Glide Slope	
08	26	HIRL (60m) CL (15m) HIALS-II TDZ PAPI-L (3.0°) RVR		11,434' 3485m 11,374' 3467m	197' 60m

1 TAKE-OFF RUN AVAILABLE			
RWY 08:	From rwy head	12,467' (3800m)	
	twy A3 int	5774' (1760m)	
RWY 26:	From rwy head	12,467' (3800m)	
	twy A3 int	6693' (2040m)	

TAKE-OFF		
AIR CARRIER (JAA)		
LVP must be in force		
	1 RL & CL	RCLM (DAY only) or RL
A		
B	200m	300m
C		400m
D	250m	

1 Available when friction coefficient is not less than 0.5 and cross wind component does not exceed half of maximum allowed value for take-off for this ACFT type.

UTAT/TAZ



JEPPESSEN


DASHOGUZ, TURKMENISTAN

28 SEP 18

10-9A

Eff 11 Oct

DASHOGUZ



INS COORDINATES	
STAND No.	COORDINATES
1, 2	N41 45.1 E059 49.2
3 thru 6	N41 45.1 E059 50.0
ISOLATED STAND	N41 45.1 E059 49.0

- Engines start-up, towing and taxiing without permission of TWR controller are prohibited.
- Stands 1 thru 10 are available for helicopters.

LOW VISIBILITY PROCEDURES (LVP)

LVP are initiated by the phrase: "Low visibility procedures in progress." LVP are applied when RVR is 900m or less, and/or ceiling is 230'/70m or less.

After landing on RWY 08/26 in low visibility condition the flight crew must report the execution of landing and RWY vacaton to TWR controller.

When regular meteorological report is issued where RVR is more than 900m and ceiling is more than 230'/70m, the Flight Controll Officer takes the decision to cancel LVP.

UTAT/TAZ


Standard
DASHOGUZ, TURKMENISTAN
DASHOGUZ

STRAIGHT-IN RWY	A	B	C	D
08				
ILS	478' (200')	478' (200')	478' (200')	478' (200')
FULL	R550m	R550m	R550m	R550m
TDZ or CL out	① R550m	① R550m	① R550m	① R550m
ALS out	R1200m	R1200m	R1200m	R1200m
LOC	NOT AUTH	NOT AUTH	NOT AUTH	NOT AUTH
② VOR	550' (272')	610' (332')	610' (332')	610' (332')
	R1000m	R1500m	R1500m	R1500m
ALS out	R1300m	R1500m	R1500m	R1500m
② 2 NDB	580' (302')	610' (332')	610' (332')	610' (332')
	R1000m	R1500m	R1500m	R1500m
ALS out	R1400m	R1500m	R1500m	R1500m
② NDB	940' (662')	940' (662')	1270' (992')	1270' (992')
	R3000m	R3000m	R5000m	R5000m
26				
ILS	478' (200')	478' (200')	478' (200')	478' (200')
FULL	R550m	R550m	R550m	R550m
TDZ or CL out	① R550m	① R550m	① R550m	① R550m
ALS out	R1200m	R1200m	R1200m	R1200m
LOC	NOT AUTH	NOT AUTH	NOT AUTH	NOT AUTH
② VOR	550' (272')	610' (332')	610' (332')	610' (332')
	R1000m	R1500m	R1500m	R1500m
ALS out	R1300m	R1500m	R1500m	R1500m
② NDB	940' (662')	1270' (992')	1270' (992')	1270' (992')
	R3000m	R5000m	R5000m	R5000m

① W/o HUD/AP/FD: RVR 750m.

② Continuous Descent Final Approach.


TAKE-OFF

	Low Visibility Take-off				
	1 RL & CL	Day: RL & RCLM	Night: RL & RCLM	Day: RL or RCLM Night: RL or CL	Adequate vis ref (Day only)
A	R200m	R300m	R300m	400m	500m
B					
C					
D					

① Available when friction coefficient is not less than 0.5 and cross wind component does not exceed half of maximum allowed value for take-off for this ACFT type.

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
28 SEP 18 **(11-1)** **Eff 11 Oct** **ILS Rwy 08**






CHANGES: New procedure.


© JEPPESSEN, 2018. ALL RIGHTS RESERVED.

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
28 SEP 18 11-2 Eff 11 Oct ILS Rwy 26

DASHOGUZ Approach				DASHOGUZ Tower		
124.7				122.7		
LOC ISH 111.3	Final Apch Crs 264°	GS D8.0 DSH 2000' (1722')	ILS DA(H) 478' (200')	Apt Elev 282'	 MSA DSH VOR	
MISSED APCH: Climb on 264° to 1000', then turn LEFT to BABMA climbing to 2500', then according to chart, or as directed.				Rwy 278'		
MISSED APCH WITH COMM FAILURE: Set SSR transponder to code 7600. Climb to holding area over BABMA to 2500' and hold for 3min, then proceed according to chart.						
Alt Set: hPa		Rwy Elev: 10 hPa		Trans level: FL 120		
Trans alt: 12000'						






Grnd speed-Kts	70	90	100	120	140	160		BABMA LT
Descent Angle 3.00°	372	478	531	637	743	849		

STRAIGHT-IN LANDING RWY 08				LOC (GS out)	
ILS					
DA(H) 478' (200')					
FULL		TDZ or CL out	ALS out		
A					
B	RVR 550m	RVR 720m	1200m		
C	VIS 800m	VIS 800m			
D					
				NOT AUTHORIZED	

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
28 SEP 18 13-1 Eff 11 Oct
VOR Rwy 08

DASHOGUZ Approach				DASHOGUZ Tower		
124.7				122.7		
VOR DSH 112.0	Final Apch Crs 084°	Minimum Alt D4.5 2000' (1722')	MDA(H) Refer to Minimums	Apt Elev 282'		
				Rwy 278'		
MISSED APCH: Climb on 084° to 1000', then turn RIGHT to SURET climbing to 2500', then according to chart or as directed. MISSED APCH WITH COMM FAILURE: ① Set SSR transponder to code 7600. Climb to SURET to 2500', then proceed to ORVIG, then to holding area over BABMA and hold for 3min, then proceed according to chart.						
Alt Set: hPa		Rwy Elev: 10 hPa		Trans level: FL 120		
Trans alt: 12000'						
DME required.						




Gnd speed-Kts	70	90	100	120	140	160		1000' on 084°	SURET RT
Descent Angle 3.00°	372	478	531	637	743	849			
MAP at D0.7									



STRAIGHT-IN LANDING RWY 08							
MDA(H) A: 550' (272')		BCD: 610' (332')					
		ALS out					
A	1000m	RVR 1500m VIS 1600m					
B							
C							
D							

UTAT/TAZ DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
28 SEP 18 **(13-2)** Eff 11 Oct
VOR Rwy 26

BRIEFING STRIP™

DASHOGUZ Approach				DASHOGUZ Tower	
124.7				122.7	
VOR DSH 112.0	Final Apch Crs 264°	Minimum Alt D8.0 2000' (1722')	MDA(H) Refer to Minimums	Apt Elev 282' Rwy 278'	 MSA DSH VOR
MISSED APCH: Climb on 264° to 1000', then turn LEFT to BABMA climbing to 2500', then according to chart, or as directed.					
MISSED APCH WITH COMM FAILURE: Set SSR transponder to code 7600. Climb to holding area over BABMA to 2500' and hold for 3min, then proceed according to chart.					
Alt Set: hPa Rwy Elev: 10 hPa Trans level: FL 120 Trans alt: 12000'					
DME required.					



									HIALS-II		1000' on 264°		BABMA	
Gnd speed-Kts	70	90	100	120	140	160			PAPI		↑		LT	
Descent Angle 3.00°	372	478	531	637	743	849								
MAP at D2.8														


STRAIGHT-IN LANDING RWY 26											
MDA(H) A: 550' (272')			BCD: 610' (332')								
			ALS out								
A	1000m										
B											
C	RVR 1500m VIS 1600m										
D											



CHANGES: New procedure.

© JEPPESSEN, 2018. ALL RIGHTS RESERVED.

UTAT/TAZ
DASHOGUZ

JEPPESSEN DASHOGUZ, TURKMENISTAN
28 SEP 18 **16-1** Eff 11 Oct 2 NDB or NDB Rwy 08

DASHOGUZ Approach				DASHOGUZ Tower		
124.7				122.7		
NDB RP 322	Final Apch Crs 084°	Minimum Alt D4.5 2000' (1722')	MDA(H) Refer to Minimums	Apt Elev 282'		
NDB R 662				Rwy 278'		
MISSED APCH: Climb on 084° to 1000', then turn RIGHT to SURET climbing to 2500', then according to chart or as directed.						
MISSED APCH WITH COMM FAILURE: ①Set SSR transponder to code 7600. Climb to SURET to 2500', then to ORVIG then to holding area over BABMA and hold for 3min, then proceed according to chart.						
Alt Set: hPa		Rwy Elev: 10 hPa		Trans level: FL 120		Trans alt: 12000'
DME required.						



Gnd speed-Kts	70	90	100	120	140	160		1000' on 084°	SURET RT
Descent Angle	3.00°	372	478	531	637	743			
MAP at LMM									

STRAIGHT-IN LANDING RWY 08							
2 NDB		NDB					
MDA(H) A: 580' (302')		MDA(H) AB: 940' (662')					
BCD: 610' (332')		CD: 1270' (992')					
ALS out		ALS out					
A	1200m	RVR 1500m VIS 1600m	3000m				
B							
C	RVR 1500m VIS 1600m	RVR 1500m VIS 1600m	5000m				
D							

DASHOGUZ, (DASHOGUZ - UTAT)

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UTAT