

List of pages in this Trip Kit

Trip Kit Index

Airport Information For UKDD

Terminal Charts For UKDD

Revision Letter For Cycle 09-2019

Change Notices

Notebook

General Information

Location: DNIPRO UKR
ICAO/IATA: UKDD / DNK
Lat/Long: N48° 21.4', E035° 06.0'
Elevation: 482 ft

Airport Use: Public
Daylight Savings: Observed
UTC Conversion: -2:00 = UTC
Magnetic Variation: 8.0° E

Fuel Types: Jet A-1
Repair Types: Minor Airframe, Minor Engine, Major Airframe, Major Engine
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: No

Sunrise: 0207 Z
Sunset: 1705 Z

Runway Information

Runway: 08
Length x Width: 9377 ft x 144 ft
Surface Type: concrete
TDZ-Elev: 478 ft
Lighting: Edge, ALS

Runway: 26
Length x Width: 9377 ft x 144 ft
Surface Type: concrete
TDZ-Elev: 473 ft
Lighting: Edge, ALS

Communication Information

ATIS: 130.900
ATIS: 134.900 Non-English
Dnipro Tower: 118.600
Dnipro Ground: 121.800
Dnipro Approach: 132.300
Dnipro Information: 122.700 Flight Info Service RCO
Dnipro Radar ACC: 119.400 RCO

UKDD/DNK**JEPPESEN****DNIPRO, UKRAINE**

DNIPROPETROVSK INTL

2 NOV 18

10-1P

Eff 8 Nov

AIRPORT BRIEFING**1. GENERAL****1.1. ATIS**

ATIS 130.9

134.9 (Russian)

1.2. NOISE ABATEMENT PROCEDURES**1.2.1. GENERAL**

SID, STAR and Approach charts are based on minimizing the impact of aviation noise on settlements located around the aerodrome.

Minimum levels provided by an ATC when ACFT are under radar vectoring or direct routing include corrections for low temperatures within the range from -28°C to -25°C inclusively.

1.2.2. NIGHT NOISE RESTRICTIONS FROM 2300-0600LT**1.2.2.1. TAXIING**

Taxiing of three-engined ACFT to be done with two side engines. Power while taxiing from stands 3, 5, 8 and 9 shall not be more than 0.6 of rated power.

1.2.2.2. RUN-UP TEST

Run-ups with take-off power are prohibited.

1.2.2.3. AUXILIARY POWER UNIT (APU)

Use limited to ± 30 minutes before departure/after landing.

1.3. LOW VISIBILITY PROCEDURES (LVP)

LVP shall be applied for take-off only and when RVR is less than 600m.

Pilots will be informed about the beginning of the procedure via ATIS or by ATC.

Take-off when RVR less than 300m is not executed.

Taxiing in the maneuvering zone is permitted only for one ACFT at a time.

1.4. TAXI PROCEDURES

For ground movement restrictions refer to 10-9 charts.

Taxiing to/from stands with Follow-me car only.

Taxiing on own thrust via TWY 7 is permitted only for ACFT of less than code 4C at daytime, in other cases taxiing via TWY 7 is carried out only by towing.

1.5. COMMUNICATION FAILURE

In case of communication failure light signals are emitted by Signal Light Gun.

1.6. OTHER INFORMATION

Birds in vicinity of APT.

UKDD/DNK

JEPPESEN

DNIPRO, UKRAINE

DNIPROPETROVSK INTL

2 NOV 18

10-1P1

Eff 8 Nov

AIRPORT BRIEFING

2. ARRIVAL

2.1. CONTINUOUS DESCENT OPERATIONS

CDO are authorized only if there is no system degradation that may affect a GNSS or ILS operation.

ATC will issue further descent instruction prior to the CDO flight reaching 900m (3000') from the last assigned level so as to prevent leveling off.

Pilots shall maintain MAX IAS 220 KT at a distance of 20 track miles from touchdown.

Specified minimum levels must be adhered to unless specifically cancelled by ATC.

3. DEPARTURE

3.1. DE-ICING

Available at D1, D3 and stand 16.


3.2. START-UP

Start-up of engine during towing is prohibited.

UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 10-2 Eff 8 Nov


DNIPRO, UKRAINE
RNAV STAR



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 (10-2A) Eff 8 Nov



DNIPRO, UKRAINE
RNAV STAR



STAR	ROUTING
ORSUS 4Z	ORSUS (9030'+) - DDW01 (7060'+) - DD403 (2960'+; K220-) - DD402 (2470'+) - DD401 (2470').
ROKOX 2Z	ROKOX (8040'+) - DDW02 (6070'+) - DD403 (2960'+; K220-) - DD402 (2470'+) - DD401 (2470').

Alt Set: hPa
Trans level: By ATC Trans alt: 10010'

1. **RNAV 1 (GNSS).**
2. **RNAV-1 (P-RNAV) approval required otherwise advise ATC.**
3. EXPECT ILS or NDB approach on DD201.
4. For CDO instructions refer to 10-1P pages.



NOT TO SCALE

KOSIR
At or above 8040'

BULIG
At or above 8040'

RUBES
At or above 8040'

DD201
(D7.3 DNP)
At 2470'

DD202
At or above 2470'

DD205
At or above 2960'
MAX 220 KT

DD209
(Fly-over for holding only)
MHA 3940

DD210
(Fly-over for holding only)
MHA 6070

DNIPRO
D 112.5 DNP
N48 21.6 E035 06.2

FT/METER CONVERSION


FT	METER
10010'	3050m
8040'	2450m
6070'	1850m
3940'	1200m
2960'	900m
2470'	750m

FT./METER CONVERSION	
	QNH
10010'	- 3050m
8040'	- 2450m
6070'	- 1850m
3940'	- 1200m
2960'	- 900m
2470'	- 750m
2140'	- 650m

DNIPRO, UKRAINE

RNAV STAR

OSLAN 4X [OSLA4X]
TIRPU 4X [TIRP4X]
UMSOT 3X [UMSO3X]
RWY 08 RNAV ARRIVALS



FT/METER CONVERSION

QNH	
10010'	- 3050m
7060'	- 2150m
6070'	- 1850m
3940'	- 1200m
2960'	- 900m
2470'	- 750m
2140'	- 650m




STAR	ROUTING
OSLAN 4X	OSLAN (FL150+) - DD2Ø6 (7060'+) - DD2Ø3 (2960'+; K220-) - DD2Ø2 (2470'+) - DD2Ø1 (2470').
TIRPU 4X	TIRPU (FL110+) - DD2Ø3 (2960'+; K220-) - DD2Ø2 (2470'+) - DD2Ø1 (2470').
UMSOT 3X	UMSOT (7060'+) - DD212 - DD2Ø5 (2960'+; K220-) - DD2Ø2 (2470'+) - DD2Ø1 (2470').

UKDD/DNK
DNIPROPETROVSK INTL

JEPPESEN
2 NOV 18 10-2E Eff 8 Nov

DNIPRO, UKRAINE
RNAV STAR




DNIPRO, UKRAINE

UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 10-2G Eff 8 Nov

DNIPRO, UKRAINE
STAR



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN


DNIPRO, UKRAINE

2 NOV 18

10-2H

Eff 8 Nov

STAR



QNH


10010'	-	3050m
9030'	-	2750m
7060'	-	2150m
6070'	-	1850m
3940'	-	1200m
2140'	-	650m

FT/METER CONVERSION	QNH
10010'	- 3050m
9030'	- 2750m
7060'	- 2150m
6070'	- 1850m
3940'	- 1200m
2140'	- 650m

UKDD/DNK
DNIPROPETROVSK INTL

JEPPesen
2 NOV 18 10-3 Eff 8 Nov


DNIPRO, UKRAINE
RNAV SID



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESEN
2 NOV 18 (10-3A) Eff 8 Nov

DNIPRO, UKRAINE
RNAV SID



UKDD/DNK

DNIPROPETROVSK INTL

JEPPESSEN

2 NOV 18

10-3B

Eff 8 Nov


DNIPRO, UKRAINE

RNAV SID

Apt Elev
482'

Trans level: By ATC Trans alt: 10010'

1. RNAV 1 (GNSS).
2. RNAV 1 (P-RNAV) approval required otherwise advise ATC.
3. If unable to comply SID procedures advise ATC.




BULIG 3U [BULI3U]
KOSIR 3U [KOSI3U]
RUBES 4U [RUBE4U]
RWY 08 RNAV DEPARTURES

These SIDs require a minimum climb gradient of 4.5% up to 2470'.

Gnd speed-KT	75	100	150	200	250	300
4.5% V/V (fpm)	342	456	684	911	1139	1367

If unable to comply advise ATC.



FT/METER CONVERSION

QNH

2470' - 750m
7060' - 2150m
9030' - 2750m
10010' - 3050m

UKDD/DNK

DNIPROPETROVSK INTL


2 NOV 18

10-3C

Eff 8 Nov

DNIPRO, UKRAINE

RNAV SID



2200


MSA
DNP VOR

© JEPPESEN, 2012, 2018. ALL RIGHTS RESERVED.

UKDD/DNK
DNIPROPETROVSK INTL

JEPPESEN
2 NOV 18 10-3E Eff 8 Nov


DNIPRO, UKRAINE
RNAV SID



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 10-3F Eff 8 Nov

DNIPRO, UKRAINE
SID



UKDD/DNK

DNIPROPETROVSK INTL



JEPPESSEN


2 NOV 18

(10-3G)

Eff 8 Nov

DNIPRO, UKRAINE


SID



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 **(10-3H)** **Eff 8 Nov**


DNIPRO, UKRAINE
SID



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
2 NOV 18 **(10-3J)** **Eff 8 Nov**

DNIPRO, UKRAINE
SID



UKDD/DNK

DNIPROPETROVSK INTL



JEPPESSEN

2 NOV 18

10-3K


Eff 8 Nov

DNIPRO, UKRAINE


SID

Apt Elev
482'

Trans level: By ATC Trans alt: 10010'
If unable to comply SID procedures advise ATC.



RUBES 1A [RUBE1A]
TADID 4A [TADI4A]
UMSOT 3F [UMSO3F]
RWY 08 DEPARTURES



These SIDs require a minimum climb gradient of 4.5% up to 2470'.

Gnd speed-KT	75	100	150	200	250	300
4.5% V/V (fpm)	342	456	684	911	1139	1367

If unable to comply advise ATC.

FT/METER CONVERSION	
QNH	
2470' - 750m	
8040' - 2450m	
9030' - 2750m	
10010' - 3050m	

SID	ROUTING
RUBES 1A	On 082° track to D8.1 DNP, turn RIGHT, 240° track, turn LEFT, intercept DNP R-156 to RUBES.
TADID 4A	On 082° track to D8.1 DNP, turn RIGHT, 262° track, turn LEFT, intercept DNP R-218 to TADID.
UMSOT 3F	On 082° track to D8.1 DNP, turn RIGHT, 262° track, turn LEFT, intercept DNP R-208 to UMSOT.

UKDD/DNK

DNIPROPETROVSK INTL



JEPPESSEN

2 NOV 18

10-3L

Eff 8 Nov


DNIPRO, UKRAINE

SID


Apt Elev
482'

Trans level: By ATC Trans alt: 10010'
If unable to comply SID procedures advise ATC.

RUBES 1B [RUBE1B]
TADID 5B [TADI5B]
UMSOT 3Q [UMS03Q]
RWY 26 DEPARTURES



DNIPRO
D 112.5 DNP
N48 21.6 E035 06.2




These SIDs require a minimum climb gradient of 5.0% up to 2470'.

Gnd speed-KT	75	100	150	200	250	300
5.0% V/V (fpm)	380	506	760	1013	1266	1519

If unable to comply advise ATC.

FT/METER CONVERSION	
QNH	
2470'	- 750m
8040'	- 2450m
9030'	- 2750m
10010'	- 3050m



ROUTING

SID	ROUTING
RUBES 1B	On 262° track to D8.1 DNP, turn LEFT, 082° track, turn RIGHT, intercept DNP R-156 to RUBES.
TADID 5B	On 262° track to D8.1 DNP, turn LEFT, 165° track, turn RIGHT, intercept DNP R-218 to TADID.
UMSOT 3Q	On 262° track to D8.1 DNP, turn LEFT, 143° track, turn RIGHT, intercept DNP R-208 to UMSOT.

UKDD/DNK

Apt Elev **482'**
N48 21.4 E035 06.0

JEPPESSEN


2 NOV 18

(10-9)

Eff 8 Nov

DNIPRO, UKRAINE

DNIPROPETROVSK INTL



ADDITIONAL RUNWAY INFORMATION					
RWY			USABLE LENGTHS		
			Threshold	Glide Slope	
08	HIRL (60m) HIALS PAPI-L (angle 2.80°)	RVR		8283' 2525m	1
26	HIRL (60m) HIALS PAPI-L (angle 3.00°)	RVR		8526' 2599m	
					144' 44m


1 TAKE-OFF RUN AVAILABLE
<u>RWY 08:</u>
From rwy head 9377' (2858m)
twy 1 int 9022' (2750m)
twy 2 int 7710' (2350m)
<u>RWY 26:</u>
From rwy head 9377' (2858m)
twy 7 int 8169' (2490m)
twy 3 int 6562' (2000m)

HOT SPOT

(For information only, not to be construed as ATC instructions.)

HS Taxi carefully, traffic congestion.

JAR-OPS			
TAKE-OFF			
All Rwys			
LVP must be in force			
RCLM (DAY only) or RL		RCLM (DAY only) or RL	NIL (DAY only)
A	300m	400m	500m
B			
C			
D			



UKDD/DNK


JEPPESSEN
16 NOV 18 **10-9S**
Standard
DNIPRO, UKRAINE
DNIPROPETROVSK INTL

STRAIGHT-IN RWY	A	B	C	D
08				
ILS FULL ALS out	654' (200') R550m ① R1200m	654' (200') R550m ① R1200m	654' (200') R550m ① R1200m	654' (200') R550m ① R1200m
LOC ② ALS out	760' (306') R750m R1400m	760' (306') R750m R1400m	760' (306') R750m R1400m	760' (306') R750m R1400m
VOR ② ALS out	840' (386') R1100m R1500m	840' (386') R1100m R1500m	840' (386') R1100m R1800m	840' (386') R1100m R1800m
NDB ② with DME ALS out	850' (396') R1100m R1500m	850' (396') R1100m R1500m	850' (396') R1100m R1800m	850' (396') R1100m R1800m
NDB ② w/o DME ALS out	900' (446') R1400m R2100m	900' (446') R1400m R2100m	900' (446') R1400m R2100m	900' (446') R1400m R2100m
NDB w/o DME ALS out	900' (446') R1600m R2300m	900' (446') R1600m R2300m	900' (446') R1800m R2500m	900' (446') R1800m R2500m
26				
ILS FULL ALS out	673' (200') R550m ① R1200m	673' (200') R550m ① R1200m	673' (200') R550m ① R1200m	673' (200') R550m ① R1200m
LOC ② ALS out	780' (307') R750m R1400m	780' (307') R750m R1400m	780' (307') R750m R1400m	780' (307') R750m R1400m
VOR ② ALS out	870' (397') R1100m R1500m	870' (397') R1100m R1500m	890' (417') R1200m R1900m	910' (437') R1300m R2000m
NDB ② with DME ALS out	870' (397') R1100m R1500m	870' (397') R1100m R1500m	870' (397') R1100m R1800m	870' (397') R1100m R1800m
NDB ② w/o DME ALS out	990' (517') R1600m R2400m	990' (517') R1600m R2400m	990' (517') R1600m R2400m	990' (517') R1600m R2400m
NDB w/o DME ALS out	990' (517') R1800m R2600m	990' (517') R1800m R2600m	990' (517') R2000m R2800m	990' (517') R2000m R2800m

① W/o HUD/AP/FD: RVR 750m.

② Continuous Descent Final Approach.

CIRCLE-TO-LAND ③	100 KT	135 KT	180 KT	205 KT
After apch to rwy 08 ④	910' (456')	1070' (616')	1200' (746')	1500' (1046')
After apch to rwy 26 ⑤	910' (437')⑥ V1500m ⑦	1070' (597') V1600m ⑦	1200' (727') V2400m ⑦	1500' (1027') V3600m

③ Not authorized North of airport between R-280 and R-045 DNP.

④ Circling height based on rwy 08 thresh elev of 454'.

⑤ Circling height based on rwy 26 thresh elev of 473'.

⑥ after NDB apch: 990' (517').

⑦ or higher minimums of preceding straight-in approach.

UKDD/DNK



Standard
DNIPRO, UKRAINE
DNIPROPETROVSK INTL

TAKE-OFF RWY 08, 26			
	Low Visibility Take-off		
	Day: RL & RCLM Night: RL	Day: RL or RCLM Night: RL	Adequate vis ref (Day only)
A			
B	R300m	400m	500m
C			
D			

PANS OPS

JAR-OPS		STRAIGHT-IN LANDING RWY 26				CIRCLE-TO-LAND 1	
ILS		LOC (GS out)				Not authorized North of airport between R-280 and R-045	
DA(H) 673'(200')		MDA(H) 780'(307')					
FULL		ALS out		Max Kts		MDA(H) _____ VIS _____	
A	RVR 550m	RVR 1000m	RVR 900m	RVR 1500m	100	910'(437')	1500m
B			RVR 1000m		135	1070'(597')	1600m
C				RVR 1400m	RVR 1800m	180	1200'(727')
D					RVR 2000m	205	1500'(1027')

© JEPPESEN, 1998, 2018. ALL RIGHTS RESERVED.

UKDD/DNK
DNIPROPETROVSK INTL



JEPPESSEN
16 NOV 18 **(13-1)**

DNIPRO, UKRAINE
VOR Rwy 08

TM

BRIEFING STRIP

ATIS		DNIPRO Radar (APP)	DNIPRO Tower	DNIPRO Ground	2200 MSA DNP VOR
130.9 (Russian 134.9)		119.4	118.6	121.8	
VOR DNP 112.5	Final Apch Crs 077°	Minimum Alt D7.3 2470' (2016')	MDA(H) 840' (386')	Apt Elev 482' Rwy 454'	
MISSED APCH: Climb on 077° to 2470', then turn RIGHT to VOR climbing to 3940', then according to chart.					
Alt Set: hPa		Rwy Elev: 17 hPa	Trans level: By ATC		
DME required.					Trans alt: 10010'



Gnd speed-Kts	70	90	100	120	140	160
Descent Angle	2.86°	354	455	506	607	809
MAP at D1.6						

JAR-OPS				CIRCLE-TO-LAND 1			
STRAIGHT-IN LANDING RWY 08				Not authorized North of airport between R-280 and R-045			
MDA(H) 840' (386')							
ALS out							
A	RVR 900m	RVR 1500m		Max Kts	MDA(H)	VIS	
B	RVR 1000m	RVR 1500m		100	910' (456')	1500m	
C		RVR 1800m		135	1070' (616')	1600m	
D	RVR 1400m	RVR 2000m		180	1200' (746')	2400m	
				205	1500' (1046')	3600m	

1 Circling height based on rwy 08 thresh elev of 454'.



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
16 NOV 18 **(13-2)**

DNIPRO, UKRAINE
VOR Rwy 26

BRIEFING STRIP™

ATIS		DNIPRO Radar (APP)	DNIPRO Tower	DNIPRO Ground	2200 MSA DNP VOR
130.9 (Russian 134.9)		119.4	118.6	121.8	
VOR DNP 112.5	Final Aptch Crs 268°	Minimum Alt D6.6 2470' (1997')	MDA(H) Refer to Minimums	Apt Elev 482' Rwy 473'	
MISSED APCH: Climb on 268° to 2470', then turn LEFT to VOR climbing to 3940', then according to chart.					
DME required.	Alt Set: hPa	Rwy Elev: 17 hPa	Trans level: By ATC	Trans alt: 10010'	
Ground proximity warning system short term alerting is possible on final apch between 990' AMSL and 660' AMSL due to terrain.					



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI 2470' on 268°
Descent Angle 3.10°	384	494	548	658	768	878	
MAP at D1.5							

JAR-OPS

STRAIGHT-IN LANDING RWY 26

C: 890'(417')

MDA(H) AB: 870'(397') D: 910'(437')

CIRCLE-TO-LAND I

Not authorized North of airport between R-280 and R-045

		ALS out	Max Kts	MDA(H)	VIS
A	RVR 900m	RVR 1500m	100	910'(437')	1500m
B	RVR 1000m		135	1070'(597')	1600m
C		RVR 1800m	180	1200'(727')	2400m
D	RVR 1400m	RVR 2000m	205	1500'(1027')	3600m

PANS OPS

1

Circling height based on rwy 26 thresh elev of 473'.



UKDD/DNK
DNIPROPETROVSK INTL

JEPPESSEN
16 NOV 18 **(16-2)**

DNIPRO, UKRAINE
NDB Rwy 26

BRIEFING STRIP

ATIS 130.9 (Russian 134.9)	DNIPRO Radar (APP) 119.4	DNIPRO Tower 118.6	DNIPRO Ground 121.8
NDB DR 335	Final Apch Crs 262°	With DME Minimum Alt D6.6 2470' (1997')	With DME MDA(H) 870' (397')
		W/o DME Minimum Alt No FAF	W/o DME MDA(H) 990' (517')
		Apt Elev 482'	Rwy 473'
			2200
			MSA DNP VOR
MISSED APCH: Climb on 262° to 2470', then turn LEFT to VOR climbing to 3940', then according to chart.			
Alt Set: hPa	Rwy Elev: 17 hPa	Trans level: By ATC	Trans alt: 10010'
DME required for FAF determination.			
Ground proximity warning system short term alerting is possible on final apch between 990' AMSL and 660' AMSL due to terrain.			



Gnd speed-Kts	70	90	100	120	140	160
Descent Angle	3.00°	372	478	531	637	743
MAP at LMM						

JAR-OPS				STRAIGHT-IN LANDING RWY 26		CIRCLE-TO-LAND 1	
with DME		w/o DME		Not authorized North of airport between R-280 and R-045		Not authorized North of airport between R-280 and R-045	
MDA(H) 870' (397')		MDA(H) 990' (517')		Max Kts		MDA(H) VIS	
ALS out		ALS out		100		990' (517') 1500m	
A	RVR 900m	RVR 1500m	RVR 1000m	RVR 1500m		135	
B	RVR 1000m	RVR 1800m	RVR 1200m	RVR 2000m		180	
C	RVR 1400m	RVR 2000m	RVR 1600m	RVR 2000m		205	
D	RVR 1400m	RVR 2000m	RVR 1600m	RVR 2000m		205	

1 Circling height based on rwy 26 thresh elev of 473'.

Chart changes since cycle 08-2019

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
DNIPRO, (DNIPROPETROVSK INTL - UKDD)				

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport UKDD